



GENERAL NOTES:

1. ALL DIMENSIONS AND CC FIELD. ANY DISCREPANCY ATTENTION OF THE ENGINEER AFFECTED PART OF THE
2. THE STRUCTURE IS DESIGNED TO BE STABLE AFTER THE BUILDING CONTRACTOR'S SOLE RESPONSIBILITY PROCEDURES AND SEQUENCE OF THE STRUCTURE AND PERSONNEL THE ADDITION OF THE NEW TEMPORARY BRACING, GUARD RAILS SHALL REMAIN THROUGH THE COMPLETION OF THE PROJECT
3. ALL APPLICABLE FEDERAL AND STATE SMALL BE FOLLOWED, INCLUDING LABOR OCCUPATIONAL SAFETY AND HEALTH

STRUCTURAL DESIGN CRITERIA:

1. BUILDING CODE: 1999 EDITION INTERNATIONAL BUILDING CODE
2. DESIGN WIND LOADS - MAXIMUM DESIGN WIND SPEED 100 MPH BUILDING USE IMPORTANT BUILDING EXPOSURE CATEGORY B
3. SNOW: GROUND SNOW LOAD 30 PSF IMPORTANCE FACTOR 1.0 EXPOSURE FACTOR 1.0 FLAT ROOF SNOW
4. ROOF DEAD LOAD 15 PSF

WOOD FRAMING NOTES:

1. STRUCTURAL LUMBER: No Fb Fc
2. DESIGN CODE: NATIONAL DESIGN SPECIFICATION FOR WOOD CONSTRUCTION PRODUCTS AND MATERIALS
3. FASTENERS: COMPLY WITH THE REQUIREMENTS OF THE BOCA BUILDING CODE, UNLESS SHOWN OTHERWISE
4. SPIKE TOGETHER ALL FRAMED JOINTS USING MULTIPLE 2x LUMBER
5. PROVIDE PRESSURE TREATED LUMBER IN CONTACT WITH MASONRY OR CONCRETE

SECTION 1
SCALE: 1/4" = 1'-0"