



OFFICE HOURS
9 TO 12 M.
& 2 TO 5 P. M.

City of Portland.

OFFICE OF INSPECTOR OF BUILDINGS

5-13-13. 191

To the Inspector of Buildings of the City of Portland:

The undersigned respectfully makes application for a permit to erect enlarge a building on
Moody street, at number 49-51 to be
Three stories high Forty-four feet long Thirty
feet wide; also an addition to be stories high
feet long feet wide, and to be used as a Dwelling

CELLAR WALL—To be constructed of Concrete to be 16 inches wide on bottom and
batter to 12 inches on top.

UNDERPINNING—To be Brick height of underpinning from top of cellar wall to bottom of
all ft. inches to be 12 inches in thickness.

EXTERIOR WALLS—To be constructed of Wood If of Brick, Stone, etc. Total length of wall
it inches. Thickness of 1st 2d 3d 4th
5th 6th story walls. If of reinforced concrete state mix and reinforcing system
to be used.

If wood construction, sills to be 4-6" Girders 6-10"
Posts 4-6" Girts 4-6" Studs 2-4" to be spaced 16 in. on C"

This building will be used for the purposes of Dwelling (If for apartments,
tenements, or other family uses state number of families accommodated and number on each floor.
If for manufacturing or mercantile purposes state character of business and amount of estimated
weight to be carried by the floor.)

Number of families on floor One
Total number of families Three

Manufacturing (state character)

Estimated load on floors per sq. ft. 60 lbs

Mercantile business (state character and load per sq. ft.)

If building is used for tenement house or family use and more than one family, the following provisions
of the Building Laws regarding dividing partitions shall be adhered to (Quote Law re. this).

FIRESTOPS—All bearing and center partitions will have firestops cut in tight on top of each partition cap
and between each set of floor timbers. Where ledger boards are used there shall be firestops cut in
tight against bottom of ledger boards, of same size as wall studs. Also wherever the Inspector of
Buildings may consider necessary.

STAIRWAYS—No. in building Two location Front and Rear to be enclosed
with walls to be lathed with lathing.

ROOF—To be constructed of Wood Rafters to be 2-6 inches to be spaced 16
inches on centers. Roof to be covered with 8 ply Tar & Gravel

Gutters to be made of Cornices to be made of

Bay windows to be made of to be covered with

Corner Windows to be made of to be covered

Chimneys, Smoke flues to be lined with Blue Lining and provided with a 19 inch outside collar and an
inside collar to go to the inside of the flue.

Estimated Cost of Building \$5500

INSPECTION—The Inspector of Buildings is to be notified when building is ready for lathing and at least
24 hours before the lathing is begun.

The Builder is W. E. Littlejohn Address 72 Atlantic St.

The Architect is Address

The Owner is Dana H. Miles Address 50 Moody St.

No Deviation will be made from the above application without written permission from the Inspector of
Buildings.

The above petition was granted the 13 day of May 1913

All floor timbers to be 2-6 in. and to be spaced 16 in. on centers.

(Applicant to sign here W. E. Littlejohn