Inspections Division
Date: 01/31/18

INVERTER

SolarEdge Single Phase Inverters

for North America

SE3000H-US / SE3800H-US / SE5000H-US / SE6000H-US / SE7600H-US

Optimized installation with HD-Wave technology

- Specifically designed to work with power optimizers
- Record-breaking efficiency
- Fixed voltage inverter for longer strings
- Integrated Arc Fault protection and Rapid Shutdown for NEC 2014 and 2017, per article 690.11 and 690.12
- UL1741 SA certified, for CPUC Rule 21 grid compliance
- Extremely small and easy to install outdoors or indoors
- High reliability without any electrolytic capacitors
- Built-in module-level monitoring
- Optional: Revenue grade data, ANSI C12.20 Class 0.5 (0.5% accuracy)

Inspections Division
Date: 01/31/18

Single Phase Inverters for North America

SE3000H-US / SE3800H-US / SE5000H-US / SE6000H-US/ SE7600H-US

	SE3000H-US	SE3800H-US	SE5000H-US	SE6000H-US	SE7600H-US	
OUTPUT						
Rated AC Power Output	3000	3800	5000	6000	7600	VA
Max. AC Power Output	3000	3800	5000	6000	7600	VA
AC Output Voltage Min.-Nom.-Max. (183 - 208 - 229)	-	-	✓	-	-	Vac
AC Output Voltage Min.-Nom.-Max. (211 - 240 - 264)	✓	✓	✓	✓	✓	Vac
AC Frequency (Nominal)	59.3 - 60 - 60.5[1]					Hz
Maximum Continuous Output Current 208V	-	-	24	-	-	A
Maximum Continuous Output Current 240V	12.5	16	21	25	32	A
GFDI Threshold	1					A
Utility Monitoring, Islanding Protection, Country Configurable Thresholds	Yes					
INPUT						
Maximum DC Power	4650	5900	7750	9300	11800	W
Transformer-less, Ungrounded	Yes					
Maximum Input Voltage	480					Vdc
Nominal DC Input Voltage	380				400	Vdc
Maximum Input Current 208V [2]	-	-	13.5	-	-	Adc
Maximum Input Current 240V [2]	8.5	10.5	13.5	16.5	20	Adc
Max. Input Short Circuit Current	45					Adc
Reverse-Polarity Protection	Yes					
Ground-Fault Isolation Detection	600kΩ Sensitivity					
Maximum Inverter Efficiency	99	99.2				%
CEC Weighted Efficiency	99					%
Nighttime Power Consumption	< 2.5					W
ADDITIONAL FEATURES						
Supported Communication Interfaces	RS485, Ethernet, ZigBee (optional), Cellular (optional)					
Revenue Grade Data, ANSI C12.20	Optional[3]					
Rapid Shutdown - NEC 2014 and 2017 690.12	Automatic Rapid Shutdown upon AC Grid Disconnect					
STANDARD COMPLIANCE						
Safety	UL1741, UL1741 SA, UL1699B, CSA C22.2, Canadian AFCI according to T.I.L. M-07					
Grid Connection Standards	IEEE1547, Rule 21, Rule 14 (HI)					
Emissions	FCC Part 15 Class B					
INSTALLATION SPECIFICATIONS						
AC Output Conduit Size / AWG Range	0.75-1" Conduit / 14-6 AWG					
DC Input Conduit Size / # of Strings / AWG Range	0.75-1" Conduit / 1-2 strings / 14-6 AWG					
Dimensions with Safety Switch (HxWxD)	17.7 x 14.6 x 6.8 / 450 x 370 x 174					in / mm
Weight with Safety Switch	22 / 10		25.1 / 11.4	26.2 / 11.9		lb / kg
Noise	< 25				< 50	dBA
Cooling	Natural Convection				Natural convection and internal fan (user replaceable)	
Operating Temperature Range	-13 to +140 / -25 to +60[4] (-40˚F / -40˚C option)[5]					˚F / ˚C
Protection Rating	NEMA 3R (Inverter with Safety Switch)					

[1] For other regional settings please contact SolarEdge support
[2] A higher current source may be used; the inverter will limit its input current to the values stated
[3] Revenue grade inverter P/N: SExxxxH-US000NNC2
[4] Power de-rating from 50˚C
[5] -40 version P/N: SExxxxH-US000NNU4

RoHS

© SolarEdge Technologies, Inc. All rights reserved. SOLAREDGE, the SolarEdge logo, OPTIMIZED BY SOLAREDGE are trademarks or registered trademarks of SolarEdge Technologies, Inc. All other trademarks mentioned herein are trademarks of their respective owners. Date: 07/2017. V.01. Subject to change without notice.