COPYRIGHT: Reuse or reproduction of the contents of this document is not permitted without written permission of Structural Integrity Consulting Engineers Inc.

GENERAL STRUCTURAL NOTES

DESIGN LIVE LOADS: 2009 IBC/SBC/IEC, U.O.N

- Snow: 60 psf (Pg)
- Wind: 100 mph, exp B, 3 second gust
- Floor: 40 psf
- Elevated Parking Slab: 100 psf

FOUNDATIONS:

- Footings shall be placed on undisturbed natural soil or compacted fill tested and approved by soils engineer.
  - Minimum design soil pressure: 2,000 psf

BASEMENT WALLS:

- Design lateral soil pressure (equivalent fluid pressure)
  - Basement Walls: 45 pcf
- Backfill all retaining walls with free draining granular material except the top two feet.
- Provide perimeter drain system with invert minimum of 6" below bottom of basement slab. Extend perimeter drain to daylight or to sump.
- Slope perimeter grade away from building.
- Place concrete continuously without horizontal cold joints.
- Basement slab must be in place prior to backfilling, or provide adequate shoring and bracing.

CONCRETE AND REINFORCEMENT:

- Concrete shall conform to applicable provisions of ACI-301 and 318.
- Minimum 28 day compressive strength (f'c) as follows:

Footings:	3,000	psi
Walls:	4,000	psi w/4-6% air entrainment
Slabs:	4,000	psi w/4-6% air entrainment and fiber mesh

- Cement Type: I/II
- Deformed reinforcement: ASTM A615 grade 60, except bars specified to be field bent, stirrups, and ties which shall be grade 40.
- Fibermesh: 100% virgin polypropylene, fibrillated fibers as manufactured by Fibermesh Co. per ASTM C-1116 type III 4.1.3 and ASTM C-1116 performance level one, 1.5 lb. per cubic yard
- Welded Wire Fabric (WWF): ASTM A185. See also plan.
- Typical minimum foundation reinforcing: 2 #4 top and bottom, (except as noted) continuous at corners and steps
- Reinforcement shall be fabricated and placed per ACI Manual of Standard Practice (ACI-315). At splices, lap bars 30 diameters unless noted otherwise.
- Minimum 2 #4 around all floor sides of all openings, extend min. 2'-0 beyond openings.
- Concrete cover over reinforcing: 1½" for concrete placed against forms, 3" for concrete placed against earth. See also drawings.
- In continuous members, splice top bars at mid span and bottom bars over supports.
- Keep reinforcement clean and free of dirt, oil, and scale. Oil forms prior to placing reinforcement

STRUCTURAL STEEL

Angles, misc:	ASTM	A36
W shapes	ASTM	A992
HSS	ASTM	A500 GRADE B
Anchor Bolts.	ASTM	A36

- Expansion Anchors shall be ICC-ES approved, installed in accordance with manufacturers specifications.
  - In concrete: Wedge Type

WOOD FRAMING:

- Dimension Lumber is designed and shall be supplied using BASE VALUES Design Criteria.
- SPF #2 and better (Minimum Moisture Content 19%) U.O.N.
  - Plates: Sill plates: Pressure Treated SPF or Southern Pine.
  - "Pressure treated lumber" shall be framing material of the specified species which has been pressure treated with a decay and insect resistant solution, meeting all current standards for wood in contact with concrete or earth.
  - Sill plates in contact with masonry or concrete foundations, footings or slabs may be treated Timber Stand LSL (one borate treatment). Sodium borate treatment may also be acceptable for sill plate applications when protected from weather.
  - Acceptable treatment mediums for wood in contact with earth or in exterior applications include ACQ-C and ACQ-D (Alkaline Copper Quaternary) and copper azole (CBA-A and CBA-B).
  - DO NOT USE WOODS WHICH HAVE BEEN TREATED WITH AMMONIA BASED CARRIERS.
  - All connectors shall meet the recommendations of the pressure treated wood manufacturer, but shall be not less than Hot Dipped Galvanized meeting requirements of ASTM A653, such as Simpson ZMAX. (G185). All screws, nails and bolts shall match hangers and other connectors, and shall meet ASTM A123 for individual connectors, and ASTM A153 for fasteners
  - For durability, it is our recommendation that connectors used in exposed conditions with treated lumber be stainless steel.
  - Do not mix galvanized and stainless products.
  - Do not allow aluminum to contact treated wood.
  - Top and Bottom Plates, SPF No 2 and better
- Hem Fir Studs U.O.N. 2 x 4 and 2 x 6 to 8'-0: stud grade
  - 2 x 4 over 8'-0: standard and better
  - 2x 6 over 8'-0: No. 2 and better
- Laminated Veneer Lumber (LVL): Manufactured 1 3/4" wide Microllam (MLL) by Barrel/Trus Joist or equivalent. Fb=2600 psi, E=1,900,000 psi, Fv=285 psi, depth noted on plans.
- All plywood and oriented strand board (OSB) sheathing shall be engineered grades with APA grade stamp indicating appropriate maximum spacings of supports.
  - Floor sheathing: nominal ¾", APA Structural Floor "2.4" tongue & groove glued and nailed.
  - Wall sheathing: ½" Gypsum nailed or screwed (exterior). ½"/16" OSB nail base sheathed panel (exterior walls)
  - Roof sheathing: 19/32" OSB base sheathed panel, fastened w/ 8d@6" wood screw @ 12" OR 16ch at 4" max.
- Nail wall sheathing with 10d commons at 6" o.c. at panel edges, and 12" o.c. intermediate framing U.N.O. BLOCK AND NAIL ALL EDGES BETWEEN STUDS. Sheathing shall be continuous from bottom plate to top plate. Cut in "L" and "T" shapes around openings. Lap sheathing over rim joists min. 4" at all floors to tie upper and lower stud wall together. Maximum height of sheathing panels shall be 16" to assure that plates are tied to studs. Use minimum 3-8d per stud and nail plates with edge nail spacing.
- Sole plate at all perimeter walls and at designated shear walls shall be nailed at for braced panels with 3-16d x 3 1/2" face free nails (toenail or deformed shank) per 16" 12d nails are not acceptable.
- SHEATH ALL EXTERIOR WALLS.
- Maximum nailing shall comply with IBC Table 2304.9.1 except where more or larger nailing shown on drawings.
- All roof rafters, joists, beams shall be anchored to supports with metal framing anchors.
- Double joists under partitions where joists are parallel to partitions
- Provide continuous stud wall each side of wall openings equal to one half or greater of number of studs interrupted by openings.
- All wall studs shall be continuous from floor to floor or from floor to roof.
- Cross bridge all dimension lumber roof and floor joists at midspan and provide solid blocking at non joists at all joist supports and joist ends.
- Metal connectors: Simpson Strong Tie unless otherwise noted, installed with number and type of nails to achieve maximum rated capacity. Note that heavy duty and sheeted hangers may require special nails.
- All beams shall be braced against rotation at points of bearing.
- Drypack grout all beam pockets full after beams are set.
- Unless otherwise indicated, install two lengths of solid blocking x joist depth x 12 inches long at floor framing under column loads. Columns must have a continuous load path to foundations.
- Lead holes for lag bolts shall be 60% to 70% of lag shank diameter at compliance with AITC criteria.

STRUCTURAL ERECTION AND BRACING REQUIREMENTS

- The structural drawings illustrate the completed structure with all elements in their final positions, properly supported and braced. The contractor, in the proper sequence, shall provide proper shoring and bracing as may be required to achieve the final completed structure.
- These plans have been engineered for construction at one specific building site. Builder assumes ALL responsibility for use of these plans at Any Other building site. Plans shall not be used for construction at any other building site without specific review by the engineer.
- Openings in foundation, partitioning or framing required by the owner, lender, insurer, building department or any other party will be accomplished by the engineer at the owner's expense. At least 24 hours advance notice as requested.
- All slabs on grade shall be separated from adjacent structural and finish elements to allow free movement of the slab, unless specifically shown and noted otherwise.

ABBREVIATIONS KEY

AB	Anchor Rod (Bolt)	BF	Both Face	MACH	Machine	OC	On Center
ADDL	Additional	BJ	Expansion Joint	MATV	Masonry	OCM	Oil Control
ADJ	Adjustable	BLKG	Blocking	MATL	Material	OHDF	Oak Drifting Soil Tamping
AFF	Above Finished Floor	BLKG	Blanket (Thermal)	MAX	Maximum	OPNG	Opening
ALT	Alternate	BNDRY	Basement	MB	Machine bolt	OR	Opposite Hand
AMT	Amount	BO	Equal	MECH	Mechanical	OWF	Sheet
ANCH	Anchor, Anchorage	BOUND	Movement	MEPTC	Metal seam	OWPC	Sheathing
APPROX	Approximate	BOUNT	Expansion	MFR	Manufacturer, or, ed	PAR	Tensile
ARCH	Architect, -ural	BS	Both Side	MIN	Minimum	PLM	Sheet Log Horizontal
ATR	At Thread Rod	BTT	Bottom	ML	Microllam	PLV	Sheet Log Vertical
AVG	Average	B.W	Rust to West		(Trus-joist brand LVL)	POC	Slab on Grade
BC	Bottom of Concrete	BWC	Bitumen	MO	Masonry Opening	PP	Source
BL	Bush Ledge	BWP	Bituminous	MTL	Metal	PPBC	Specifications
BLK	Block	BWT	Exterior	NF	Near Face	PQ	Square
BLKG	Blocking	BWD	Foundation	NTC	Not In Contact	PT	Strap Plate
BM	Beam	BF	Far Face, Finished Floor	NS	Near Side	PTD	Standard
BOT	Bottom	F.B	Face to Face	N.S	Neoprene Sheath	QTRW	Staircase
BRG	Bearing	FCG	Fascia	NTS	Not to Scale	STL	Steel
BSF	Bottom of Steel	FL	Flush	OCL	OSHA Column Joint	STRUCT	Structure, -al
CB	Countersbore	FLG	Flange	OD	Outside Diameter	SUPT	Support
CF	Color Face	FLR	Floor	OF	Outside Face	SY	Source Yard
CG	Center of Gravity	FO	Face of	OH	Opposite Hand	SYM	Symmetrical
CIP	Cast in Place	FP	Full Penetration	OPNG	Opening	TCB	Top and Bottom
CJ	Construction Joint	FS	Far Side	OPP	Opposite	TEG	Tongue and Groove
	Control Joint	FTG	Footing	OSB	Oriented Strand Board	TB	Top of Beam
CLG	Ceiling	GA	Gage (Gauge)	PAF	Powder Actuated Fastn	TC	Top of Concrete
CLR	Clear	GALV	Galvanized	PC	Precast	TD	Top of Deck
CM	Construction Manager	GC	General Contractor	PCF	Pounds Per Cubic Foot	THD	Thread
	(Management)	GEN	General	PEN	Penetration	THK	Thick, -ness
CMU	Concrete Masonry Unit	GL	Glue laminated (Glulam)	PERP	Perpendicular	TJ	Top of Joist
COL	Column	GND	Ground	PL	Property Line	TL	Total Load
COM	Common	GR	Grade	PLF	Pounds per Linear Foot	TNG	Training
CONB	Combination	GT	Girder Truss	PNL	Panel	TRANS	Transverse
CONC	Concrete	GYP BD	Gypsum Board	PP	Panel Point	TW	Top of Wall
CONN	Connection	HAS	Headed Anchor Stud	PS	Prestressed	TYP	Typical
CONT	Continue (Continuous)	HORIZ	Horizontal	PSF	Pounds per Square Foot	UF	Ultimate
COORD	Coordinate, -tion	HT	Height	PSI	Pounds per Square Inch	UNO	Unless Noted Otherwise
CS	Countersink	ID	Inside Diameter	PSL	Parallel Strand Lumber	VERT	Vertical
CTR	Center	IF	Inside Face		(power brand)	VIF	Verify in Field
CY	Cubic Yard	INT	Interior (Intermediate)	PT (1)	Post Tensioned	WA	Window Awning
DAB	Deformed Anchor Bar	IN	Inch Bearing	PT (2)	Pressure Treated	WF	Wide Flange
DET	Detail	JST	Joist	PTN	Partition	WT	Wheels
DIAG	Diagonal	JT	Joint	PVMT	Pavement	WWM	Welded Wire Fabric
DIM	Dimension	K	Kip (1,000 lbs.)	QTY	Quantity	YS	Yield Strength
DL	Dead Load	LD	Load	R	Radius	YMAT	Construction
DN	Down	LL	Live Load	RB	Reference (refer to)	XTD	Double Bore Screw
DP	Drilled Pier	LLH	Long Leg Horizontal	RECT	Rectangle		
DT	Double Tee	LLV	Long Leg Vertical	REINF	Reinforce, -ed, -ing	(S)	Shimmy
DWG	Drawing	LOC	Location	REQ	Required	(S)	New
DWL	Dowel	LSL	Laminated Strand	RESIL	Resilient	(S)	Remove
EA	Each		Lumber (generic term)	RET	Retaining		
EC	Engineer	LT	Light	RM	Room		
EF	Each Face	LVL	Laminated Veneer	RMC	Rough Masonry Opening		
E.W	Each to West		Lumber (generic term)	RO	Rough Opening		



TYPICAL REINFORCING AT STEPS AND OPENINGS
NO SCALE



TYPICAL CONCRETE WALL INTERSECTIONS



TYPICAL JOINTS AT INTERIOR SLAB ON GRADE
NO SCALE

Structural Drawing Index

S1-0	General Notes, Etc.
S1-1	Foundation Plan
S1-2	Roof Framing Plan
S2-1	Sections

PROGRESS ONLY
NOT FOR CONSTRUCTION

Structural Integrity
Consulting Engineers
317 A Street
P.O. Box 1492
Belfast, Maine 04915
(207) 338-3450
(207) 338-3348
www.structuralintegrity.com
LICENSED MAINE & NEW HAMPSHIRE
SIE 14-0066

PROJECT NO. 14-0066
PROJECT NAME 218 Washington Ave Found.
Portland, Maine

ISSUE DATE 05.16.14
SHEET SCALE
SCALE
DRAWN BY MKL
SHEET TITLE GENERAL NOTES

S
S1-0