Reviewed for Code Compliance
Inspections Division
Approved with Conditions
Date: 08/26/14

# DOORS

DOOR NOTES:

1. EXTERIOR DOOR JAMBS TO BE SEALED TO THIER ROUGH OPENINGS USING LOW EXPANDING FOAM, BACKER ROD OR CAULKING.

2. ALL EXTERIOR DOORS TO BE WEATHER STRIPPED

3. ALL STOREFRONT DOORS AND FRAMES TO BE THERMALLY BROKEN WITH LOW -E ARGON FILLED INSULATED GLAZING UNITS

4. ALL GLAZING IN DOORS TO BE TEMPERED GLAZING

5. ALL HARDWARE TO BE ADA 'LEVER TYPE' HARDWARE UNLESS OTHERWISE NOTED

6. G.C. TO CONFIRM ALL DOOR SIZES WITH EXISTING OPENINGS

1 DOOR TYPES
1/4" = 1'-0"

## DOOR SCHEDULE

| DOOR | | | | | | | FRAME | | | | | GENERAL | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | SIZE | | | | | | | DETAILS | | | | | | |
| DOOR NO. | TYPE | WIDTH | HEIGHT | THICKNESS | MATERIAL | FINISH | INSULATED | TYPE | MATERIAL | THRESHOLD | HEAD | JAMB | SILL | CLOSER | FIRE RATING (MINUTES) | HARDWARE | REMARKS |
| 100.1 | A | 3'-0" | 7'-0" | 1-3/4" | AL | PTD | Y | - | AL | AL | - | - | - | Y | - | - | PANIC HARDWARE, STOREFRONT DOOR WITH SIDELIGHT, 1" DIAMETER 12" LONG PULL, ENLARGE FRAME HEAD AS REQUIRED TO FIT EXISTING OPENING |
| 100.2 | B | 3'-0" | 6'-8" | 1-3/4" | AL | PTD | Y | - | AL | AL | - | - | - | Y | - | - | PANIC HARDWARE, STOREFRONT DOOR, 1" DIAMETER 12" LONG PULL, CONFRIM DOOR SIZE WITH EXISITNG OPENING |
| 101.1 | C | 3'-0" | 7'-0" | 1-3/4" | STL | PTD | Y | 1 | STL | - | - | - | - | Y | - | - | |
| 102.1 | C | 3'-0" | 7'-0" | 1-3/4" | STL | PTD | Y | 1 | STL | - | - | - | - | Y | - | - | |
| 200.1 | B | 3'-0" | 7'-0" | 1-3/4" | AL | PTD | Y | - | AL | AL | - | - | - | Y | - | - | PANIC HARDWARE, STOREFRONT DOOR, 1" DIAMETER 12" LONG PULL, CONFRIM DOOR SIZE WITH EXISITNG OPENING, INFILL HEAD ABOVE FRAME WITH MTL FLASHING TO MATCH DOOR |
| 200.2 | D | 3'-0" | 7'-0" | 1-3/4" | STL | PTD | Y | 1 | STL | AL | - | - | - | Y | 60 | - | PANIC HARDWARE |
| 200.3 | K | 9'-0" | 8'-0" | 1-3/4" | STL | PTD | Y | - | - | - | - | - | - | Y | - | - | OVERHEAD DOOR, AUTOMATIC OPERATOR, CUT NEW MASORY OPENING |
| 201.1 | C | 3'-0" | 7'-0" | 1-3/4" | STL | PTD | Y | 1 | STL | - | - | - | - | Y | - | - | |
| 300.1 | B | 3'-0" | 7'-0" | 1-3/4" | AL | PTD | Y | - | AL | AL | - | - | - | Y | - | - | PANIC HARDWARE, STOREFRONT DOOR, 1" DIAMETER 12" LONG PULL, CONFRIM DOOR SIZE WITH EXISITNG OPENING, INFILL ADJACENT TO DOOR FRAME WITH FRAMING AND MTL FLASHING TO MATCH DOOR |
| 300.2 | D | 3'-0" | 7'-0" | 1-3/4" | STL | PTD | Y | 1 | STL | AL | - | - | - | Y | 60 | - | PANIC HARDWARE |
| 300.3 | F | 6'-0" | 7'-0" | 1-3/4" | AL | PTD | Y | - | AL | AL | - | - | - | Y | - | - | STOREFRONT DOORS, 1" DIAMETER 12" LONG PULL, CONFRIM DOOR SIZE WITH EXISITNG OPENING, PAIR OF DOORS |
| 301.1 | C | 3'-0" | 7'-0" | 1-3/4" | STL | PTD | Y | 1 | STL | - | - | - | - | Y | - | - | |
| 400.1 | B | 3'-0" | 7'-0" | 1-3/4" | AL | PTD | Y | - | AL | AL | - | - | - | Y | - | - | PANIC HARDWARE, STOREFRONT DOOR, 1" DIAMETER 12" LONG PULL, ADJUST MASONRY OPENING TO ACCOMMODATE 3'-0" DOOR, PROVIDE LINTEL |
| 400.2 | E | 12'-0" | 12'-0" | 1-3/4" | STL | PTD | Y | - | - | - | - | - | - | Y | - | - | OVERHEAD DOOR WITH INSULATED GLAZING PANELS, AUTOMATIC OPERATOR |
| 400.3 | F | 8'-0" | 8'-0" | 1-3/4" | AL | PTD | Y | - | AL | AL | - | - | - | Y | - | - | PANIC HARDWARE, STOREFRONT DOORS, 1" DIAMETER 12" LONG PULL, CONFRIM DOOR SIZE WITH EXISITNG OPENING, PAIR OF OVERSIZED DOORS |
| 401.1 | C | 3'-0" | 7'-0" | 1-3/4" | STL | PTD | Y | 1 | STL | - | - | - | - | Y | - | - | |
| 500.1 | D | 3'-0" | 7'-0" | 1-3/4" | STL | PTD | Y | 1 | STL | AL | - | - | - | Y | 60 | - | PANIC HARDWARE |
| 500.2 | D | 3'-0" | 7'-0" | 1-3/4" | STL | PTD | Y | 1 | STL | AL | - | - | - | Y | - | - | PANIC HARDWARE |
| 500.3 | G | 10'-0" | 8'-0" | 1-3/4" | STL | PTD | Y | - | - | - | - | - | - | Y | - | - | OVERHEAD DOOR, AUTOMATIC OPERATOR |
| 501.1 | C | 3'-0" | 7'-0" | 1-3/4" | STL | PTD | Y | 1 | STL | - | - | - | - | Y | - | - | |
| 502.1 | G | 10'-0" | 8'-0" | 1-3/4" | STL | PTD | Y | - | - | - | - | - | - | Y | - | - | OVERHEAD DOOR, AUTOMATIC OPERATOR (REPLACE IN FUTURE WITH FIRE RATED ROLL-UP DOOR IF SEPARATE TENANT LEASES SPACE) |
| 502.2 | D | 3'-0" | 7'-0" | 1-3/4" | STL | PTD | Y | 1 | STL | AL | - | - | - | Y | 60 | - | |
| 502.3 | H | 8'-0" | 8'-0" | 1-3/4" | STL | PTD | Y | - | - | - | - | - | - | Y | - | - | OVERHEAD DOOR, AUTOMATIC OPERATOR, CUSTOM SIZE DOOR OR INFILL HEAD AT OPENING WITH FRAMING AND FLASHING TO MATCH DOOR |
| 502.4 | H | 8'-0" | 8'-0" | 1-3/4" | STL | PTD | Y | - | - | - | - | - | - | Y | - | - | OVERHEAD DOOR, AUTOMATIC OPERATOR, CUSTOM SIZE DOOR OR INFILL HEAD AT OPENING WITH FRAMING AND FLASHING TO MATCH DOOR |
| 502.5 | H | 8'-0" | 8'-0" | 1-3/4" | STL | PTD | Y | - | - | - | - | - | - | Y | - | - | OVERHEAD DOOR, AUTOMATIC OPERATOR, CUSTOM SIZE DOOR OR INFILL HEAD AT OPENING WITH FRAMING AND FLASHING TO MATCH DOOR |
| 502.6 | B | 3'-0" | 7'-0" | 1-3/4" | AL | PTD | Y | - | AL | AL | - | - | - | Y | - | - | PANIC HARDWARE, STOREFRONT DOOR, 1" DIAMETER 12" LONG PULL, ADJUST MASONRY OPENING TO ACCOMMODATE 3'-0" DOOR, PROVIDE LINTEL |
| 502.7 | D | 3'-0" | 7'-0" | 1-3/4" | STL | PTD | Y | 1 | STL | AL | - | - | - | Y | 60 | - | |
| 502.8 | G | 10'-0" | 8'-0" | 1-3/4" | STL | PTD | Y | - | - | - | - | - | - | Y | - | - | OVERHEAD DOOR, AUTOMATIC OPERATOR (REPLACE IN FUTURE WITH FIRE RATED ROLL-UP DOOR IF SEPARATE TENANT LEASES SPACE) |
| 600.1 | I | 6'-0" | 8'-0" | 1-3/4" | AL | PTD | Y | - | AL | AL | - | - | - | Y | - | - | PANIC HARDWARE, PAIR OF STOREFRONT DOORS, TRANSOM ABOVE DOOR, CUSTOM MUNTINS ON DOORS |
| 600.2 | B | 3'-0" | 7'-0" | 1-3/4" | AL | PTD | Y | - | AL | AL | - | - | - | Y | - | - | PANIC HARDWARE, STOREFRONT DOOR, 1" DIAMETER 12" LONG PULL, CONFRIM EXISTING OPENING |
| 600.3 | D | 3'-0" | 7'-0" | 1-3/4" | STL | PTD | Y | 1 | STL | AL | - | - | - | Y | 60 | - | |
| 600.4 | C | 3'-0" | 7'-0" | 1-3/4" | STL | PTD | Y | 1 | STL | - | - | - | - | Y | - | - | |
| 600.5 | D | 3'-0" | 7'-0" | 1-3/4" | STL | PTD | Y | 1 | STL | AL | - | - | - | Y | 60 | - | PANIC HARDWARE |
| 700.1 | C | 3'-0" | 7'-0" | 1-3/4" | STL | PTD | Y | 1 | STL | AL | - | - | - | Y | 60 | - | PANIC HARDWARE |
| 800.1 | J | 3'-0" | 7'-0" | 1-3/4" | AL | PTD | Y | - | AL | AL | - | - | - | Y | - | - | PANIC HARDWARE, STOREFRONT DOOR WITH SIDELIGHT, 1" DIAMETER 12" LONG PULL, ENLARGE FRAME HEAD AS REQUIRED TO FIT EXISTING OPENING |

HARDWARE KEY
MLS - MORTISE LOCK SET
LS - LOCK SET
PR - PRIVACY SET
PS - PASSAGE SET
LP - LEVER PULL
PH - PEEPHOLE LENSE

ABBREVIATION KEY
STL - STEEL
WD - WOOD
AL - ALUMINUM
FRP - FIBERGLASS REINFORCED

REGISTERED ARCHITECT
RYAN J. SENATORE
No. 3322
STATE OF MAINE

© 2014 RYAN SENATORE ARCHITECTURE

RENOVATIONS TO
170 ANDERSON STREET
PORTLAND, MAINE

RSA
RYAN SENATORE
ARCHITECTURE
565 CONGRESS STREET
SUITE 304
PORTLAND, MAINE 04101
207-650-6414
senatorearchitecture.com

CONSULTANTS:
STRUCTURAL:
Structural Integrity
77 Oak Street
Portland, ME 04101
207-774-4614

REVISIONS:

| | |
|---|---|
| DATE: | MAY 09, 2014 |
| PROJECT No. | 1416 |
| DRAWN BY: | RJS / RRT |
| CHECKED BY: | RJS |
| SCALE: | AS NOTED |

SHEET TITLE:
DOOR SCHEDULE

A7-1