



## SECOND FLOOR FRAMING PLAN

1/4" = 1'-0"

**PLAN NOTES:**

- FLANGES AND WEBS OF STEEL BEAMS SHALL BE PUNCHED FOR ATTACHMENT OF WOOD MAILERS AND/OR BLOCKING, SEE DETAIL 2/S3.

ADD 1/2" SHEATHING TO INSIDE FACE OF WALL. NAILED w/ 0.131"  $\phi$  x 2 1/2" LONG NAILS AT 4" oc AT PANEL EDGES. SHEATHING SHALL BE INSTALLED ABOVE AND BELOW WINDOWS.

ISSUED FOR PERMIT REVIEW  
NOT FOR CONSTRUCTION.

<b>M<sup>2</sup> Structural Engineering P.C.</b> 23 Thornbury Way Windham, ME 04062 (207) 892-0983	<b>LAURA BALLADUR</b> 89 WALNUT STREET PORTLAND, ME		Drawn: MJM
	RENOVATIONS TO 89 WALNUT STREET PORTLAND, MAINE		Checked: MJM
Sheet: <b>S3</b>	Sheet Title: <b>SECOND FLOOR FRAMING PLAN</b>		Scale: AS NOTED
Project No.: 14016			Date: 04/07/2014