THIRD FLOOR REFLECTED CEILING PLAN

FOR APARTMENT UNIT CEILING INFORMATION SEE APARTMENT UNIT DETAIL SHEETS REFLECTED CEILING PLAN NOTES 1.) G.C. TO COORDINATE LOCATIONS OF PLUMBING CLEAN OUTS WITH ACCESS PANELS AS SHOWN ON REFLECTED CEILING PLANS 2.) G.C. TO PROVIDE ACCESS PANELS AS REQUIRED FOR ALL ELEMENTS (SPRINKLER, VALVES, ETC) NOT SHOWN ON THIS REFLECTED CEILING PLAN) 3.) G.C. TO PROVIDE METAL FRAMING AND BLOCKING REQUIRED FOR ALL ACCESS PANELS AND CONTROL JOINTS

SYMBOL TAG DESCRIPTION A TROSS IKEA SURFACE MOUNT B SURFACE MOUNTED - TBD C SURFACE MOUNT - IN CLOSETS D SURFACE MOUNTED ON WALL ABOVE DOOR EWALL SCONCE IN BATHROOM OVER VANITY ○ | F | SURFACE MOUNT - WET LOCATION H SURFACE MOUNT CENTER IN BEDROOMS O J RECESSED DOWN LIGHT - WET LOCATION △ K EXTERIOR CUT OFF DOWN LIGHT L RECESSED CAN LIGHT FIXTURE CEILING GRILLE

WALL FOR VALVE TO BE INSTALLED WITHIN
CABINETRY AND APPLIANCE ABBREVIATIONS
DB = DRAWER BASE
DRB = DOOR BASE
SB = SINK BASE
WC = WALL CABINET
WC(24) = WALL CABINET 24" DEEP
PU = PANTRY UNIT 24" DEEP
OS = OPEN SHELVES
RA = RANGE
DW = DISHWASHER
REF = REFRIGERATOR
REFLECTED CEILING PLAN AND LIGHTING LEGEND

WHICH IS PART OF THE RATED ASSEMBLY
10.) WHERE PLUMBING VALVES (TUB, SHOWER, ETC) ARE LOCATED IN FIRE RATED WALLS, PROVIDE FIRE RATED BOX IN

INSTALLATION9.) WHERE DROPPED SOFFITS AND CEILINGS ARE SHOWN, THESE ARE IN ADDITION TO THE FIRE RATED GWB CEILING ABOVE

7.) PROVIDE FIRE EXTINGUISHER ON BRACKET IN BASE CABINET BELOW KITCHEN SINK - TYPICAL
8.) HANG HOT WATER HEARER FROM CEILING ABOVE CLOTHES ROD IN CLOSET, PROVIDE UNISTRUT SUPPORTS ON TOP OF BOTTOM CHORDS OF TRUSSES PRIOR TO CEILING

ADDITIONAL INFORMATION REGARDING, LIGHTING, DIFFUSERS, ETC.

CEILINGS IN BATHROOMS TYPICAL 5.) SET ALL CLOTHES WASHERS IN PANS WITH WATER SENSOR 6.) REFER TO ELECTRICAL AND MECHANICAL DRAWINGS FOR

GRAB BARS TO BE PROVIDED IN WALLS OF BATHROOMS IN ALL UNITS 4.) PROVIDE MOISTURE RESISTANT GWB AT ALL WALLS AND

G.C. TO CONFRIM AND COORDINATE ALL CABINETRY AND APPLIANCES DIMENSIONS 3.) PROVIDE APPROPRIATE BLOCKING IN WALLS BEHIND ALL FIXTURES, PARTITIONS AND ACCESSORIES. BLOCKING FOR

 DEPICT ONE FLOOR ONLY, FOR HEIGHT INFORMATION REFER TO BUILDING SECTIONS AND WALL SECTIONS
 2.) G.C. TO CONFRIM AND COORDINATE ALL ROUGH FRAMING DIMENSIONS FOR TUBS, SHOWERS, BUILT-IN FIXTURES ETC.

1.) CEILING HEIGHTS, WINDOW HEAD AND SILL HEIGHTS VARY FROM FLOOR TO FLOOR, INTERIOR ELEVATIONS GRAPHICALLY DEPICT ONE FLOOR ONLY, FOR HEIGHT INFORMATION REFER

UNIT NOTES

