Reviewed for Code Compliance
Inspection Division
Portland, Maine
Date: 03/21/17

LEGEND:
T = TEMPERED GLASS
F = FIXED
STN = STAINED
PTD = PAINTED
ANO = ANNODIZED
AL = ALUMINUM
STL = STEEL

DOOR NOTES:

1.) ALL EXTERIOR GLAZING TO BE LOW-E ARGON FILLED INSULATED GLAZING UNITS
2.) FRAME ALL OPENINGS WITH ELEVATIONS
3.) SEAL EXTERIOR DOORS TO ROUGH OPENING WITH LOW EXPANDING FOAM INSULATION - SEE DETAILS
4.) ALL DOOR HARDWARE TO BE 'LEVER' TYPE
5.) ALL EXTERIOR DOORS TO BE WEATHERSTRIPPED

1 DOOR TYPES
1/4" = 1'-0"

FRAME TYPES:

GLAZING SCHEDULE

KEY	GLAZING TYPE
GL-1	INSULATED CLEAR TEMPERED GLAZING
GL-2	FIRE RATED INSULATED GLAZING
GL-3	CLEAR TEMPERED GLASS
GL-4	CLEAR INSULATED TEMPERED GLASS
GL-5	FIRE RATED GLAZING

DOOR SCHEDULE

DOOR								FRAME						GENERAL			
		SIZE									DETAILS						
DOOR NO.	TYPE	WIDTH	HEIGHT	THICKNESS	MATERIAL	FINISH	INSULATED	TYPE	MATERIAL	THRESHOLD	HEAD	JAMB	SILL	CLOSER	FIRE RATING (MINUTES)		REMARKS
100,1	C	3'-0'	7'-0"	1-3/4"	STL	PTD	Y	2	STL	AL	-	-	-	Y	-	-	THERMALLY BROKEN STEEL DOOR WITH PANIC HARDWARE
110,1	A	3'-0'	7'-0"	1-3/4"	AL	ANO	Y	-	AL	AL	-	-	-	Y	-	-	THERMALLY BROKEN STOREFRONT DOOR WITH PANIC HARDWARE
110,2	D	7'-8"	8'-0"	1-3/4"	AL	ANO	Y	-	AL		-	-	-	-	-	-	OVERHEAD DOOR, BY OVERHEAD DOOR, 521 SERIES (OR EQUAL), FINISH TO MATCH ADJACENT STOREFRONT
111,1	B	3'-0"	7'-0"	1-3/4"	WD	STN	-	2	STL	-	-	-	-	Y	-	-	
112,1	B	3'-0"	7'-0"	1-3/4"	WD	STN	-	2	STL	-	-	-	-	Y	-	-	
120,1	A	3'-0'	7'-0"	1-3/4"	AL	ANO	Y	-	AL	AL	-	-	-	Y	-	-	THERMALLY BROKEN STOREFRONT DOOR WITH PANIC HARDWARE
120,2	A	3'-0'	7'-0"	1-3/4"	AL	ANO	Y	-	AL	AL	-	-	-	Y	-	-	THERMALLY BROKEN STOREFRONT DOOR WITH PANIC HARDWARE
120,3	E	6'-0'	7'-0"	1-3/4"	STL	PTD	Y	2	STL	-	-	-	-	Y	60	-	FIRE RATED DOOR
121,1	C	3'-0'	7'-0"	1-3/4"	STL	PTD	Y	2	STL	AL	-	-	-	Y	-	-	THERMALLY BROKEN STEEL DOOR WITH PANIC HARDWARE
122,1	B	3'-0"	7'-0"	1-3/4"	WD	STN	-	2	STL	-	-	-	-	Y	-	-	
123,1	B	3'-0"	7'-0"	1-3/4"	WD	STN	-	2	STL	-	-	-	-	Y	-	-	
124,1	E	6'-0'	7'-0"	1-3/4"	STL	PTD	Y	2	STL	-	-	-	-	Y	60	-	
140,1	B	3'-0'	7'-0"	1-3/4"	STL	PTD	Y	2	STL	AL	-	-	-	Y	60	-	FIRE DOOR WITH PANIC HARDWARE

HARDWARE KEY
MLS - MORTISE LOCK SET
LS - LOCK SET
PR - PRIVACY SET
PS - PASSAGE SET
LP - LEVER PULL
PH - PEEPHOLE LENSE

NOTE: FOR DOOR HARDWARE SEE DOOR HARDWARE SPECIFICATION SECTION 08710

REGISTERED ARCHITECT
RYAN J. SENATORE
No. 3322
STATE OF MAINE

© 2016 RYAN SENATORE ARCHITECTURE

123 WASHINGTON

123 WASHINGTON AVENUE
PORTLAND, MAINE

RSA
RYAN SENATORE
ARCHITECTURE
565 CONGRESS STREET
PORTLAND, MAINE 04101
207-650-6414
senatorearchitecture.com

CONSULTANTS:

REVISIONS:

DATE: DECEMBER 05, 2016
PROJECT No. 1638
DRAWN BY: JPF
CHECKED BY: RJS
SCALE: AS NOTED

SHEET TITLE:
DOOR SCHEDULE

A7-0