


NOTE:
CONTRACTOR TO CARRY AN ALLOWANCE FOR (4) BEAM PENETRATIONS TO BE MADE AFTER STEEL ERECTION. CONTRACTOR SHALL NOT PERFORM ANY BEAM PENETRATIONS WITHOUT SPECIFIC APPROVAL FROM EOR

FLOOR FRAMING IS NOT CONTINUOUS OVER INTERIOR DEMISING/ BEARING WALLS -TYP. SEE ARCH AND SECTIONS FOR ADDITIONAL INFORMATION

TRUSS MANUFACTURER/ DESIGNER TO LAY OUT TRUSSES TO UTILIZE BEARING WALLS BELOW AS INDICATED. -TYP


LAYOUT TRUSSES TO AVOID PLUMBING PENETRATIONS ETC. -TYP

FRAMING PLAN SYMBOLS KEY	
(Symbol)	W/2x10
(Symbol)	W/2x12
(Symbol)	W/2x14
(Symbol)	W/2x16
(Symbol)	W/2x18
(Symbol)	W/2x20
(Symbol)	W/2x22
(Symbol)	W/2x24
(Symbol)	W/2x26
(Symbol)	W/2x28
(Symbol)	W/2x30
(Symbol)	W/2x32
(Symbol)	W/2x34
(Symbol)	W/2x36
(Symbol)	W/2x38
(Symbol)	W/2x40
(Symbol)	W/2x42
(Symbol)	W/2x44
(Symbol)	W/2x46
(Symbol)	W/2x48
(Symbol)	W/2x50
(Symbol)	W/2x52
(Symbol)	W/2x54
(Symbol)	W/2x56
(Symbol)	W/2x58
(Symbol)	W/2x60
(Symbol)	W/2x62
(Symbol)	W/2x64
(Symbol)	W/2x66
(Symbol)	W/2x68
(Symbol)	W/2x70
(Symbol)	W/2x72
(Symbol)	W/2x74
(Symbol)	W/2x76
(Symbol)	W/2x78
(Symbol)	W/2x80
(Symbol)	W/2x82
(Symbol)	W/2x84
(Symbol)	W/2x86
(Symbol)	W/2x88
(Symbol)	W/2x90
(Symbol)	W/2x92
(Symbol)	W/2x94
(Symbol)	W/2x96
(Symbol)	W/2x98
(Symbol)	W/2x100



FOURTH FLOOR / LOW ROOF FRAMING PLAN

- NOTES:
- SEE SHEET S-1.0 FOR GENERAL STRUCTURAL NOTES
 - ALL WOOD COLUMNS IN 2x6 WALLS SHALL BE 3-2x6 AND IN 2x4 WALLS SHALL BE 3-2x4 UNLESS NOTED OTHERWISE ON PLANS
 - ALL BEAMS ARE FLUSH, UNO
 - ALL HEADERS IN INTERIOR 2x BEARING WALLS ARE 2-2x8, UNO
 - ALL HEADERS IN EXTERIOR 2x BEARING WALLS ARE 3-2x8, UNO
 - ALL FLOOR JOISTS TO BE 14\"/>



FRAMING KEY

(Symbol)	INDICATES DROPPED BEAM -TYP UNO
(Symbol)	INDICATES FLUSH TOP BEAM -TYP UNO
(Symbol)	INDICATES DIAGONAL STL BRACE BELOW
(Symbol)	INDICATES W14x53 DRAG STRUT W/ 3/4\"/>

