



Exterior downlight at street level facade on Sheridan Street

Item Code: SON-ANGLED-PLANE-NAR-DNLT-OTDR-LED-W-SCE  
Description: **Material(s):** Metal

**Dimensions:**

- Overall: 4"W X 7.75"H X 2.25" extension
- Backplate: 2.5"W X 5.25"H

**Lamp Type:** LED

**Bulbs:** 1 X 10W 120V LED array, 90 CRI, 3000K, 420 lumens (included)

**Listing:** ADA, WET-LOCATION

Price: Now: \$229.50  
Compare: \$270.00  
+ Free Shipping

Options: **Finish:**

- Gray
- Bronze
- White

The Angled Plane Narrow Downlight Outdoor LED Wall Sconce reflects downward LED illumination for outdoor applications, and can also be used as an uplight fixture for indoor use. Its clean and minimal design is ideal for most modern interiors and exteriors.

Offered in three textured finishes: gray, bronze and white, the Angled Plane is a minimal and stylish addition to modern indoor and outdoor spaces. Dimmable with an electronic low voltage or standard TRIAC dimmer (sold separately). LED driver located in outlet box. ADA compliant. Shown in gray.

If you have questions, call (866) 428 9289

Exterior light at all exterior decks adjacent to door at 7'-0" above finished deck level

Project: \_\_\_\_\_  
 Fixture Type: \_\_\_\_\_  
 Location: \_\_\_\_\_  
 Contact: \_\_\_\_\_

# P5674 SERIES

LED Wall Mount • Wet Location



## Specifications:

### Description:

The P5674 Series are ideal for a wide variety of interior and exterior applications including residential and commercial. The Cylinders feature a 120V alternating current source and eliminates the need for a traditional LED driver. This modular approach results in an encapsulated luminaire that unites performance, cost and safety benefits.

### Construction:

- Powdercoated Antique Bronze (-20), White (-30), Black (-31), Metallic Gray (-82)
- Die-cast aluminum construction
- Flicker-free dimming to 10% brightness with many ELV type dimmers (See Dimming Notes)
- Covers a standard 4" recessed outlet box
- Mounting strap for outlet box included

### Performance:

Number of Modules	1
Input Power	17W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	1000/58 (LM-79) per module
CCT	3000K
CRI	90
Life	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	5 yrs.
Labels	cCSAus certified for wet locations

## P5674-30/30K


### Images:



### Dimensions:

A	B
5"	7-1/2"

Extends H/CTR	
8"	2.5



### Catalog number:

Base	Finish	Color Temp	CRI
P5674	20 - Antique Bronze	30K - 3000K	90 CRI
	30 - White		
	31 - Black		
	82 - Metallic Gray		

## P5674-30/30K

### Dimming Notes:

---

P5674 is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls:

### Electronic Low Voltage ELV Reverse Phase Controls

Lutron	Diva Series	(Part Number DVELV-300)
Lutron	Nova T Series	(Part Number NTELV-300)
Lutron	Vierti Series	(Part Number VTELV-600)
Lutron		(Part Number MAELV-600)
Lutron		(Part Number SPELV-600)
Leviton		(Part Number AWRMG-EAW)

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.