					F	PERN	AIT IS	SUED			
City of Portland, Maine - Bui	lding or Use	Permi	t Application	n Pe	mit N	į.	Issue I	- 1		CBL:	
389 Congress Street, 04101 Tel: (	207) 874-8703, Fax: (207) 874-8°			6	01	-0599	JN 6	2001		013 F0	07001
Location of Construction:	Owner Name:			Owner Address:				Phone:			
30 Washington Ave	Seavey Timothy E &			Po Box 7411 Portland, Me 041				-04 M		207-878-	0187
Business Name:	Contractor Name:			Contractor Address: Phone							
Al-hila meat and general grocery	no contractor/self			n/a n/a							T
Lessee/Buyer's Name Ardinoor- Hassan	Phone: 207-878-0187			Permit Type: Signs - Permanent					B2b		
				Permit Fee: Cost of Work:					CEO District:		
Past Use: Furniture store. Change of use done	Proposed Use: grocery store/restaurant SIGNAGE		Perm	it Fee:		Cost of V	vork: \$0.00	CEU	District:		
01-0248								d INSPI	ECTIO	DN: 914 1	1411
				Denied				Use C	Use Group: Type:		
							1.	A PEPMIT ISSUED			
	<u> </u>							100		1190 [1	441
Proposed Project Description: signage 4' x 4' attached to building				Cianat	f			s: Z	21	1 1 71	
signage + X + attached to building				Signature: PEDESTRIAN ACTIVITIES DISTRIBUTED DISTRIBUT			ISTRICT	7 X	1/1/	7	
				Action		Appro		Approved	w/Con	ditions	Denied
				Signat	ture:				Dat	e:	
Permit Taken By: Date A <sub>1</sub>	oplied For:	Zo			Zoning Approval						
jodinea 05/3	1/2001										
<ol> <li>This permit application does not preclude the Applicant(s) from meeting applicable State and Federal Rules.</li> <li>Building permits do not include plumbing, septic or electrical work.</li> </ol>		Special Zone or Reviews		ws	ws Zoning Appeal			Historic Preservation			
		Shoreland			☐ Variance				Not in District or Landniar		
		□ w	Miscellaneous				Does Not Require Review				
3. Building permits are void if work is not started within six (6) months of the date of issuance. False information may invalidate a building permit and stop all work		☐ Flood Zone			Conditional Use				Requires Review		
		☐ Su	Interpretation				Approved				
		Sit	te Plan			Approv	ed			Approved w/	Conditions
		Maj [	Minor May			Denied				Denied (	$\nearrow$
		Date:	OKTA	<u>/</u>	Ilate:				Date:		
			(a) (v)	\				W	PEF ITH	RMIT ISS REQUIRÍ	EMENTS
I hereby certify that I am the owner of I have been authorized by the owner to jurisdiction. In addition, if a permit for shall have the authority to enter all are such permit.	make this appli r work describe	med pro ication a d in the	as his authorized application is is	ne prop l agent sued,	t and I	<b>I</b> agree ify that	to conforthe code	rm to all a official's	applic autho	cable laws orized repr	of this resentative
SIGNATURE <b>OF</b> APPLICANT			ADDRESS	<u> </u>			DA	TE.		PHC	NE

RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE

DATE

PHONE

2/13/03 0K

## SIGNAGE PRE-APPLICATION

PLEASE ANSWER ALL QUESTIONS
ADDRESS: 30 Washington AVR. ZONE: 5-20
OWNER: KONSTANDED HOSSON TIMOThy Seally
APPLICANT: KOSSIA ARDINOOR HOSSON
ASSESSOR NO
PLEASE CIRCLE APPROPRIATE ANSWER
SINGLETENANTLOT? YES NO  FREESTANDING SIGN? (ex. Pole Sign) YES NO DIMENSIONS 4 4 HEIGHT 4  MORE THAN ONE SIGN? YES NO DIMENSIONS 4 HEIGHT 4  SIGNATTACHED TO BLDG.? YES NO DIMENSIONS  MORE THAN ONE SIGN? YES NO DIMENSIONS  AWNING: YES NO IS AWNING BACKLIT? YES NO HEIGHT OFF SIDEWALK  IS THERE ANY MESSAGE, TRADEMARK OR SYMBOL ON IT?  LISTALL EXISTING SIGNAGE AND THEIR DIMENSIONS:
*** TENANT BLDG. FRONTAGE (IN FEET): 30 0 17 - 60 MAX  *** REQUIRED INFORMATION  AREA FOR COMPUTATION

## **YOU SHALL PROVIDE:**

A SITE SKETCH AND BUILDING SKETCH SHOWING EXACTLY WHERE EXISTING AND NEW SIGNAGE IS LOCATED MUST BE PROVIDED. SKETCHES AND/OR PICTURES OF PROPOSED ARE ALSO REQUIRED.

SIGNATURE OF APPLICANT: DATE:

01.0599

## THIS IS NOT A PERMIT/CONSTRUCTION MAY NOT COMMENCE UNTIL THE **PERMIT IS ISSUED**

## **SIGNAGE APPLICATION**

THIS IS NOT A PERMIT
CONSTRUCTION CANNOT NOT COMMENCE UNTIL THE PERMIT IS ISSUED

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

If you or the property owner owes real estate or personal property taxes or user charges on any property within the City, payment arrangements must be made before permits of any kind are accepted.

<u>-</u>						
Location/Address of Construction: 30	Heshing	ston Ave.				
Total Square Footage of Proposed Structur	Square Footage of Lot					
Tax Assessor's Chart, Block & Lot Number  Chart# 013 Block# F Lot# W	Owner:			Telephone #:  C76-0167		
Lessee/Buyer's Name (If Applicable)  Cossin ABDINOOR-HASSAN  Owner's/Purchaser/Lessee Address:  TIMOTHY Seally				Total s.f of signs しんx.20 \$ ろんり, plus \$30.00		
Current use: Was furniture store. Proposed use: Grand Proposed use						
Applicants Name, Address & Telephone:  240 #6	ndy: <b>K@</b> S	Sin	IA			
If you would like it mailed, what mailing ad	dress should	we use:		5/25		
				Rec'd By: CH		

# THIS IS NOT A PERMITKONSTRUCTION MAY NOT COMMENCE UNTIL THE PERMIT IS ISSUED

If the property is located in a HISTORIC DISTRICT, a separate sketch is required indicating the design, dimensions, construction materials and source of illumination if any. A photograph of the building façade should be submitted, showing where each sign is to be installed.

## Certification

I hereby certify that I am the Owner of record of the named property, or that the owner of record authorizes the proposed work and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued, I certify that the Code Official's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to enforce the provisions of the codes applicable to this permit.

	, <b>/</b> '
Signature of applicant:	Date: 5/25/01

Sign Permit Fee: \$30.00 plus \$0.20 per square foot.

A building permit is also required for any awning based on cost of work-\$30.00 for the first \$1,000.00 and \$6.00 for each additional \$1,000.00

BY FILLING OUT THIS APPLICATION IS DOES NOT MEET THAT YOU WILL BE APPROVED FOR THE AMOUNT OF SIGNAGE YOU ARE APPLYING FOR

IT IS SUGGESTED THAT YOU DO NOT ORDER ANY SIGNAGE UNTIL YOU HAVE RECEIVED YOUR SIGN PERMIT THAT HAS BEEN SIGNED BY THE BUILDING, ZONING AND POSSIBLE HISTORICAL OFFICIALS OF THIS OFFICE

### **BUILDING PERMIT REPORT**

DATE: 27 MAY 200/ ADDRESS: 30 Washing Ton Ave. CBL: \$13-5-607
REASON FOR PERMIT: $2/2$ $na q p$ .
BUILDING OWNER: Tracky Seavey
PERMIT APPLICANT: /CONTRACTOR / A SSIVE, Abeliagor, Hass
USE GROW: Signal Construction type:
The City's Adopted Building Code (The BOCA National Building Code/1999 with City Amendments) The City's Adopted Mechanical Code (The BOCA National Mechanical Code/1993)
CONDITION(S) OF OVA
This permit is being issued with the understanding that the following conditions shall be met: $\frac{\times}{/}$ $\frac{\times}{3}$ $\frac{\times}{3}$

¥1.

This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.

- 2. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained (A 24 hour notice is required prior to inspection) "ALL LOT LINES SHALL BE CLEARLY MARKED BEFORE CALLING."
- 3. Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that **passes** through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2
- **4.** Foundations anchors shall be a minimum of ½" in diameter, 7" into the foundation wall, minimum of 12" from comers of foundation and a maximum 6' O.C. between bolts. Section 2305.17
- **5.** Waterproofing and dampproofing shall be done in accordance with <u>Section 1813.0</u> of the building code.
- 6. Precaution must be taken to protect concrete and masonry. Concrete Sections 1908.9-19.8.10/ Masonry Sections 21 11.3-2111.4.
- 7. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed This is done to verify that the proper setbacks are maintained.
- 8. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than I-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4, Section 407.0 of the BOCA/1999)
- All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993). Chapter 12 & NFPA 21 1
- 10. Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building Code.
- 11. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42". In occupancies in Use Group A, B.H-4, I-1, I-2, M, R, public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. Handrails shall be a minimum of 31" but not more than 38". Exception: Handrails that form part of a guard shall have a height not less than 36 inches (914 mm) and not more than 42 inches (1067 mm). Handrail grip size shall have a circular cross section with an outside diameter of at least 1 ¼" and not greater than 2". (Sections 1021 & 1022.0). Handrails shall be on both sides of stairway. (Section 1014.7)
- 12. Headroom in habitable space is a minimum of 7'6". (Section 1204.0)
- 13. Stair construction in <u>Use Group R-3 & R-4 is a minimum of 10" tread and 7½" maximum rise.</u> All other Use Group minimum 11" tread, 7" maximum rise. (Section 1014.0)
- 14. The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4
- 15. The Minimum required width of a corridor shall be determined by the most restrictive of the criteria under section 1011.3 but not less then 36".
- 16. Every sleeping room below the fourth story in buildings of Use Groups Rand I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (I 118mm) above the floor. All egress or rescue windows from steeping remains and in the ammunitarity of the minimum net clear opening width dimension shall be 20 inches (508)mm, and a minimum net clear opening of 5.7 sq. ft. (Section 1010.4)
- 17. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)
- **18.** All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closure's. (Over 3 stories in height requirements for fire rating is two (2) hours. (Section 710.0)
- 19. The boiler shall be protected by enclosing with (1) hour fire rated construction including fire doors and ceiling, or by providing automatic extinguishment. (Table 302.1.1)

5/3/

- 20. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1999), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
  - In the immediate vicinity of bedrooms
  - In all bedrooms
  - In each story within a dwelling unit, including basements
- 21. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. (Section 921.0)
- 22. The Fire Alarm System shall be installed and maintained to NFPA #72 Standard
- 23. The Sprinkler System shall be installed and maintained to NFPA #13 Standard.
- 24. All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 of the 'City's Building Code. (The BOCA National Building Code/1999)
- 25. Section 25 135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- 26. The builder of a facility to which Section 4594-C of the Maine State Human **Rights** Act Title **5** MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection Services.
- 27. Ventilation and access shall meet the requirements of Chapter 12 Sections 1210.0 and 1211.0 of the City's Building Code. (Crawl spaces & attics).
- **28.** All electrical, plumbing and HVAC permits must be obtained by Master Licensed holders of their trade. No closing in of walls until all electrical (min. 72 hours notice) and plumbing inspections have been done.
- 29. All requirements must be met before a final Certificate of Occupancy is issued.
- **30.** All building elements shall meet the fastening schedule **as** per Table **2305.2** of the City's Building Code (The BOCA National Building Code/1996).
- 31. Ventilation of spaces within a building shall be done in accordance with the City's Mechanical code (The BOCA National Mechanical Code/1993). (Chapter M-16)
- **32.** Please read and implement the attached Land Use Zoning report requirements.
- 33. Boring, cutting and notching shall be done in accordance with Sections 2305.3, 2305.3.1, 2305.4.4 and 2305.5.1 of the City's Building Code.
- **34.** Bridging shall comply with Section 2305.16.
- 35. Glass and glazing shall meet the requirements of Chapter 24 of the building code. (Safety Glazing Section 2406.0)
- **36.** All flashing shall comply with Section 1406.3.10.

_37.	All signage shall be done in accordance with Section 3102.0 signs of the City's Building Code, (The BOCA National Building Code/1999).

P Samuel Helfses, Building Inspector Cc: Lt. McDougall, PFD

Marge Sehmuckal. Zoning Administrator Michael Nugent, Inspection Service Manager

PSH 10/1/00

\*\*This permit is herewith issued, on the basis of plans submitted and conditions placed on these plans, any deviations shall require a separate approval.

\*\*\*THISPERMIT HAS BEEN ISSUED WITH THE UNDERSTANDING THAT ALL THE CONDITIONS OF THE APPROVAL SHALL BE COMPLETED. THEREFORE, BEFORE THE WORK IS COMPLETED A REVISED PLAN OR STATEMENT FROM THE PERMIT HOLDER SHALL BE SUBMITTED TO THIS OFFICE SHOWING OR EXPLAINING THAT THE CONDITIONS HAVE BEEN MET. IF THIS REQUIREMENT IS NOT RECEIVED YOUR CERTIFICATE OF OCCUPANCY SHALL BE WITHHELD. (You Shall Call for Inspections)

\*\*\*\*ALL PLANS THAT REQUIRE A PROFESSIONAL DESIGNER'S SEAL, (AS PER SECTION 114.0 OF THE BUILDING CODE) SHALL ALSO RE PRESENTED TO THIS DIVISION ON AUTO CAD LT. 2000, DXF FORMAT OK EQUIVALENT.

\*\*\*\*\*CERTIFICATEOF OCCUPANCY FEE \$50.00

AL-HLAL GOOD,

MEAT AND GENERAL

SROCCERY AND SROCERY SHOT

AT SAME TIME