



© 2015 RYAN SENATORE ARCHITECTURE

**NISSEN BUILDING
RENOVATIONS
PORTLAND, MAINE**



**RYAN SENATORE
ARCHITECTURE**
565 CONGRESS STREET
PORTLAND, MAINE
207-650-6414
senatorearchitecture.com

CONSULTANTS:
STRUCTURAL:
Structural Integrity
77 Oak Street
Portland, ME 04101
207-774-4614

REVISIONS:

DATE: NOVEMBER 9, 2015

PROJECT No. 1523

DRAWN BY: JPF

CHECKED BY: RJS

SCALE: AS NOTED

SHEET TITLE:
**DOOR AND
WINDOW
SCHEDULE**

A7-0

FRAME TYPES

NOTES:
1. EXTERIOR DOOR JAMBS TO BE SEALED TO THEIR ROUGH OPENINGS USING LOW EXPANDING FOAM, BACKER ROD OR CAULKING.
2. ALL EXTERIOR DOORS TO BE WEATHER STRIPPED

GLAZING SCHEDULE	
KEY	GLAZING TYPE
GL-1	INSULATED CLEAR GLAZING
GL-2	FIRE RATED INSULATED GLAZING
GL-3	CLEAR TEMPERED GLASS
GL-4	CLEAR INSULATED TEMPERED GLASS
GL-5	FIRE RATED GLAZING

LEGEND:
T = TEMPERED GLASS
F = FIXED

NOTES:
1. CONTRACTOR TO VERIFY ALL ROUGH OPENINGS
2. ALL EXTERIOR GLAZING INSULATED
3. FRAME OPENINGS WITH ELEVATIONS
4. SEAL WINDOW TO ROUGH OPENINGS WITH LOW EXPANDING FOAM INSULATION - SEE DETAILS

1 DOOR TYPES
1/4" = 1'-0"

2 WINDOW TYPES
1/4" = 1'-0"

NOTES:
1. CONTRACTOR TO VERIFY ALL ROUGH OPENINGS
2. ALL EXTERIOR GLAZING INSULATED
3. FRAME OPENINGS WITH ELEVATIONS
4. SEAL WINDOW TO ROUGH OPENINGS WITH LOW EXPANDING FOAM INSULATION - SEE DETAILS

WINDOW SCHEDULE											
KEY	ACTION	ROUGH OPENING (WxH) VIF	R.O. HEAD RECEPTOR	R.O. FROM RECEPTOR	DETAILS			MATERIAL	FINISH	REMARKS	FOR TEMPERED GLASS LOCATIONS SEE WINDOW ELEVATION TYPES FOR MASONRY OPENING DIMENSIONS COORDINATE COURSING WITH EXTERIOR ELEVATION SHEETS AND PLAN AND SECTION DETAIL SHEETS
					HEAD	JAMB	SILL				
A	STORE	5'-6" X 12'-10"	-	-	-	-	AL	ANO	-	OLDCASTLE SERIES 3000 THERMAL MULTIPANE CENTER SET - THERMALLY BROKEN STOREFRONT WINDOW SYSTEM - PROVIDE STEEL REINFORCING WITHIN MEMBERS	
B	F	-	-	-	-	-	VL	-	-	FIXED WINDOW AT PENHOUSE SOUTH WALL. SEE SECTION DETAIL FOR WINDOW INFORMATION	

DOOR SCHEDULE																
DOOR NO.	TYPE	DOOR				FRAME					GENERAL					
		WIDTH	HEIGHT	THICKNESS	MATERIAL	FINISH	INSULATED	TYPE	MATERIAL	THRESHOLD	HEAD	JAMB	SILL	CLOSER	FIBERGLASS (MINUTES)	HARDWARE
100.1	E	14'-0"	12'-10"	1-3/4"	AL	ANO	Y	-	AL	-	-	-	Y	-	-	OVERHEAD DOOR WITH AUTOMATIC OPERATOR, BY OVERHEAD DOOR, 521 SERIES, FINISH TO MATCH ADJACENT STOREFRONT
100.2	A	3'-0"	7'-0"	1-3/4"	AL	ANO	Y	-	AL	-	-	-	Y	-	-	STOREFRONT DOOR WITH PANIC HARDWARE
100.3	D	3'-0"	7'-0"	1-3/4"	STL	PTD	-	-	STL	-	-	-	-	-	-	NEW DOOR IN EXISTING OPENING, MODIFY OPENING AS REQUIRED
102.1	C	3'-0"	7'-0"	1-3/4"	STL	PTD	Y	1	STL	AL	-	-	Y	60	-	FIRE DOOR WITH PANIC HARDWARE
103.1	B	3'-0"	7'-0"	1-3/4"	STL	PTD	Y	1	STL	-	-	-	Y	-	-	
104.1	C	3'-0"	7'-0"	1-3/4"	STL	PTD	Y	1	STL	AL	-	-	Y	60	-	FIRE DOOR WITH PANIC HARDWARE
105.1	C	3'-0"	7'-0"	1-3/4"	STL	PTD	Y	1	STL	AL	-	-	Y	60	-	FIRE DOOR WITH PANIC HARDWARE
105.2	C	3'-0"	6'-8"	1-3/4"	STL	PTD	Y	1	STL	AL	-	-	Y	60	-	FIRE DOOR WITH PANIC HARDWARE

- STOREFRONT INFORMATION**
- 1.) ALL STOREFRONT TO BE THERMALLY BROKEN WITH INSULATED GLAZING UNITS WITH LOW-E COATING ARGON FILLED UNITS
 - 2.) TEMPER ALL GLASS AS REQUIRED BY BUILDING CODE
 - 3.) PROVIDE SUB SILLS WITH DRAINED PANS WITH END AND BACK DAMS, PROVIDE COMPRESSION HEAD SLIP TRACKS
 - 4.) PROVIDE FINISH TO MATCH ADJACENT EXISTING STOREFRONT, PROVIDE SAMPLE AND SHOP DRAWINGS FOR OWNER AND ARCHITECT APPROVAL PRIOR TO ORDER
 - 5.) FOR STOREFRONT FRAME GEOMETRY AND ARRANGEMENTS SEE EXTERIOR BUILDING ELEVATIONS
 - 6.) G.C. TO FIELD MEASURE ALL STOREFRONT UNITS PRIOR TO ORDER
 - 7.) PROVIDE STANDARD HEAD COMPENSATING RECEPTORS (DEFLECTION HEAD)