



FOURTH FLOOR FRAMING PLAN
 1/4"=1'-0"

FLOOR FRAMING IS 14" PREFABRICATED, PARALLEL CHORD, WOOD TRUSSES SPACED AT 16" UNLESS NOTED. DOUBLE TRUSSES AT FRAMED OPENINGS AND TRANSFERS FROM ROOF LEVEL. DESIGN TRANSFER TRUSSES FOR P1 = 840 LB SNOW LOAD + 340 LB DEAD LOAD. LVL MEMBERS ARE MANUFACTURED BY TRUS JOIST MACMILLAN. FLOOR SHEATHING IS 3/4" T&G ADVANTECH. TOP OF FLOOR SHEATHING ELEV = 70'-0".

© 2004 TFH ARCHITECTS

SUMNER COURT
 A QUALITY RESIDENTIAL DEVELOPMENT BY FORT SUMNER, LLC
 117 SHERIDAN STREET, PORTLAND, MAINE

TFH ARCHITECTS
 100 COMMERCIAL STREET
 PORTLAND MAINE 04101
 TELEPHONE 207 775 6141
 ARCHITECTURE PLANNING

CONSULTANTS:

REVISIONS:

DATE: February 3, 2005
 PROJECT No. 04057
 DRAWN BY: DJT
 CHECKED BY: DJT
 SCALE: As Noted

SHEET TITLE:
Fourth Floor Framing Plan And Details

S1-5