



THIRD LEVEL FRAMING PLAN
SCALE: 1/4"=1'-0"
0' 1' 5' 10'

- NOTES:
- SEE S1.0 FOR GENERAL STRUCTURAL NOTES.
 - ALL FLOOR SHEATHING SHALL BE 3/4" OSB, SEE GENERAL NOTES FOR ADDITIONAL INFO.
 - ROOF SHEATHING SHALL BE 5/8" OSB, SEE GENERAL NOTES FOR ADDITIONAL INFO.
 - ALL WOOD COLUMNS IN 2x6 WALLS SHALL BE 3-2x6 AND IN 2x4 WALLS SHALL BE (3) 2x4, UNO.
 - ALL WOOD BEAMS ARE FLUSH, UNO.
 - ALL HEADERS ARE (2) 2x8, UNO.
 - NEW 2x BLOCKING BETWEEN JOISTS WHERE BEARING WALL ABOVE.

FRAMING PLAN SYMBOLS KEY	
□	WOOD POST
○	STEEL COLUMN
⊗	NUMBER OF WOOD STUDS IN POST BELOW
A	COLUMN ABOVE THIS LEVEL
C	COLUMN CONTINUOUS THROUGH THIS LEVEL
→	JOIST BEARING
→	CONTINUOUS JOIST WITH INTERMEDIATE BEARING
→	FLUSH FRAMED JOIST BEARING WITH HANGER
→	WOOD STUD BEARING WALL BELOW
→	SHEAR WALL
2x4	NUMBER OF TRIM STUDS UNDER HEADER
2x4	NUMBER OF KING STUDS ADJACENT TO HEADER