## City of Portland, Maine - Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716

Location of Construction: 195 Congress S	Owner: Antranig	ian, Arsine Exec.	Phone:		Permit No:			
Owner Address:	Lessee/Buyer's Name:	Phone:	BusinessName:		-	•		
SAA	Portland Trading Po	<del></del>	<u> </u>		Pormit	Issued:		
Contractor Name:	Address:	Phone		ļ	Permit			
Past Use:	Proposed Use:	COST OF WORK	PERMIT FER 25.00		1	1/25		
Video Store	Pone Shop	FIRE DEPT.   A	<del></del>		- ' '			
			enied Use Group:	Type:		T		
		G:	g:		Zone:	CBL: 13-	M-22	
Proposed Project Description:	<del></del>	Signature: PEDESTRIAN AG	Signature: CTIVITIES DISTRICT (	PAD)	Zoning	Approval:		
1		Action: A	approved		Spe	ecial Zone or	Reviews:	
Change of Use						☐ Shoreland ☐ Wetland		
-			emed .		1	od Zone		
		Signature:	Date:			division		
Permit Taken By: Sherry Pinard	Date Applied For:	November 19, 1997	~.		□Site	Plan maj ⊡r	ninor 🗆mm 🗖	
					Zoning Appeal ☐ Variance			
1. This permit application does not preclude the Applicant(s) from meeting applicable State and Federal rules.					☐ Miscellaneous			
2. Building permits do not include plumbing, septic or electrical work.					□ Conditional Use			
3. Building permits are void if work is not started within six (6) months of the date of issuance. False informa-					☐ Interpretation ☐ Approved			
tion may invalidate a building permit an	d stop all work				Der			
					Н	listoric Prese	rvation	
						in District or		
						es Not Require Juires Review	Review	
					Action	:		
	CERTIFICATIO	N	Ł		□App	noved		
I hereby certify that I am the owner of record			owner of record and that I	have been	□App	roved with Co	onditions	
authorized by the owner to make this applica			•		□Der	nied		
if a permit for work described in the application areas covered by such permit at any reasonal				to enter all	Date: _	<del></del>		
		· · · · · · · · · · · · · · · · · · ·	•					
Tole South			•					
SIGNATURE OF APPLICANT	ADDRESS:	DATE:	PHONE:		<b> </b>	<del></del>		
Robert <b>B</b> eckner	·					Γ		

## BUILDING PERMIT REPORT

DATE	:25 NOV 97 ADDRESS: 195 Congress ST.
REAS	ON FOR PERMIT: To erect sign
BUILI	DINGOWNER: Arsine Antronizian
CONT	TRACTOR:
PERM	HT APPLICANT: BUB BOCK NEV APPROVAL: */ DENNED
USE G	GROUPBOCA 1996 CONSTRUCTION TYPE
	CONDITION(S) OF APPROVAL
1.	This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.
2.	Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection)
3.	Precaution must be taken to protect concrete from freezing.
4.	It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
5.	Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996)
<b>6</b> .	All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA
7.	National Mechanical Code/1993).  Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the city's
. <del>.</del>	building code.
8. 	Gnardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and R and public garages and open parking structures, open gnards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".) Headroom in habitable space is a minimum of 7'6".
0.	Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group
	minimum 11" tread. 7" maximum rise.
2.	The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8")  Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft.
3. 1.	Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units.  All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors with self closer's.
5.	The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment.
<b>)</b> .	All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the

provisions of the City's Building Code Chapter 9, Section 19, 920.3.2 (BOCA National Building Code/1996), and NFPA

101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):

In the immediate vicinity of bedrooms

In all bedrooms

## SIGNAGE

## PLEASE ANSWER ALL QUESTIONS

$\rho$ . (
ADDRESS: 155 CONGRESS ST ZONE:
OWNER: PORHAnd TRAding POST
APPLICANT: DAVIC COULOMBE
ASSESSOR NO.: $13-m-\lambda 2$
SINGLE TENANT LOT? YES NO
MULTI TENANT LOT? YES NO NO
FREESTANDING SIGN? YES NO DIMENSIONS (ex. pole sign)
MORE THAN ONE SIGN? YESNODIMENSIONS
BLDG. WALL SIGN? YES NO DIMENSIONS 16 X 1,83 = 29.28
MORE THAN ONE SIGN? YES NODIMENSIONS
LIST ALL EXISTING SIGNAGE AND THEIR DIMENSIONS: None
LOT FRONTAGE (FEET)
BLDG FRONTAGE (FEET) 28 TT STORE FRONT X 1,5 = (424 MAX
AWNING YESNO IS AWNING BACKLIT? YESNO
HEIGHT OF AWNING:
IS THERE ANY COMMUNICATION, MESSAGE, TRADEMARK OR SYMBOL ON IT?
A SITE SKETCH AND BUILDING SKETCH SHOWING EXACTLY WHERE EXISTING AND NEW
SIGNAGE IS LOCATED MUST BE PROVIDED. SKETCHES AND/OR PICTURES OF THE

PROPOSED SIGNS ARE ALSO REQUIRED.