

**ReliaBilt Fire Resistant 6-Panel
Prehung Inswing Steel Entry Door
(Common: 32-in x 80-in; Actual:
31.75-in x 79-in)**

Item # 16593 | Model # 16593

Be the first to

Enter ZIP code to see price

Tweet 0

Description

Fire Resistant 6-Panel Prehung Inswing Steel Entry Door (Common: 32-in x 80-in; Actual: 31.75-in x 79-in)

- 90 minute fire rated door with fire rated steel frame
- Rust and corrosion resistant galvanized steel
- Energy-saving insulated core
- Ready to paint with smooth primed surface
- Limited Lifetime Warranty

Specifications

Glass Style	None	Look and feel of real woodgrain	No
Glass Caming	N/A	Fire Resistant	Yes
Glass Insert Shape/Style	N/A	Lowe's Exclusive	Yes
Brickmould	No	Blinds Between the Glass	N/A
Door Swing	Inswing	Prefinish Color	None
Rough Opening Height (Inches)	82	Optional Additions Available	None
Masonry Opening Height (Inches)	83.75	Sidelite Width (Inches)	0
Masonry Opening Width (Inches)	37.25	Door Style	6-panel
Sill Type	Fixed	ENERGY STAR Qualified Northern Zone	Yes
Sill Finish	Mill	ENERGY STAR Qualified North-Central Zone	Yes
Lockset Bore	Yes	ENERGY STAR Qualified Southern Zone	Yes
Collection Name	Fire-Rated	Iris Technology	No
Type	6-panel	Door Handing	Left
Prefinished	No	Rot-Resistant Frame	No
Primed	Yes	Slab or Prehung	Prehung
Paintable	Yes	Hinge Finish	Polished brass
Caming Option	N/A	Common Height (Inches)	80
Vented Glass with Screen	N/A	Common Jamb Width (Inches)	4.5625
Construction	Insulating core	Common Width (Inches)	32
Glass Insulation	N/A	Height (Actual) (Inches)	79
Lockset Option	Ready for lockset and deadbolt	Jamb Width (Actual) (Inches)	4.5625
Tempered Glass	N/A	Width (Actual) (Inches)	31.75

Customers Also Viewed