# CITY OF PORTLAND WASTEWATER CAPACITY APPLICATION

Department of Public Services, 55 Portland Street, Portland, Maine 04101-2991



Bradley Roland, P.E. Water Resources Division

Date: 2/24/17

## 1. Please, Submit Utility, Site, and Locus Plans.

,				
Site Address:	7 Cumberland Avemue			
		Cha	rt Block Lot Number: <u>14 - C - 17</u>	
Proposed Use: <u>Res</u>	idential (6-unit)			
Previous Use: Res	sidential (2-unit)	_ >	Commercial (see part 4 below)	
<b>Existing Sanitary Flo</b>	ws:GPD	got	Industrial (complete part 5 below)	
Existing Process Flow	ws:GPD	ate	Governmental	
Description and location of City sewer that is to		Ü	Residential	Х
receive the proposed building sewer lateral.			Other (specify)	
Existing latera; in Cu	imberland Ave.			

Clearly, indicate the proposed connections, on the submitted plans.

## 2. Please, Submit Contact Information.

City Planner's Name:	Phone:
Owner/Developer Name:	Banner Properties
Owner/Developer Address:	126 Underwood Road, Falmouth, ME 04105
Phone: <u>332-3038</u>	Fax: E-mail: mboisso1@maine.rr.com
Engineering Consultant Name:	Plymouth Engineering Inc Jon Whitten, Jr. PE
Engineering Consultant Address:	PO Box 46, Plymouth, ME
Phone: _257-2071	Fax: 257-2130 E-mail: jon.whitten@plymouthengineering.com

Note: Consultants and Developers should allow +/- 15 days, for capacity status, prior to Planning Board Review.

## 3. Please, Submit Domestic Wastewater Design Flow Calculations.

Estimated Domestic Wastewater Flow Generated:120 X 6 = 720GPDPeaking Factor/ Peak Times:21.6 gallons per minute peak domestic flowSpecify the source of design guidelines:(i.e. "Handbook of Subsurface Wastewater Disposal in<br/>Maine," "Plumbers and Pipe Fitters Calculation Manual," Portland Water District Records,<br/>Other (specify)

Note: Please submit calculations showing the derivation of your design flows, either on the following page, in the space provided, or attached, as a separate sheet.

4. Please, Submit External Grease Interceptor Calculations.

Total Drainage Fixture Unit (DFU) Values:	
Size of External Grease Interceptor:	
Retention Time:	
Peaking Factor/ Peak Times:	

Note: In determining your restaurant process water flows, and the size of your external grease interceptor, please use The Uniform Plumbing Code. Note: In determining the retention time, sixty (60) minutes is the minimum retention time. Note: Please submit detailed calculations showing the derivation of your restaurant process water design flows, and please submit detailed calculations showing the derivation of the size of your external grease interceptor, either in the space provided below, or attached, as a separate sheet.

### 5. Please, Submit Industrial Process Wastewater Flow Calculations

Estimated Industrial Process Wastewater Flows Generated:	GPD
Do you currently hold Federal or State discharge permits?	YesNo
Is the process wastewater termed categorical under CFR 40?	YesNo
OSHA Standard Industrial Code (SIC):	(http://www.osha.gov/oshstats/sicser.html)
Peaking Factor/Peak Process Times:	

Note: On the submitted plans, please show where the building's domestic sanitary sewer laterals, as well as the building's industrial-commercial process wastewater sewer laterals exits the facility. Also, show where these building sewer laterals enter the city's sewer. Finally, show the location of the wet wells, control manholes, or other access points; and, the locations of filters, strainers, or grease traps.

Note: Please submit detailed calculations showing the derivation of your design flows, either in the space provided, or attached, as a separate sheet.