

# Technical Data Manual

Model Nos. and pricing: see Price List



53 and 79 USG /  
200 and 300 liter capacity



119 USG / 450 liter  
capacity

## Vitocell 300-V

### EVI Series

Vertical indirect-fired domestic hot water storage tank  
of high-grade stainless steel



*This tank version is not suitable  
for steam heating applications.*




### Vitocell 300-V

Fully hygienic, efficient and economical domestic hot water production with DHW tanks of high-grade stainless steel – vertical version.

#### The benefits at a glance:

- Corrosion-resistant tank of **high-grade SA 240-316 Ti stainless steel** offers a long service life.
- Fully hygienic due to **high quality homogeneous stainless steel surfaces**.
- The high alloy material is immune to cracking or peeling. The tank stays hygienic and requires only minimum service.
- **Does not require a consumable anode** for corrosion protection.
- The entire water content is heated by a **1 1/4" / 32 mm diameter stainless steel heat exchanger surface which extends to the bottom of the tank**.
- The positioning of the tubular heat exchanger coil further ensures that 82 to 97% of the tank volume can be drawn at **constant water temperature**.
- The stainless steel heat exchanger coil is self-venting towards the top and self-draining towards the bottom, therefore not susceptible to reduced heat transfer due to air lock or deposits.
- **Universally suitable** – for applications requiring larger quantities of hot water, multiple vertical tanks can be combined via headers to form tank batteries.
- **Standby losses minimized** by 2 1/4" / 58 mm highly effective, foamed-in-place or 4"/100 mm wrap-around PET insulation HCFC-free insulation.
- **Easy transport** into mechanical room due to low weight and compact construction.



Inspection port/  
clean-out opening

Recirculation tapping

Boiler water supply

2 1/4" / 58 mm foamed-in-place PUR foam or 4" / 100 mm  
wrap-around PET insulation (HCFC-free)

Non-finned, stainless steel, tubular heat  
exchanger coil extends to tank  
bottom – the entire water  
volume is heated ensuring no  
cold spots where bacteria  
growth could occur

Boiler water return

Flanged cleanout opening

5167 410 v2.5

Product may not be exactly as illustrated.

# Technical Data

## Technical data

<b>For domestic hot water heating applications</b> which utilize modulating and low temperature hot water heating boilers		Suitable for heating systems with: ■max. working pressure on <b>heat exchanger side</b> up to <b>220 psig</b> at 392°F / 200°C ■max. working pressure on <b>DHW water side</b> of up to <b>150 psig</b> at 210°F / 99°C			
<b>Storage capacity</b>	USG ltr	53 200	79 300	119 450	
<b>Recovery rates</b> *1 with a temperature rise of the domestic hot water from <b>50 to 140°F / 10 to 60°C</b> and heating water supply temperature of ..... at the supply flow rate stated below	194°F 90°C	MBH GPM ltr/h	215 4.7 1084	280 6.2 1410	276 6.1 1393
	176°F 80°C	MBH GPM ltr/h	164 3.6 826	201 4.5 1014	212 4.7 1066
	158°F 70°C	MBH GPM ltr/h	99 2.1 499	140 3.1 705	147 3.3 739
<b>Supply flow rate</b> for the recovery rates stated	GPM m <sup>3</sup> /h	22.0 5.0	22.0 5.0	28.6 6.5	
<b>Standby losses</b> *2	MBH/24 h	5.5	6.8	9.2	
<b>Overall dimensions with insulation</b> *3					
Overall width	inches	22 <sup>7</sup> / <sub>8</sub>	25	36 <sup>1</sup> / <sub>3</sub>	
	mm	581	633	923	
Overall depth	inches	25 <sup>1</sup> / <sub>2</sub>	27 <sup>3</sup> / <sub>8</sub>	38 <sup>3</sup> / <sub>8</sub>	
	mm	649	704	974	
Overall height	inches	56	70	68 <sup>1</sup> / <sub>2</sub>	
	mm	1420	1779	1740	
Tilt height	inches	58	71 <sup>3</sup> / <sub>8</sub>	66 <sup>1</sup> / <sub>2</sub>	
	mm	1471	1821	1690	
<b>Weight</b>	lbs	168	220	245	
Tank with insulation	kg	76	100	111	
<b>Heating water content</b> (heat exchanger pipe coil)	USG	2.64	2.91	4.0	
	ltr	10	11	15.0	
<b>Heat exchanger surface area</b>	ft <sup>2</sup>	14	16	20.5	
	m <sup>2</sup>	1.3	1.5	1.9	
<b>Connections</b>					
Heating water supply/return	Ø" (male thread)	1	1	1 <sup>1</sup> / <sub>4</sub>	
Domestic cold/hot water	Ø" (male thread)	1	1	1 <sup>1</sup> / <sub>4</sub>	
Temp. and press. relief valve	Ø" (male thread)	1	1	1 <sup>1</sup> / <sub>4</sub>	
Recirculation	Ø" (male thread)	1	1	1 <sup>1</sup> / <sub>4</sub>	

\*1 When planning for the recovery rate as stated or calculated, allow for the corresponding circulation pump.

The stated recovery rate is only achieved when the rated output of the boiler is equal to or greater than that stated under "Recovery rates".


Please also refer to the corresponding sizing chart at the end of this manual.

\*2 Measured values are based on a room temperature of 68°F / 20°C and a domestic hot water temperature of 149°F / 65°C and can vary by ± 5%.

\*3 For other dimensions, see illustration and table on page 5.

► For information regarding other Viessmann System Technology componentry, please reference documentation of the respective product.

**Vitocell 300-V, 53 and 79 USG / 200 and 300 ltr  
with PUR Foam insulation**




**Dimensions**

Storage capacity	USG	53	79
		200	300
a	inches	13 3/4	14 1/2
	mm	353	357
b	inches	12 1/2	13 1/2
	mm	317	343
c	inches	3 1/2	3 1/2
	mm	87	87
d	inches	11 3/4	11 3/4
	mm	297	301
e	inches	27 1/2	29 1/2
	mm	697	751
f	inches	35 1/3	37 1/2
	mm	897	951
g	inches	50 2/3	64 1/2
	mm	1286	1640
h	inches	24 1/4	26 1/4
	mm	614	665

**Legend**

- AQ Aquastat well
- BWR Boiler water return
- BWS Boiler water supply
- D Drain
- DCW Domestic cold water
- DHW Domestic hot water
- IO Inspection and clean-out opening
- RT Recirculation tapping
- TPV Temperature and pressure relief valve

**Vitocell 300-V, 119 USG / 450 ltr  
with wrap-around foam insulation**



**Dimensions**

Storage capacity	USG	119
		450
a	inches	20
	mm	508
b	inches	18 3/4
	mm	476
c	inches	19 2/3
	mm	498
d	inches	4
	mm	102
e	inches	17 7/8
	mm	453
f	inches	31 1/2
	mm	802
g	inches	39 7/8
	mm	1012
h	inches	63
	mm	1601
i	inches	65 2/3
	mm	1667
j	inches	36
	mm	914
k *1	inches	28
	mm	715

\*1 Without insulation jacket.

5167 410 v2.5

**Legend**

- AQ Aquastat well
- BWR Boiler water return
- BWS Boiler water supply
- D Drain
- DCW Domestic cold water
- DHW Domestic hot water
- IO Inspection and cleanout opening
- TPV Temperature and pressure relief valve
- RT Recirculation tapping

**Domestic hot water draw rate**

Storage tank contents heated to 140°F / 60°C, boiler not reheating


<b>Storage capacity</b>	USG	53	79	119
	ltr	200	300	450
<b>Domestic hot water draw rate</b>	GPM	2.6	4.0	4.0
	ltr/min	10	15	15
<b>Domestic hot water draw</b>	USG	37	72	109
	ltr	139	272	413
Water with t = 140°F/60°C (constant)				
<b>Percentage tank volume</b>		70%	91%	92%

**Heat-up time**


The stated heating times are achieved when the maximum recovery rate of the domestic hot water tank is made available at the respective supply temperature and with a domestic hot water rise from 50 to 140°F / 10 to 60°C.

<b>Storage capacity</b>	USG	53	79	119
	ltr	200	300	450
<b>Heating water supply temperature</b>	<b>Heat-up time (minutes)</b>			
	194°F / 90°C	11.4	15.5	20
	176°F / 80°C	15	21.5	24
	158°F / 70°C	23.5	32.5	35

**Pressure drop on heating water side (primary circuit)**



**Pressure drop on domestic hot water side (secondary circuit)**



- Ⓐ 79 USG / 300 ltr and 119 USG / 450 ltr storage capacity
- Ⓑ 53 USG / 200 ltr storage capacity

**Technical data**

The 79 and 119 USG / 300 and 450 ltr tank sizes may be combined into a battery consisting of between 2 and 4 tanks. Tank batteries consisting of more than 4 tanks can be installed by creating up to 4 batteries, each consisting of 4 tanks. The heating contractor is responsible to ensure proper piping on both the primary and secondary circuits.

Tank storage capacity		USG	79	119	
		ltr	300	450	
Total capacity of tank battery		USG	158	238	476
		ltr	600	900	1800
Number of storage tanks			2	2	3
			●●	●●	●●●
Recovery rates <sup>*1</sup>			560	553	829
with a temperature rise of the domestic hot water from 50 to 140°F / 10 to 60°C		194°F MBH	12.4	12.3	18.4
		90°C GPM	2820	2786	4179
		ltr/h			
and heating water supply temperature of ..... at the supply flow rate stated below		176°F MBH	403	423	635
		80°C GPM	8.9	9.4	14.1
		ltr/h	2028	2132	3198
		158°F MBH	280	293	440
		70°C GPM	6.2	6.5	9.8
		ltr/h	1410	1479	2217
Supply flow rate		GPM	44	57	86
		m <sup>3</sup> /h	10	13	19.5
for the recovery rates stated					
Standby losses <sup>*2</sup>		MBH/24 h	13.6	18.4	27.6
Overall dimensions with insulation					
Overall width	inches		57½	75¾	114¾
	mm		1461	1926	2914
Overall depth	inches		43 <sup>5</sup> / <sub>8</sub>	50¼	50¼
	mm		1109	1278	1278
Overall height	inches		70	69½	69½
	mm		1779	1767	1767
Heat exchanger surface area		ft <sup>2</sup>	30.1	38.8	58.1
		m <sup>2</sup>	2.8	3.6	5.4

<sup>\*1</sup> When planning for the recovery rate as stated or calculated, allow for the corresponding circulation pump. The stated recovery rate is only achieved when the rated output of the boiler is equal to or greater than that stated under "Recovery rates".

<sup>\*2</sup> Measured values are based on a room temperature of 68°F / 20°C and a domestic hot water temperature of 149°F / 65°C and can vary by ± 5%.

**Installation of additional aquastat(s)**

**WARNING**


In a multiple-tank installation, it is recommended that an additional high limit aquastat be installed in the common domestic hot water supply header to the system. This aquastat should be wired in series to the operating aquastat on the tank battery. The setting on this additional high limit aquastat should be approximately 9°F / 5°C higher than the operating high limit.

Ensure that temperature tempering valve(s) is/are installed if the domestic hot water storage tank temperature exceeds 140°F / 60°C to protect from scalding.

Consult plumbing codes and authorities for local requirements.

# Vitocell 300-V in a Multiple-Tank Installation

For domestic hot water heating applications which utilize modulating and low temperature hot water heating boilers




Side view

Qty 2

Qty 3

Qty 4



Top view

**Legend**

- A Air vent
- AQ Aquastat well
- BWR Boiler water return
- BWS Boiler water supply
- D Drain
- DCW Domestic cold water
- DHW Domestic hot water
- IO Inspection and cleanout opening
- RT Recirculation tapping
- TPV Temperature and pressure relief valve

Storage tank capacity		79 USG / 300 ltr		119 USG / 450 ltr	
<b>Total capacity of tank battery</b>	USG	158	238	357	476
	ltr	600	900	1350	1800
<b>Number of storage tanks</b>		2	2	3	4
a	inches	3 <sup>3</sup> / <sub>8</sub>	4	4	4
	mm	87	102	102	102
b	inches	11 <sup>7</sup> / <sub>8</sub>	17 <sup>7</sup> / <sub>8</sub>	17 <sup>7</sup> / <sub>8</sub>	17 <sup>7</sup> / <sub>8</sub>
	mm	301	453	453	453
c	inches	29 <sup>1</sup> / <sub>2</sub>	31 <sup>1</sup> / <sub>2</sub>	31 <sup>1</sup> / <sub>2</sub>	31 <sup>1</sup> / <sub>2</sub>
	mm	751	802	802	802
d	inches	64 <sup>1</sup> / <sub>2</sub>	63	63	63
	mm	1640	1601	1601	1601
e	inches	13 <sup>1</sup> / <sub>2</sub>	19 <sup>1</sup> / <sub>2</sub>	19 <sup>1</sup> / <sub>2</sub>	19 <sup>1</sup> / <sub>2</sub>
	mm	343	498	498	498
f	inches	5	5	5 <sup>1</sup> / <sub>2</sub>	5 <sup>1</sup> / <sub>2</sub>
	mm	127	130	135	139
g	inches	9 <sup>3</sup> / <sub>8</sub>	8 <sup>1</sup> / <sub>2</sub>	8 <sup>1</sup> / <sub>2</sub>	9
	mm	237	217	217	226
h	inches	8 <sup>1</sup> / <sub>8</sub>	14 <sup>1</sup> / <sub>4</sub>	14 <sup>1</sup> / <sub>4</sub>	14 <sup>1</sup> / <sub>4</sub>
	mm	206	359	359	359
<b>Common header size boiler supply / return</b>	inches	2	2	2	2 <sup>1</sup> / <sub>2</sub>
	mm	51	51	51	64
<b>Common header size domestic hot / cold water</b>	inches	1 <sup>1</sup> / <sub>4</sub>	1 <sup>1</sup> / <sub>4</sub>	1 <sup>1</sup> / <sub>2</sub>	2
	mm	32	32	38	51

5167 410 v2.5



**Domestic hot water draw rate**

Storage tank content heated to 140°F / 60°C, boiler not reheating

<b>Storage capacity</b>	USG	79	119		
	ltr	300	450		
<b>Battery storage capacity</b>	USG	158	238	357	476
	ltr	600	900	1350	1800
<b>No. of tanks</b>		2	2	3	4
<b>DHW draw rate</b>	GPM	7.9	7.9	11.9	15.9
	ltr/min	30	30	45	60
<b>Domestic hot water draw</b>	USG	143.7	243	365	486
	ltr	544	920	1380	1840
Water with t = 140°F / 60 °C (constant)					
<b>Percentage of battery volume</b>		93%	92%	92%	92%

**Quick recovery (over 10-minute period)**

Domestic hot water rise from 50 to 113°F / 10 to 45°C

<b>Storage capacity</b>	USG	79	119		
	ltr	300	450		
<b>Battery storage capacity</b>	USG	158	238	357	476
	ltr	600	900	1350	1800
<b>No. of tanks</b>		2	2	3	4
<b>Heating water supply temperature</b>		<b>Quick DHW recovery (over 10-minute period)</b>			
194°F / 90°C	USG/10 min	237	314	422	528
	ltr/10 min	898	1190	1600	2000
176°F / 80°C	USG/10 min	229	314	422	528
	ltr/10 min	870	1190	1600	2000
158°F / 70°C	USG/10 min	184	277	388	475
	ltr/10 min	698	1050	1470	1800

**Max. domestic hot water draw rate (over 10-minute period)**

Domestic hot water rise from 50 to 113°F / 10 to 45°C

<b>Storage capacity</b>	USG	79	119		
	ltr	300	450		
<b>Battery storage capacity</b>	USG	158	238	357	476
	ltr	600	900	1350	1800
<b>No. of tanks</b>		2	2	3	4
<b>Heating water supply temperature</b>		<b>Max. DHW draw rate (over 10-minute period)</b>			
194°F / 90°C	GPM	23.5	32	42.3	52.8
	ltr/min	90	120	160	200
176°F / 80°C	GPM	23	32	42.3	52.8
	ltr/min	87	120	160	200
158°F / 70°C	GPM	18.5	26.6	39	47.5
	ltr/min	70	101	148	180

# Standard Equipment Product Installation

## Standard Equipment

**Vitocell 300-V,  
53 and 79 USG / 200 and 300 ltr  
capacity**

Domestic hot water tank of high-grade stainless steel with PUR Foam insulation with  
 – thermometer and  
 – adjustable leveling bolts.

The following is packed separately and attached to the crate:  
 – installation fittings package: with the necessary brass adaptors, other necessary hardware, and Loctite 55  
 – sensor well with insulation  
 – temperature and pressure relief valve.

Electrostatically powder coated sheet metal enclosure panel in a Vitosilver finish.

**Vitocell 300-V,  
119 USG / 450 ltr  
capacity**


Domestic hot water tank of high-grade stainless steel with wrap-around PET insulation with  
 – thermometer and  
 – adjustable leveling bolts.

The following is packed separately and attached to the crate:  
 – installation fittings package: with the necessary brass adaptors, other necessary hardware, and hemp  
 – sensor well with insulation  
 – temperature and pressure relief valve.

Synthetic wrap-around enclosure panel in a Vitosilver finish.

## Product Installation

### Domestic hot water connections



### IMPORTANT

This is a simplified conceptual drawing only! Piping and necessary componentry must be field verified. Proper installation and functionality in the field is the responsibility of the heating contractor.

- (A) Spring-loaded flow check valve
- (B) Discharge pipe
- (C) Anti-scald tempering valve (field supplied)
- SV Shut-off valve
- FV Flow check valve
- PR Pressure reducing valve
- D Drain
- DCW Domestic cold water supply


- PGC Pressure gauge connection
- E Precharged expansion tank (required where backflow preventer is installed; check local plumbing codes and requirements)
- BP1 Backflow preventer
- BP2 Backflow preventer
- T&P Temperature and pressure relief valve

- DHW Domestic hot water supply
- DW Water filter
- RP Recirculation pipe
- RPU Recirculation pump

**Sensor Well**

Vitocell 300-V,  
53 to 119 USG / 200 to 450 ltr  
capacity

<b>Storage Capacity</b>	USG	53	79	119
	ltr	200	300	450
a	inches	8 3/4	8 3/4	13
	mm	220	220	330
b	inches	7 3/4	7 3/4	12 1/4
	mm	200	200	310



**⚠ WARNING**

To ensure optimum, safe operation, the supplied stainless steel well must be installed. The well diameter is large enough to accommodate a wide variety of sensing bulbs.

**Always use spring clip to ensure proper contact of capillary bulb against the stainless steel well for proper sensing/heat transfer!**

**Heating water supply temperatures over 230°F / 110°C**

For these operating conditions, an approved high limit safety aquastat must be installed to limit the domestic hot water temperature to 203°F / 95°C in the tank.

**Recirculation tapping**

The recirculation tapping is on a separate tapping (see page 5). Cap this opening if the tank is not installed with recirculation.

**Backflow preventers**

Where backflow preventers are required, a domestic water expansion tank installation is recommended in the cold water inlet piping before the cold water enters the Vitocell. For the backflow device, observe local plumbing codes and regulations.

**Temperature and pressure relief valve**

A temperature and pressure relief valve (T&P relief valve) is supplied with the tank. The heating contractor must install the valve on each tank in a method meeting code requirements. If local codes require a different relief valve, substitute the manufacturer's supplied valve. The tank is approved for 100 psig where a CRN is required. Maximum operating pressure is 150 psig.

The T&P relief valve supplied with the tank is ASME pressure steam rated for 998 MBH and CSA temperature steam rated for 200 MBH. It is tested under ANSI Z21.22 code for Relief Valves and Automatic Gas Shut-off Devices for Hot Water Supply Systems.

Watts Model 40XL-8	100 psig (Canada where CRN is required)	150 psig (US and Canada)
ASME pressure steam rating	998 MBH	1438 MBH
CSA temperature steam rating	205 MBH	
Relief temperature	210°F (99°C)	
Inlet thread	3/4" male	
Outlet thread	3/4" female	

**Warranty excerpt**

Our warranty for domestic hot water tanks states that the water heated should be of drinking water quality and that any water treatment equipment in use must function correctly.

If the product has been improperly installed or misapplied by the installer, contractor or final user, Viessmann accepts no responsibility for damage howsoever caused and reserves the right to withdraw the product warranty. In order to qualify for product warranty, strict adherence to the installation and service manuals must be observed. In the event that components not approved by Viessmann are utilized, Viessmann reserves the right to withdraw all expressed or implied warranties without written notice.

The water to be heated with the Vitocell must be drinking (potable) water quality. If the tank is used to heat other media, the warranty will be null and void. Damage resulting from excessive pressure or temperature is clearly not the responsibility of Viessmann.

The amount of chloride and sulfate acceptable to the tank is limited. In areas where high concentrations of chloride and sulfate are present in drinking water, please consult Viessmann for directions.

For full warranty details, please read the product warranty card.

# Vitocell 300-V Sizing Continuous Flow Capacity Chart


## Vitocell 300-V, 53 USG / 200 ltr capacity

Curve (A)  
Domestic hot water 40 to 140°F / 4 to 60°C

Curve (B)  
Domestic hot water 40 to 176°F / 4 to 80°C

Domestic hot water  
delivery rate

(A)	(B)
4- 60°C	4- 80°C
40- 140°F	40- 176°F



	l/r/h USG/h	l/r/h USG/h
	2303 608	1697 448
	2150 568	1584 418
	1996 527	1471 389
	1843 487	1358 359
	1689 446	1245 329
	1535 406	1131 299
	1382 365	1018 269
	1228 324	906 239
	1075 284	792 209
	921 243	679 179
	768 203	565 149
	614 162	453 120
	461 122	339 90
	307 81	227 60
	154 41	113 30

**Vitocell 300-V,  
79 USG / 300 ltr capacity**


Curve (A)  
Domestic hot water 40 to 140°F / 4 to 60°C

Curve (B)  
Domestic hot water 40 to 176°F / 4 to 80°C

Domestic hot water  
delivery rate

(A)	(B)
4- 60° C	4- 80° C
40- 140° F	40- 176° F

ltr./h USG/h	ltr./h USG/h
-----------------	-----------------



5167 410 v2.5

# Vitocell 300-V Sizing Continuous Flow Capacity Chart


## Vitocell 300-V, 119 USG / 450 ltr capacity

Curve **(A)**  
Domestic hot water 40 to 140°F / 4 to 60°C

Curve **(B)**  
Domestic hot water 40 to 176°F / 4 to 80°C

Domestic hot water  
delivery rate


<b>(A)</b>	<b>(B)</b>
4- 60°C	4- 80°C
40- 140°F	40- 176°F



# Vitocell 300-V Sizing Continuous Flow Capacity Chart

## Example: Vitocell 300-V, 119 USG / 450 ltr capacity

Assume boiler output to tank is 238 MBH. Enter chart at left and draw horizontal line across to recovery rate of 284 GPH / 4.7 GPM for 140°F / 60°C domestic hot water under column A. Where the horizontal line intersects the 194°F / 90°C curve is the point of intersection for the diagonal line used to size the pump. The diagonal line begins at the origin and goes through the point of intersection extending up to the top of the chart. Read between the reference diagonal lines to get a pump specification of 20 GPM at 8.4 ft. To summarize: For a Vitocell-V 300 with 119 USG / 450 ltr capacity and 238 MBH input, the boiler water temperature is 194°F / 90°C, difference between boiler return and supply water temperature is 29°F / 16°C, recovery rate is 4.7 GPM of 140°F / 60°C DHW, and the pump required is 20 GPM, 8.4 ft. plus pressure drop in piping and boiler. If a multiple-tank application is required, i.e. 4 tanks at 238 MBH input each, then the pump selection would be (4 x 20 GPM) 80 GPM at 8.4 ft. plus piping pressure drop.



5167 410 v2.5

Viessmann Manufacturing Company Inc.  
750 McMurray Road  
Waterloo, Ontario • N2V 2G5 • Canada  
**Technifo Line 1-888-484-8643**  
1-800-387-7373 • Fax (519) 885-0887  
[www.viessmann.ca](http://www.viessmann.ca) • [Info@viessmann.ca](mailto:Info@viessmann.ca)

Viessmann Manufacturing Company (U.S.) Inc.  
45 Access Road  
Warwick, Rhode Island • 02886 • USA  
**Technifo Line 1-888-484-8643**  
1-800-288-0667 • Fax (401) 732-0590  
[www.viessmann-us.com](http://www.viessmann-us.com) • [Info@viessmann-us.com](mailto:Info@viessmann-us.com)

