





INDICATES 5/8" OSB ABOVE CEILING ELEVATION 121'-8 1/8" +/- V.I.F.


## 3rd LEVEL FRAMING/REFERENCE PLAN

1. FLOOR SHEATHING SHALL BE 5/8" OSB, SEE GENERAL NOTES FOR ADDITIONAL INFO
2. ALL WOOD COLUMNS IN 2x6 WALLS SHALL BE 3-2x6 AND IN
2x4 WALLS SHALL BE 3-2x4 UNLESS NOTED OTHERWISE ON PLANS

3. ALL WOOD BEAMS ARE DROPPED, UNO 4. ALL HEADERS ARE 2-2x6, UNO

5. SEE S-1.0 FOR GENERAL STRUCTURAL NOTES

FRAMING PLAN SYMBOLS KEY			
	WOOD POST		
(X)	NUMBER OF WOOD STUDS IN POST BELOW		
A	COLUMN ABOVE THIS LEVEL		
С	COLUMN CONTINUOUS THROUGH THIS LEVEL		
В	COLUMN BELOW THIS LEVEL		
<b>—</b>	TRUSS OR JOIST BEARING		
<u> </u>	FLUSH FRAMED JOIST BEARING WITH HANGER		
	WOOD STUD BEARING WALL BELOW		
///////////////////////////////////////	SHEAR WALL		
<e></e>	EXISTING FRAMING MEMBER		
<n></n>	NEW FRAMING MEMBER		
<u>"X"T</u>	NUMBER OF TRIM STUDS UNDER HEADER		
<u>"X"K</u>	NUMBER OF KING STUDS ADJACENT TO HEADER		



Project:				
Arnold Addition				
Ted & Toni Arnold				
61 St Lawrence St.				
Portland, ME				

Drawing:	3rd LEVEL FRAMING/REFERENCE PLAN			
Scale:	1/2"=1'-0"	Drawn by:		
Date:	SEPTEMBER 27, 2011	Revised	S-1	