



### HIGH ROOF FRAMING PLAN

- NOTES: SCALE 1/2"=1'-0"
1. ROOF SHEATHING SHALL BE 5/8" OSB, SEE GENERAL NOTES FOR ADDITIONAL INFO
  2. ALL WOOD COLUMNS IN 2x6 WALLS SHALL BE 3-2x6 AND IN 2x4 WALLS SHALL BE 3-2x4 UNLESS NOTED OTHERWISE ON PLANS
  3. ALL WOOD BEAMS ARE DROPPED, UNO
  4. ALL HEADERS ARE 2-2x6, UNO
  5. SEE S-1.0 FOR GENERAL STRUCTURAL NOTES

FRAMING PLAN SYMBOLS KEY	
□	WOOD POST
⊗	NUMBER OF WOOD STUDS IN POST BELOW
A	COLUMN ABOVE THIS LEVEL
C	COLUMN CONTINUOUS THROUGH THIS LEVEL
B	COLUMN BELOW THIS LEVEL
←	TRUSS OR JOIST BEARING
⊢	FLUSH FRAMED JOIST BEARING WITH HANGER
⊢	WOOD STUD BEARING WALL BELOW
▨	SHEAR WALL
<E>	EXISTING FRAMING MEMBER
<N>	NEW FRAMING MEMBER
⊗	NUMBER OF TRIM STUDS UNDER HEADER
⊗	NUMBER OF KING STUDS ADJACENT TO HEADER