City of Portland, Maine – Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716 Permit No:9 7 Location of Construction: Phone: 761-4053 | Ted Arnold/V. Lambert Lessee/Buyer's Name: | Phone: 61 St. Lawrence St Owner Address: BusinessName: ermit Issued: Phone: Contractor Name: Address: JU 1 4 1997 COST OF WORK: PERMIT FEE: Past Use: Proposed Use: \$_{80.00} \$12,000.00 CITY OF PORTLAN FIRE DEPT. Approved INSPECTION: 3 unit same with addition ☐ Denied Use Group: Type: CBL: Zone: R - 6Signature: Zoning Approval: Proposed Project Description: PEDESTRIAN ACTIVITIES DISTRICT Action: Approved Special Zone or Reviews Approved with Conditions: ☐ Shoreland Denied □ Wetland construct addition as per plans ☐ Flood Zone Signature: □ Subdivision Date: ☐ Site Plan mai ☐minor ☐mm ☐ Permit Taken By: Date Applied For: 5/23/97 Vicki Dover **Zoning Appeal** □ Variance This permit application does not preclude the Applicant(s) from meeting applicable State and Federal rules. ☐ Miscellaneous Building permits do not include plumbing, septic or electrical work. □ Conditional Use Building permits are void if work is not started within six (6) months of the date of issuance. False informa-☐ Interpretation ☐ Approved tion may invalidate a building permit and stop all work.. □ Denied MH REQUIREMENTS Historic Preservation ☑Not in District or Landmark Call owner for P/U D-Boes Not Require Review □ Requires Review Action: CERTIFICATION ☐ Appoved □ Approved with Conditions I hereby certify that I am the owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his authorized agent and I agree to conform to all applicable laws of this jurisdiction. In addition, □ Denied if a permit for work described in the application is issued, I certify that the code official's authorized representative shall have the authority to enter all Date: areas covered by such permit at any reasonable hour to enforce the provisions of the code(s) applicable to such permit 03 July 1997 761-4053 ADDRESS: SIGNATURE OF APPLICANT RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE PHONE: **CEO DISTRICT**

COMMENTS	
1/30/97 Act with sewner & contra mensured setback on sideyard some set brack 20+ Fort OK forms are up on to pour	ictor
1 Mensuled selback In Sidilyand	
IN SEC WACK IN TO MOUSE	D=1 / `
	Muny
Inspection Record Type Foundation:	Date
Foundation: Framing:	
Plumbing:	

Final: ______
Other: _____

Marland 761-4053 les St Ju 7-2.50

BUILDING PERMIT REPORT

DATE	E: M Solo 1 ADDRESS: U. S. S. Lawrence ST
REAS	SON FOR PERMIT: 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
BUIL	DING OWNER: Handage has any one of
CONT	TRACTOR:
PERM	APPROVAL: DENIED
	1, 2, 5, 8, 9, 10, 11, 13, 14, 157:25
	CONDITION(S) OF APPROVAL 20, 26
1) 2) 3. 4. 5)	This permit does not excuse the applicant from meeting applicable State and Federal rules and laws. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection) Precaution must be taken to protect concrete from freezing. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996) All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993) U.L. 103. Guardrail & Handrails A guardrail system is a system of building components located near the open sides of clevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. Headroom in habitable space is a minimum of 7'6". Stair construction in Use Group R-3 & R-4 is a minimum of 10" (read and 7 3/4" maximum rise. All other Use group
2.	minimum 11" tread. 7" maximum rise. The minimum headroom in all parts of a stairway shall not be less than 80 inches. Every sleeping room below the fourth story in buildings of use Groups R and I-I shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable
3.) 4.) 5.)	when it exits directly from the apartment to the building exterior with no communications to other apartment units. All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors with self closer's. The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 19, 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations): In the immediate vicinity of bedrooms In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required)

- 16. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. 17. The Fire Alarm System shall be maintained to NFPA #72 Standard. 18. The Sprinkler System shall maintained to NFPA #13 Standard. 19. All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 1024. Of the City's building code. (The BOCA National Building Code/1996) (20)All construction and demolition debris must be disposed at the City's authorized reclamation site. The fee rate is attached. Proof of such disposal must be furnished to the office of Inspection Services before final Certificate of Occupancy is issued or demolition permit is granted. 21. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year". 22. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services. 23. This permit does not excuse the applicant from obtaining any license which may be needed from the City Clerk's office. 24. Ventilation shall meet the requirements of Chapter 12 Sections 1210, of the City's Building Code. -25. 26 All electrical and plumbing permits must be obtained by a Master Licensed holders of their trade.
- P. Samuel Hoffses, Chief of Code Enforcement

cc: Lt. McDougall, PFD Marge Schmuckal

27.

28.

M DING

Applicant: Tel Anold	Date: 7/11/97			
Address: 61 St LAwrence St	and II F			
C-B-L: (6 - C - (5) CHECK-LIST AGAINST ZONING ORDINANCE				
Date - THS (880)	6075			
Zone Location - R-6	$3.5 \times 145 = 170$			
	10 ×17 = 129			
Interior or corner lot -	8 × 16 =			
Proposed Use/Work - 16 X 24 gar Age	9 x 48 = 170			
Sewage Disposal -	, hy —			
Lot Street Frontage -				
Front Yard -	6 x 168 = 288			
Rear Yard - 20' veg - 27' Chu	- 6x48 =			
Side Yard - 10 / Feg - 10 9 22 8 home	green 2103.5)			
Projections -	recording 103.5)			
Width of Lot -	No driver of Ol			
Height -	60			
1 16"				
Lot Area - Lot Coverage/ Impervious Surface - Area per Family - Off-street Parking - Loading Bays -	= 2726			
Area per Family - 76 000 000	oper :			
Area per ramny -				
Off-street Parking - (() 40.4	· r			
Loading Bays -	<i>i</i> ,			
Site Plan -	66			
Shoreland Zoning/Stream Protection -	3 X CZ 148 Z			
Flood Plains -	$3 \times 22 = 66$ $3 \times 22 = 66$ $26 \times 57 = 260$ $26 \times 10 = 384$			
	1 v24 = 384			
	Z1924			