

WINDOW SCHEDULE

SYM.	MANUFACTURER	TYPE	UNIT NUMBER	MANUFACTURER'S ROUGH OPENING DIMENSIONS			MATERIAL	SCREEN	REMARKS
				WIDTH	HEIGHT	B.O. HEADER			
AWN2872	MARVIN	AWNING	CUAWN2872	2'-5" RO	5'-11-3/4" RO	7'-1-3/4" A.F.F.	GUNMETAL CLAD /WOOD	YES	3 LITE -7/8" SDL, TEMPERED GLASS; INTERIOR SHADE: WHITE; DIRECT MULL- to flank center fixed picture unit.
CCMP7272	MARVIN	FIXED PICTURE w/FRAME	CCMP7272	6'-1" RO	5'-11-3/4" RO	7'-1-3/4" A.F.F.	GUNMETAL CLAD /WOOD	NO	9 LITE -7/8" SDL, TEMPERED GLASS; INTERIOR SHADE: WHITE; DIRECT MULL- w/ flanking awning units.
CCM2472	MARVIN	FIXED PICTURE w/FRAME	CCM2472	2'-1" RO	5'-11-3/4" RO	7'-1-3/4" A.F.F.	GUNMETAL CLAD /WOOD	NO	3 LITE -7/8" SDL, TEMPERED GLASS; INTERIOR SHADE: WHITE.
CCMP2472	MARVIN	VENTING PICTURE UNIT	CCMP2472	2'-1" RO	5'-11-3/4" RO	7'-1-3/4" A.F.F.	GUNMETAL CLAD /WOOD	NO	3 LITE -7/8" SDL, TEMPERED GLASS; VENTING UNIT -w/single stud mull to door unit.
CAWN3248	MARVIN	AWNING	CUAWN3248	2'-9" RO	3'-11-3/4" RO	7'-0" A.F.F.	CLAD /WOOD	YES	9 LITE -7/8" SDL, VENTING UNIT.
CAWN3248	MARVIN	FIXED	CUAWN3248	2'-9" RO	3'-11-3/4" RO	7'-0" A.F.F.	CLAD /WOOD	NO	9 LITE -7/8" SDL, FIXED UNIT.
CAWN2424	MARVIN	AWNING	CUAWN2424	2'-1" RO	1'-11" RO	align w/ext'g DH	CLAD /WOOD	YES	4 LITE -7/8" SDL, TEMPERED GLASS; VENTING UNIT.
DH TILT PAC	MARVIN	DOUBLE-HUNG	CUD2422	2'-6-1/2"	4'-5"	VERIFY	CLAD/WOOD	YES	6/6 LITE, -7/8" SDL, DH TILT PAC, SASH REPLACEMENT. EXT'G 9" x 12" PANES. VERIFY EXISTING OPENINGS.

NOTES:

01. VERIFY ALL ROUGH OPENING REQUIREMENTS WITH MANUFACTURER PRIOR TO ROUGH CARPENTRY AND WINDOW ORDER.
02. VERIFY WINDOW R.O. HEAD HEIGHTS WITH SECTION & ELEVATION DRAWINGS BEFORE INSTALLING WINDOWS. HEAD HEIGHTS MAY VARY THROUGHOUT THE PROJECT.
03. ALL GROUPED UNITS TO BE FACTORY MULLED U.N.O.
04. PROVIDE SHOP DRAWINGS FOR ARCHITECT'S REVIEW PRIOR TO WINDOW ORDER. SHOP DRAWINGS SHOULD INCLUDE ALL INFORMATION PERTINENT TO EACH WINDOW UNIT. INCLUDE DRAWN ELEVATIONS OF EACH WINDOW TYPE, INCLUDING MUNTIN PATTERNS AND SWING DIRECTIONS.
05. WINDOW UNITS TO UTILIZE CLEAR LO-E1 GLAZING AND BE TEMPERED WHERE REQUIRED BY CODE. (NOTE TEMPERED UNITS IN SHOP DRAWINGS FOR ARCHITECT'S REVIEW)
06. ALL WINDOW MUNTINS TO BE 7/8" SIMULATED DIVIDED LIGHT (SDL) WITH INTERNAL SPACER BARS, U.N.O. (SEE ELEVATIONS FOR DIVIDED LITE PATTERNS)
07. WINDOWS TO BE MANUFACTURER'S 'OVOLO STICKING' WITH MATCHING MUNTINS (OAE)
08. ALL WINDOWS TO UTILIZE MANUFACTURER'S 'COASTAL HARDWARE' - MANUFACTURER'S INTERIOR HARDWARE FINISH - MANUFACTURER'S 'SATIN NICKEL' FINISH
09. EXTERIOR COLOR - MANUFACTURER'S 'STONE WHITE' UNLESS NOTED
10. INTERIOR FINISH - MANUFACTURER'S 'PRIME' FINISH
11. INCLUDE FULL HEIGHT 'HI-TRANSPARENCY' SCREENS AT ALL OPERABLE WINDOWS TO MATCH EXTERIOR WINDOW COLOR. WINDOWS WITH INTERIOR SCREENS, SCREEN FRAME TO MATCH INTERIOR MATERIAL / FINISH.
12. PROVIDE MANUFACTURER RECOMMENDED SILL PAN (OAE) AT ALL WINDOWS. ADJUST ROUGH OPENING TO ACCOMMODATE SILL PAN.
13. FOLLOW ALL MANUFACTURER GUIDELINES FOR INSTALLATION.

ROB & ROBIN WHITTEN ARCHITECTS.COM  
 Whitten Architects  
 37 Silver Street Portland, Me 04101

3.04.2016

ROB & ROBIN WHITTEN  
 23 ST. LAWRENCE ST.  
 PORTLAND, ME 04101

A-302

WINDOW SCHEDULE