

Surface washers · asymmetrical wide spread light distribution

Post construction: One piece extruded aluminum, 1/8" wall thickness internally welded to a die-cast base plate cover.

Enclosure: One piece die-cast aluminum housing connected to the post/pole by a two piece, die-cast aluminum knuckle. The knuckle has infinite adjustability from 0° to 90° and is secured by one stainless steel fastener. Fully gasketed using a one piece molded high temperature silicone gasket and provided with a pure anodized matte aluminum reflector. Molded 1/4" thick etched tempered glass secured by a one piece die-cast aluminum frame secured to the housing with four stainless steel captive fasteners. Die castings are marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy.

Electrical: 26W LED luminaire, 31 total system watts, -30°C start temperature. Integral 120V through 277V electronic LED driver, 0-10V dimming. LED module(s) are available from factory for easy replacement. Standard LED color temperature is 3000K with an 85 CRI. Available in 4000K (85 CRI); add suffix K4 to order.


Anchor base: Pole Mount; Mounts to #896A anchorage kit (supplied).

Finish: All BEGA standard finishes are polyester powder coat with minimum 3 mil thickness. Available in four standard BEGA colors: Black (BLK); White (WHT); Bronze (BRZ); Silver (SLV). To specify, add appropriate suffix to catalog number. Custom colors supplied on special order.

CSA certified to U.S. and Canadian standards, suitable for wet locations. Protection class IP65

Weight: 8.8 lbs.

Type:
 BEGA Product:
 Project:
 Voltage:
 Color:
 Options:
 Modified:



Pole mounted · assymetrical wide spread

	Lamp	A	B	C	Anchorage
99878	26W LED	10 1/4	98 1/2	12 1/2	79818