



SYMBOL LEGEND

(XX)	DOOR TAG -REFER TO SHEET A6.0X
(XXX)	FINISH TAG -REFER TO DESIGN GUIDE PROJECT MANUAL MASTER
(XX)	ACCESSORY TAG -REFER TO SPEC SECTION 10800
X-000	FURNISHING REFERENCE - REFER TO INTERIOR DESIGN SPECIFICATIONS BOOK
XX-00	M.E.P. COMPONENT REFERENCE - REFER TO IPFS
J	JUNCTION, PULL OR TAP BOX, CEILING, WALL OR FLOOR MOUNTED
⏏	TELEPHONE OUTLET
⏏	USB DATA JACK
⏏	TV OUTLET, FLUSH MOUNTED.
⏏	DUPLEX RECEPTACLE, 20A 125V, 3W., WALL MOUNTED NEMA 5-20R.
⏏	RECESSED CEILING LIGHTS.
⊙	MOTION SENSOR
⊕	THERMOSTAT

- ### REFERENCE NOTES
- REFER TO INTERIOR PRODUCT AND FINISH SPECIFICATIONS.
 - ELECTRICAL OUTLETS SHOWN ON ELEC/PLUMBING/MECH PLAN AND ON ELEVATIONS ARE FOR DEVICES AND FIXTURES SPECIFIED. ADDITIONAL OUTLETS MAY BE REQUIRED BY LOCAL BUILDING DEPARTMENT CODES.
 - ELECTRICAL OUTLETS ARE MOUNTED AT STANDARD HEIGHT OF 18" UNLESS NOTED OTHERWISE.
 - SWITCHES AND THERMOSTATS TO BE LOCATED AT 48" CENTERLINE AFF UNLESS NOTED OTHERWISE.
 - REFER TO GUESTROOM ELEVATIONS FOR MOUNTING CONFIGURATIONS OF OUTLETS. COORDINATE FINAL LOCATIONS WITH CASEGOODS.
 - SOME PRODUCTS, FIXTURES AND FURNITURE ITEMS ARE HANDED (LEFT OR RIGHT), DESIGNED TO COORDINATE, WHERE APPLICABLE.
 - ALL DIMENSIONS ARE FROM FACE OF FINISH TO FACE OF FINISH, U.N.O. HOLD ALL CLEAR INTERIOR ROOM DIMENSIONS.
 - WATER CLOSET WASTE LINES ARE TO BE LOCATED IN WALL CHASE, NOT IN EXTERIOR WALLS.

- ### CRITERIA NOTES
- PROVIDE CONTINUOUS SOLID WOOD BLOCKING IN CEILING FOR DRAPERY ATTACHMENT AND SLIDING DOOR TRACKS.
 - COORDINATE PARTITION DIMENSIONS WITH HVAC EQUIPMENT & CONFIGURATION.
 - PROVIDE METAL TRIM TRANSITION (316) AT ALL OUTSIDE CORNERS OF BATHROOM.
 - IRONING BOARD MOUNT (316) & IRON RACK MOUNT (328) TO BE COORDINATED WITH CLOSET INSERT.
 - PROVIDE ACCENT VINYL (327)
 - NOT USED
 - COORDINATION BY HEADBOARD INSTALLER & ELECTRICIAN WILL BE REQUIRED AND MAY REQUIRE NUMEROUS VISITS BY BOTH TRADES.
 - WALL OUTLETS SHALL NOT OCCUR IN SAME WALL CAVITY OF ADJACENT GUESTROOMS, TYPICAL.
 - PROVIDE BLOCKING FOR ACCESSORIES, EQUIPMENT, AND FF&E AS REQUIRED.
 - MASTER LIGHT SWITCH WITH SIGNAGE TO CONTROL ALL HARDWIRED LIGHTS AND LED STRIP LIGHTING IN GUESTROOM, WITH EXCEPTION OF BATHROOM. WIRE AHEAD OF INDIVIDUAL SWITCHES. SEE 3&4/522.
 - AT HEARING IMPAIRED ROOM ONLY.
 - NOT USED
 - NOT USED
 - PAINT EXTERIOR WINDOW WALL (309) WITH MOLD AND MILDEW TEXTURED FINISH.
 - SIZE AND LOCATION OF EXTERIOR WINDOW TO BE ACCEPTED BY MARRIOTT.
 - ARCHITECT TO REVIEW VANITY SHOP DRAWINGS IN IPFS FOR LATEST INFORMATION (INCLUDING DIMENSIONS & FINISHES) FOR CUSTOM VANITIES. ARCHITECT TO OBTAIN ACCEPTANCE FROM MARRIOTT REVIEW TEAM. ARCHITECT TO PROVIDE VANITY SUPPORT DESIGN. SUPPORT DESIGN SHOULD COMPLY WITH LOCAL CODES.
 - 4-WAY SWITCHES AT HEADBOARD AND GUESTROOM ENTRY, WIRED TO LED STRIP LIGHT (#1) TO PLUG INTO OUTLET UNDER BENCH NEAR ENTRY TO BEDROOM. SEE 3&4/522.
 - 4-WAY SWITCH AT HEADBOARD AND GUESTROOM ENTRY, WIRED TO OVERHEAD ENTRY & CLOSET LIGHTS. SEE 3&4/522.
 - REMOVABLE CEILING PANELS.
 - DRAPERY PULL WANDS ARE LOOP TYPE HANDLES AND 48" MAX AFF.
 - ANY GAP BETWEEN THE FLOORING MATERIAL AND THE GUESTROOM WALL SHOULD BE NO MORE THAN A 1/2" SO THAT THE BASE WILL COMPLETELY COVER THIS GAP.
 - SECURE VANITY BASE TO FLOOR AND WALL. SECURE VANITY MIRROR TO CEILING. PROVIDE BLOCKING AS REQUIRED.
 - WRAP DRAINAGE AND SUPPLY PIPES WITH INSULATING MATERIAL.
 - PROVIDE (1) GFI RECEPTACLE (EL-12) ABOVE COUNTER BACKSPASH AT 44" A.F.F. AND (1) RECEPTACLE (EL-11) AT 60" A.F.F. CONNECT TOGETHER TO A DEDICATED SINGLE 120V CIRCUIT.
 - ARCHITECT TO REVIEW DOOR & SHOWER ASSEMBLY SHOP DRAWINGS IN IPFS FOR LATEST INFORMATION (INCLUDING DIMENSIONS & FINISHES). FOR MODIFYING SHOWER ASSEMBLIES & DOORS, ARCHITECT TO OBTAIN ACCEPTANCE FROM MARRIOTT REVIEW TEAM.
 - NOT USED
 - LED STRIP LIGHT (#2) ON MOTION SENSOR UNDER BENCH. MOTION SENSOR TO BE PLUGGED INTO ADJACENT OUTLET (EL-13). BREAK TAB ON ONE SIDE OF DUPLEX OUTLET, SO THAT PLUG CONTROLLING MOTION SENSOR IS CONTROLLED BY SWITCH (EL-13).
 - NOT USED
 - HOLES FOR LIGHTS IN CEILING PANELS TO BE CUT IN FIELD.
 - BASE BOARD CAN BE PURCHASED THROUGH MARRIOTT AND IS IN THE ID SPEC MANUAL.
 - REFRIGERATOR DOOR TO BE INSTALLED, SUCH THAT, DOOR SWINGS TOWARDS ADJACENT WALL.
 - ELECTRICAL DEVICES FOR TV AND MOTION SENSOR OUTLET UNDER BENCH SHOULD NOT BE PROPRIETARY.

11 CORPORATE DRIVE • BELMONT, MA 02459
PHONE (603) 527-5000 • WWW.OPECHEE.COM

21 West Third St. Boston, MA
www.groponline.com
617-248-7000

AC HOTELS by MARRIOTT

Fore Street / Hancock Street / Thames Street
Portland, Maine

REVISION: 09-30-16 PER GROUP 1 09-27-16 REDLINES

ISSUED: 09-22-16 PROGRESS 10-18-16 60% MARRIOTT REVIEW

project architect: KAK
drawn by: DLS

KS1-RIGHT
PLANS AND
ELEVATIONS

sheet number:

A2.10