




**Submittal Data Sheet**  
1.0-Ton Wall Mounted Unit  
**FTXS12LVJURXS12LVJU**

**OUTDOOR UNIT DETAILS**

Power Supply (V/Hz/Ph):	208-230 / 60 / 1	Compressor Type:	Inverter
Power Supply Connections:	L1, L2, Ground	Capacity Control Range (%):	-
Min. Circuit Amps MCA (A):	8.80	Airflow Rate (H) (CFM):	1,183
Max Overcurrent Protection (MOP) (A):	15.00	Gas Pipe Connection (inch):	3/8
Max Starting Current MSC(A):		Liquid Pipe Connection (inch):	1/4
Rated Load Amps RLA(A):	5.3	Sound Pressure ( ) (dBA):	
Dimensions (HxWxD) (in):	21-5/8 x 30-1/8 x 11-1/4	Sound Power Level (dBA):	61
Net Weight (lb):	75		

**DIMENSIONAL DRAWING - OUTDOOR UNIT**

**RXS09/12D(A)VJU**  
Unit (in.)






**Submittal Data Sheet**  
4 PORT HP, DUCTLESS OD 3 TON  
4MXS36NMVJU

**FEATURES**

- Up to 18.9 SEER / Up to 12.7 EER / Up to 12.5 HSPF
- High-efficiency inverter driven swing compressor
- Low ambient heating to 5°F / -4°F with optional drain pan heater
- Specialized drain pan design for improved cold climate drainage

**BENEFITS**

- 12 Year limited parts warranty with online registration
- 5 Year limited parts warranty for commercial applications
- High efficiency cooling and heating operation provides utility bill savings
- Multiple indoor unit style options: wall mounted, floor standing, ceiling cassette, slim duct
- May qualify for regional utility rebates and incentives
- Compatible with optional Daikin ENVI Wi-Fi capable Smart Control





**Submittal Data Sheet**  
4 PORT HP, DUCTLESS OD 3 TON  
4MXS36NMVJU

**PERFORMANCE**

Outdoor Unit Model No.	4MXS36NMVJU	Outdoor Unit Name:	4 PORT HP, DUCTLESS OD 3 TON
Type:	Heat Pump		
Rated Cooling Conditions:	Indoor (°F DB/DB): 80 / 67 Ambient (°F DB/WB): 95 / 75	Rated Heating Conditions:	Indoor (°F DB/WB): 70 / 60 Ambient (°F DB/WB): 47 / 43
Rated Piping Length(ft):	25		
Rated Height Difference (ft):	49.00		
Rated Cooling Capacity (Btu/hr):	36,000	Rated Heating Capacity (Btu/hr):	36,000
Cooling Input Power (kW):		Heating input Power (kW):	
EER (Non-Ducted/Ducted):	9.20 / 7.90	Heating COP (Non-Ducted/Ducted):	4.5 / 3.5
SEER (Non-Ducted/Ducted):	17.70 / 14.00	HSPF (Non-Ducted/Ducted):	12.2 / 8.2
Max/Min Cooling Capacity (Btu/hr):	38,000 /	Max/Min Heating Capacity (Btu/hr):	43,000 /

**OUTDOOR UNIT DETAILS**

Power Supply (V/Hz/Ph):	208-230 / 60 / 1	Compressor Type:	Inverter
Power Supply Connections:	L1, L2, Ground	Capacity Control Range (%):	-
Min. Circuit Amps MCA (A):	19.75	Airflow Rate (H) (CFM):	2,613
Max Overcurrent Protection (MOP) (A):	20.00	Gas Pipe Connection (inch):	1/2
Max Starting Current MSC(A):	17.50	Liquid Pipe Connection (inch):	1/4
Rated Load Amps RLA(A):	17.5	Sound Pressure (H) (dBA):	54
Dimensions (HxWxD) (in):	28-15/16 x 34-1/4 x 12-5/8	Sound Power Level (dBA):	
Net Weight (lb):	139		

Daikin North America LLC, 5151 San Felipe, Suite 500, Houston, TX, 77056

Daikin City Generated Submittal Data

[www.daikinac.com](http://www.daikinac.com) [www.daikincomfort.com](http://www.daikincomfort.com)

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)




**Submittal Data Sheet**  
**4 PORT HP, DUCTLESS OD 3 TON**  
**4MXS36NMVJU**

**SYSTEM DETAILS**

Refrigerant Type:	R-410A	Cooling Operation Range (°F DB):	14 - 115
Holding Refrigerant Charge (lbs):	6.2	Heating Operation Range (°F WB):	5 - 72
Additional Charge (lb/ft):	0.01	Max. Pipe Length (Vertical) (ft):	49
Pre-charge Piping (Length) (ft):	132	Cooling Range w/Baffle (°F DB):	14 - 115
Max. Pipe Length (Total) (ft):	230	Heating Range w/Baffle (°F WB):	-4 - 72
Max Height Separation (Ind to Ind ft):	49		

**DIMENSIONAL DRAWING**



C. 3D093199




### Submittal Data Sheet

03-Ton VRV-III-S Heat Pump Unit

RXYMQ36PVJU

### FEATURES

- Single-phase technology enables installation in light commercial and residential applications
- Space-saving design and flexible indoor unit options offer quick and easy installation
- Standard Limited Warranty: 10-year warranty on compressor and all parts



VRV III-S





**Submittal Data Sheet**  
03-Ton VRV-III-S Heat Pump Unit  
RXYMQ36PVJU

**PERFORMANCE**

Outdoor Unit Model No.	RXYMQ36PVJU	Outdoor Unit Name:	03-Ton VRV-III-S Heat Pump Unit
Type:	Heat Pump		
Rated Cooling Conditions:	Indoor (°F DB/DB): 80 / 67 Ambient (°F DB/WB): 95 / 75	Rated Heating Conditions:	Indoor (°F DB/WB): 70 / 70 Ambient (°F DB/WB): 47 / 43
Rated Piping Length(ft):			
Rated Height Difference (ft):	0.00		
Rated Cooling Capacity (Btu/hr):	36,000	Rated Heating Capacity (Btu/hr):	42,000
Cooling Input Power (kW):	3.05	Heating Input Power (kW):	3.27
EER (Non-Ducted/Ducted):	11.50 / 9.90	Heating COP (Non-Ducted/Ducted):	2.8 /
SEER (Non-Ducted/Ducted):	14.90 / 14.00	HSPF (Non-Ducted/Ducted):	8.2 / 8.4
Max/Min Cooling Capacity (Btu/hr):	36,000 /	Max/Min Heating Capacity (Btu/hr):	42,000 /

**OUTDOOR UNIT DETAILS**

Power Supply (V/Hz/Ph):	208-230 / 60 / 1	Compressor Type:	Inverter
Power Supply Connections:	L1, L2, Ground	Capacity Control Range (%):	29 - 100
Min. Circuit Amps MCA (A):	27.00	Airflow Rate (H) (CFM):	3,740
Max Overcurrent Protection (MOP) (A):	30.00	Gas Pipe Connection (inch):	5/8
Max Starting Current MSC(A):		Liquid Pipe Connection (inch):	3/8
Rated Load Amps RLA(A):	17.6	Sound Pressure (H) (dBA):	58
Dimensions (HxWxD) (in):	52-15/16 x 35-7/16 x 12-5/8	Sound Power Level (dBA):	70
Net Weight (lb):	283		




**Submittal Data Sheet**  
03-Ton VRV-III-S Heat Pump Unit  
RXYMQ36PVJU

**SYSTEM DETAILS**

Refrigerant Type:	R-410A	Cooling Operation Range (*F DB):	23 - 115
Holding Refrigerant Charge (lbs):	8.8	Heating Operation Range (*F WB):	0 - 77
Additional Charge (lb/ft):		Max. Pipe Length (Vertical) (ft):	
Pre-charge Piping (Length) (ft):		Cooling Range w/Baffle (*F DB):	-
Max. Pipe Length (Total) (ft):	492	Heating Range w/Baffle (*F WB):	4 - 60
Max Height Separation (Ind to Ind ft):	0		

**DIMENSIONAL DRAWING**



RXYMQ36/48PVJU  
Units (in.)