



MEMBER TABLE ROOF PLAN		
MARK	PART	LENGTH
P-1	12Z12	25'-5"
P-2	12Z13	18'-0"
P-3	H0505188	22'-11 13/16"
SI-1	PS6	4'-10 1/2"
SI-2	PS6	4'-7 1/2"
SI-3	PS6	5'-0 1/2"
CB-11	R10	36'-0"
CB-12	R10	36'-5"
CB-13	CB38	29'-7"
CB-14	R34	29'-7"
CB-15	R78	29'-8"

MEMBER TABLE ROOF PLAN		
MARK	PART	LENGTH
P-501	12Z14	20'-7"
P-502	12Z14	30'-2"
P-503	12Z14	20'-2"
E-501	12E14	16'-11 1/2"
E-504	12E14	16'-6 1/2"
E-505	12E14	22'-11"
E-506	12E14	16'-11 1/2"
SI-1	PS6	4'-10 1/2"
P-601	12Z12	26'-6"
P-602	12Z13	26'-5"
P-603	12Z13	25'-4"
P-604	12Z13	26'-5"
P-605	12Z13	25'-7"
E-601	12E14	23'-11 1/2"
E-602	12E14	22'-5"
E-603	12E14	22'-5"
E-604	12E14	22'-5"
E-605	12E14	23'-0 1/2"
E-606	12E14	23'-0 1/2"
E-607	12E14	22'-5"
E-608	12E14	22'-5"
E-609	12E14	22'-5"
SI-1	PS6	5'-0 1/2"
CB-611	CB38	28'-7"
CB-612	CB38	28'-9"
CB-613	CB38	28'-3"
CB-614	CB38	28'-4"
CB-615	CB38	28'-5"

** - PROVIDE 1'-5" LAP AT INDICATED LOCATIONS

RTL-24 SEAMING REQUIREMENTS:
 THE ROOF PANELS ARE TO BE FASTENED AS FOLLOWS:
 () HAND CRIMP ONLY AT EAVE, RIDGE AND EACH CLIP.
 () TRIPLE LOC (MECHANICALLY SEAMED, SINGLE PASS).
 (X) QUAD LOC (MECHANICALLY SEAMED, DOUBLE PASS)
 - ALL SAFETY REGULATIONS TO BE FOLLOWED WHEN OPERATING ELECTRICAL SEAMER.
 - STEELWAY IS NOT RESPONSIBLE FOR DAMAGE OF SEAMER DUE TO IMPROPER USE.

UROOF
USHEETING
PANELS: 24 Ga. RTL
GALVALUME

UROOF FRAMING PLAN

BUILDER IRISHSPAN INDUSTRIES INC.	PROJECT SHIPYARD BREWING CO.	DWG # 73178-S2	0 ISSUED FOR INFORMATION	05/10/07 TSD
	LOCATION PORTLAND, US.	DWG NOT TO SCALE	REV. DESCRIPTION	DATE BY

STEELWAY
 7825 SPRINGWATER ROAD • AYLMEYER • ONTARIO
 CANADA • N5H 2R4 PH • 519 765 2244
 WWW.STEELWAY.COM