



PLAN DIMENSIONS LEGEND

F.O.B. - FACE OF PRECAST
 F.O.B. - FACE OF BRICK
 1ST AND 5TH FLOOR DIMENSIONS TO FACE OF PRECAST
 2-4 FLOORS DIMENSIONS TO FACE OF BRICK
 2-4 FLOORS DIMENSIONS TO FACE OF BRICK
 SEE 450-457 FOR PLAN AND FOUNDATION DETAILS
 SEE STRUCTURAL DWGS FOR FOUNDATION DETAILS
 ALL WINDOW DIMENSIONS ARE TO PRECAST OPENING AND/OR
 MASONRY OPENING (EIFS WALL IS UNIT SIZE)
 NOTE: OVERALL DIMS ARE TO FACE OF BRICK. CORNER PIERS
 ARE 4" OF MAIN BRICK WALL & INNER PIERS ARE 1" OF MAIN
 BRICK WALL

GENERAL NOTES:

1. SEE GUESTROOM PLANS ON DRAWINGS A1.20 TO A1.24.
2. SEE INTERIOR ELEVATIONS STARTING ON DRAWING 46.0.
3. SEE SCHEDULES STARTING ON DRAWING A8.0 & A9.0.
4. FOR TYPICAL INTERIOR AND EXTERIOR WALL TYPES SEE A0.6.
5. G.C. TO COORDINATE ROUGH OPENING REQUIREMENTS FOR ALL SHAFT ENCLOSURES FOR FRAMING.
6. LOCATIONS INDICATED FOR RECESSED FIRE EXTINGUISHER CABINETS (F.E.) ARE APPROXIMATE. VERIFY LOCATIONS AND QUANTITIES REQUIRED WITH LOCAL JURISDICTION. HEIGHT OF F.E. TO BE 5'-0" FROM FLOOR TO TOP OF CABINET.
7. ALL PUBLIC CORRIDORS TO HAVE CORNER GUARDS AT PROTRUDING CORNERS, PER SPECIFICATIONS. MAIN LAUNDRY ROOM TO HAVE STAINLESS STEEL CORNER GUARDS.
8. G.C. TO COORDINATE SHAFT SIZE & LOCATION WITH MECHANICAL DRAWINGS AND ALL RELATED PLUMB PENETRATIONS REQUIREMENTS.
9. RELATED PLUMB PENETRATIONS REQUIREMENTS.

FC2 - LARSEN PH0 6-2404-5H FIRE EXTINGUISHER SURFACE MOUNT WITH 'GENIE' SERIES DOOR AND LARSEN-LOC. (ABC CLASSIFICATION UL 444/60C EXTINGUISHER)

FC1 - LARSEN PH0 6R-2404-6R FIRE EXTINGUISHER AND 1H FIRE RATED CABINET WITH 'GENIE' SERIES DOOR AND LARSEN-LOC. (ABC CLASSIFICATION UL 444/60C EXTINGUISHER)

FCR - LARSEN PH0 6-2404-5H FIRE EXTINGUISHER SURFACE MOUNT WITH 'GENIE' SERIES DOOR AND LARSEN-LOC. (ABC CLASSIFICATION UL 444/60C EXTINGUISHER)

FCR - LARSEN PH0 6R-2404-6R FIRE EXTINGUISHER AND 1H FIRE RATED CABINET WITH 'GENIE' SERIES DOOR AND LARSEN-LOC. (ABC CLASSIFICATION UL 444/60C EXTINGUISHER)

FCR - LARSEN PH0 6-2404-5H FIRE EXTINGUISHER SURFACE MOUNT WITH 'GENIE' SERIES DOOR AND LARSEN-LOC. (ABC CLASSIFICATION UL 444/60C EXTINGUISHER)

FCR - LARSEN PH0 6R-2404-6R FIRE EXTINGUISHER AND 1H FIRE RATED CABINET WITH 'GENIE' SERIES DOOR AND LARSEN-LOC. (ABC CLASSIFICATION UL 444/60C EXTINGUISHER)

SECOND FLOOR PLAN
 SCALE: 3/32" = 1'-0"

LEGEND OF SYMBOLS

(XX)	COLUMN LINE MARKER
(XXX)	DETAIL OR WALL SECTION NUMBER APPEARS
(XXX)	BUILDING SECTION DESIGNATION APPEARS
(XXX)	DETAIL NUMBER WHERE DETAIL APPEARS
(XXX)	BUILDING ELEVATION DESIGNATION APPEARS
(XXX)	DRWG. NUMBER WHERE ELEVATION APPEARS
(XXX)	WALL TYPE NUMBER SEE DRWG. A0.3
(XX)	DOOR NUMBER SEE DRWG. A6.1
(XX)	ROOM NUMBER

<p>GROUP ONE 21 W. THIRD STREET, BOSTON, MA 02127 TEL: (617)268-7000, FAX: (617)268-0209</p>	<p>PROJECT RESIDENCE INN BY MARRIOTT PORTLAND, ME</p>	<p>TITLE SECOND FLOOR PLAN</p>	<p>NO. 1 REVISION</p>	<p>DATE 11/05/07</p>	<p>ISSUED FOR CONSTRUCTION - 11/05/07</p>
	<p>SCALE: As Noted</p>	<p>DATE:</p>	<p>DRAWN BY: ANS</p>	<p>CHECKED BY: JR</p>	<p>PERMIT REVIEW CORRECTIONS 1-16-08</p>