



SECTION D
SCALE: 3/8" = 1' 0"

GROUT SOLID BEHIND BRICK UP TO FLASHING
PROVIDE TAR PAPER AGAINST SHEATHING
FIRST BRICK OR MORTAR BED SET TO
MATCH BUILDING BRICK COURSING
METAL STANDING SEAM ROOF
WATERPROOFING MEMBRANE
SLOPED WOOD FRAMING
RIGID INSL OR SPRAY FOAM INSL

TYPICAL CORNER FIREPLACE
FIREPLACE UNIT

INSTALL DRYWALL
BEHIND FIREPLACES

PROVIDE 1x4 AT BOTTOM EDGE OF
STRINGER AT FIRE RATED WALLS
PROVIDE BLOCKING IN WALL FOR
OUTSIDE STRINGERS TO BE LAGGED
TO BLOCKING

EXTEND DRYWALL OF
FIRE RATED WALLS BY STRINGERS
& LANDING JOISTS

PROVIDE 2x4 AT
BOTTOM EDGE
OF STRINGER AT
NON FIRE RATED
WALLS
PROVIDE
BLOCKING IN
WALL FOR
OUTSIDE
STRINGERS TO
BE LAGGED TO
BLOCKING

COORDINATE BLOCKING
IN WALLS FOR ELEVATOR
RAIL SUPPORTS

LOCATE HATCH WHERE SHOWN ON
THE PLAN

COORD LOCATION
OF ACCESS DOOR
LOCATION TO NOT
INTERFERE WITH
LADDER

EXTEND ROOF
MEMBRANE OVER
CURB PRIOR TO
INSTALLING ROOF
HATCH

HEAD OFF TRUSS

DAVID M. WHITE, ARCHITECT
4029 Tibbetts Hill Road
P. O. Box 447
Goffstown, NH 03045
(603) 437-3425

THE VILLAGE AT OCEAN GATE, LLC
c/o Atlas Investment Group, LLC
95 Fay Street, Suite 107B
Boston, MA 02118

THE BAY HOUSE
Middle Street
Portland, Maine

SECTION D
Scale: 3/8" = 1'-0"
Commission No.: 06-008
Date: July 15, 2008

REVISIONS:

DRG. NO.
BUILDING 1
ISC.A