



TYPICAL ROOFING NOTE
 PROVIDE ADDITIONAL TAPERED INSULATION TO PROVIDE POSITIVE SLOPE TO ALL ROOF DRAINS
 REFER TO ROOF PLAN

TOP FLOOR CEILING NOTE
 CHECK BOTTOM CHORD W/ LASER
 ADD SHIMS AS REQUIRED TO LEVEL
 RESILIENT CHANNELS FOR A LEVEL CEILING

INTERIOR WALL PIPE PENETRATION DETAIL
 SCALE: 2" = 1' 0"

TYPICAL INTERIOR UNIT DOOR CONSTRUCTION
 REFER TO DOOR SCHEDULE FOR DOOR
 WOOD SPLIT JAMB FRAME
 2 1/2" COLONIAL INTERIOR CASING

GENERAL NOTES:
 1. ALL CONSTRUCTION MATERIALS BELOW THE SECOND FLOOR SLAB LINE SHALL BE NONCOMBUSTIBLE AS DEFINED BY THE BUILDING CODE. ONLY BLOCKING FOR OPENINGS IS PERMITTED TO BE STANDARD FRAMING LUMBER.

ASSEMBLY LABEL REFER TO ASSEMBLY SCHEDULES FOR COMPONENTS OF ASSEMBLY REFERENCED

DAVID M. WHITE, ARCHITECT
 4029 Tibbetts Hill Road
 P. O. Box 447
 Gorham, NH 03045
 (603) 437-3405

THE VILLAGE AT OCEAN GATE, LLC
 c/o Atlas Investment Group, LLC
 95 Fay Street, Suite 107B
 Boston, MA 02116

THE BAY HOUSE
 Middle Street
 Portland, Maine

SECTION A
 Scale: 3/8" = 1'-0"
 Commission No.: 06-008
 Date: July 15, 2008

REVISIONS:

DRG. NO.
 BUILDING 2
25C.1