



© 2017 RYAN SENATORE ARCHITECTURE

RISEING TIDE BREWING - EXPANSION
 103 FOX STREET
 PORTLAND, MAINE 04101



RYAN SENATORE
 ARCHITECTURE
 565 CONGRESS STREET
 PORTLAND, MAINE 04101
 207-650-6414
 senatorearchitecture.com

CONSULTANTS:

REVISIONS:

DATE: MAY 12, 2017

PROJECT No. 1718

DRAWN BY: JPF

CHECKED BY: RJS

SCALE: AS NOTED

SHEET TITLE:
WALL AND FLOOR ASSEMBLIES

A0-1

GRAPHIC DEPICTION		DESCRIPTION		
		- LAYER OF 5/8" GWB - 3 5/8" LIGHT GAUGE METAL STUDS AT 16" O.C. - 6" SOUND BATT - 1/2" RESILIENT SOUND CHANNEL AT 16" O.C. - LAYER OF 5/8" GWB		
TYPE				
NB	FIRE RATING	UL NUMBER	STC RATING	IIC RATING
	N/A	N/A		N/A

GRAPHIC DEPICTION		DESCRIPTION		
		- LAYER OF TYPE 'X' 5/8" GWB - 18 GAUGE 6" LIGHT GAUGE METAL STUDS AT 16" O.C. - 6" ROXUL SOUND BATT INSULATION - LAYER OF TYPE 'X' 5/8" GWB - PROVIDE HEAD SLIP TRACK		
TYPE				
1B	FIRE RATING	UL NUMBER	STC RATING	IIC RATING
	1 HR	V450	50-54	N/A

GRAPHIC DEPICTION		DESCRIPTION		
		- LAYER OF 5/8" GWB - 3 5/8" LIGHT GAUGE METAL STUDS AT 16" O.C. - LAYER OF 5/8" GWB		
TYPE				
NA	FIRE RATING	UL NUMBER	STC RATING	IIC RATING
	N/A	N/A		N/A

GRAPHIC DEPICTION		DESCRIPTION		
		- LAYER OF TYPE 'X' 5/8" GWB - 1/2" RESILIENT SOUND CHANNEL AT 16" O.C. - 18 GAUGE 6" LIGHT GAUGE METAL STUDS AT 16" O.C. - 6" ROXUL SOUND BATT INSULATION - 1/2" RESILIENT SOUND CHANNEL AT 16" O.C. - LAYER OF TYPE 'X' 5/8" GWB - PROVIDE HEAD SLIP TRACK		
TYPE				
1A	FIRE RATING	UL NUMBER	STC RATING	IIC RATING
	1 HR	V450	50-54	N/A

- WALL TYPE NOTES**
- REFER TO STRUCTURAL DRAWINGS FOR STUD SIZE AND SPACING
 - INSTALL WATER RESISTANT GYPSUM WALLBOARD IN ALL RESTROOMS AND TOILET ROOM WALLS AND CEILINGS, AND AT ANY WALL WITH PLUMBING FIXTURES
 - PROVIDE 1/2" GWB BEHIND ALL TUBS AND SHOWERS AT EXTERIOR WALLS AND FIRE RATED ASSEMBLIES. PROVIDE ADDITIONAL LAYER OF GWB TO COVER TUB AND SHOWER FLANGE. EXTEND ADDED LAYER ALONG ADJACENT WALLS AND ADJUST DOOR JAMB WIDTHS AS REQUIRED.
 - WHEN TWO ADJACENT WALL TYPES HAVE DIFFERING NUMBERS OF LAYERS OF GWB, THE FINISHED FACE OF GWB MUST FORM ONE CONTINUOUS PLANE, ADJUST STUD PLANE LOCATION AS REQUIRED TO ACHIEVE THE CONTINUOUS PLANE
 - HOLD BOTTOM OF GWB UP 1/2" FROM CONCRETE, PROVIDE SEALANT AT JOINT.
 - ALL WALL TYPES WITH AN INSULATION COMPONENT TO BE ACOUSTICALLY SEALED
 - ALL FIRE WALLS TO EXTEND TO DECK ABOVE, PROVIDE FIRE CAULKING AND BLOCKING AT ALL TOPS OF WALLS
 - ALL NON-BEARING LIGHT GAUGE WALLS TO HAVE SLIP HEAD TRACKS WHEN FRAMED TO DECK OR BEAM EDGE

GRAPHIC DEPICTION		DESCRIPTION		
		- 3/4" T & G FLOOR SHEATHING (SEE STRUCTURAL) - 2X10 JOISTS AT 12" O.C. (SEE STRUCTURAL) - 6" SOUND BATT INSULATION - MTL HAT CHANNEL AT 16" O.C. FASTENED TO JOISTS - LAYER OF TYPE 'X' 5/8" GWB		
TYPE				
F1	FIRE RATING	UL NUMBER	STC RATING	IIC RATING
	N/A	V450	-	N/A