



© 2017 RYAN SENATORE ARCHITECTURE

RIISING TIDE BREWING - EXPANSION
 103 FOX STREET
 PORTLAND, MAINE 04101



RYAN SENATORE
 ARCHITECTURE
 565 CONGRESS STREET
 PORTLAND, MAINE 04101
 207-650-8414
 senatorearchitecture.com

CONSULTANTS:

REVISIONS:

DATE: MAY 12, 2017

PROJECT No. 1718

DRAWN BY: JPF

CHECKED BY: RJS

SCALE: AS NOTED

SHEET TITLE:
FINISH SCHEDULE

A7-1

ROOM FINISH SCHEDULE												
ROOM #	ROOM NAME	WALLS					FLOOR	CEILINGS			REMARKS	PAINT COLOR
		NORTH	EAST	SOUTH	WEST	BASE		MATL.	HEIGHT	RATING		
111	EXPANDED TASTING ROOM	3	3	3	1	11	20	30	-	-		
112	EXTENDED BREWERY	1	1	3	3	11	21	30	-	-		
113	OFFICE	3	1	1	1	11	21	31	-	-		
115	LOCKERS / ENTRY	1	1	1	1	11	21	31	-	-		
114	STAIR	1	1	1	1	11,12	23	31	-	-	PAINTED 1X STRINGER TRIM, RUBBER TREADS RISERS AND LANDINGS	
200	MEZZANINE	3	1	-	3	11	22	30	-	-		

FINISH SCHEDULE KEY	
WALLS	
1	GWB - PAINTED
2	MOISTURE RESISTANT GWB - PAINTED
3	PAINT EXISTING CMU
4	
5	
6	
7	
8	
9	
BASE	
10	WOOD BASE
11	4" VINYL
12	RUBBER TREADS, RISERS AND LANDINGS
FLOORS	
20	POLISH EXISTING CONCRETE FLOOR
21	CLEAN AND SEAL EXISTING FLOOR TO MATCH EXISTING BREWERY
22	PLYWOOD - PAINTED - ANTI SLIP PAINT
23	
24	
25	
26	
27	
28	
CEILINGS	
30	PAINT EXISTING BEAMS, DECK AND JOISTS
31	GWB - PAINTED
32	WOOD CEILING - REFINISH
33	
34	

ROOM FINISH GENERAL NOTES

- ALSO SEE INTERIOR ELEVATIONS FOR GRAPHIC DEPICTION'S OF EXTENT OF FINISHES
- INSTALL MOISTURE RESISTANT (MOLD AND MILDEW RESISTANT) GWB IN ALL AREAS WHERE PLUMBING FIXTURES EXIST (CEILING AND WALLS IN BATHROOMS)
- CLOSETS SHALL BE FINISHED AS THE ROOMS THEY SERVICE
- ALL SPACES DESIGNATED AS CLOSET OR 'CL.' ARE TO RECEIVE ONE CLOTHING ROD 5'-2" AFF AND ONE 12" SHELF ABOVE THE ROD ALONG THE WALL OPPOSITE THE DOOR UNLESS NOTED OTHERWISE.
ALL SPACES DESIGNATED AS LINEN CLOSETS (LIN) OR PANTRY (PAN) ARE TO RECEIVE FOUR 12" SHELVES SPACED AT 1'-6" OC STARTING AT FINISH FLOOR, UNLESS NOTED OTHERWISE.
- PROVIDE APPROPRIATE BLOCKING IN WALLS OF ALL BATHROOMS BEHIND FIXTURES, PARTITIONS AND ACCESSORIES. PROVIDE BLOCKING FOR GRAB BARS IN WALLS OF BATHROOMS
- PROVIDE APPROPRIATE BLOCKING IN WALLS FOR DOOR STOPS
- PROVIDE APPROPRIATE BLOCKING IN WALLS FOR WALL HUNG CABINETS
- BOTTOM EDGE OF GWB ON WALL SURFACES TO BE HELD UP 1/2" FROM CONCRETE FLOOR SURFACES, FILL GAP WITH SEALANT
- PROVIDE VINYL TRANSITIONS STRIPS AT ALL FLOOR TRANSITIONS UNLESS OTHERWISE NOTED
- UNLESS OTHERWISE NOTED IN DRAWINGS THE TYPICAL WALL TYPE IS 'NA'. ALL OTHER PARTITION TYPES WILL BE INDICATED.
- VERIFY UNDERLAYMENT MEETS MANUFACTURERS SPECIFICATION AT RESILIENT FLOORING

PAINT NOTES	
1.)	XXXXX
2.)	
3.)	