DOOR NOTES:

1.) ALL EXTERIOR GLAZING TO BE LOW-E ARGON FILLED INSULATED GLAZING UNITS

2.) FRAME ALL OPENINGS WITH ELEVATIONS

3.) SEAL EXTERIOR DOORS TO ROUGH OPENING WITH LOW EXPANDING FOAM INSULATION - SEE DETAILS

4.) ALL DOOR HARDWARE TO BE 'LEVER' TYPE

5.) ALL EXTERIOR DOORS TO BE WEATHERSTRIPPED

A BARN DOOR

B INTERIOR FIRE ROLL UP DOOR

C

D

E

F

G

1 DOOR TYPES
1/4" = 1'-0"

FRAME TYPES:

1 WOOD CASED

2 STEEL

GLAZING SCHEDULE

KEY	GLAZING TYPE
GL-1	INSULATED CLEAR TEMPERED GLAZING
GL-2	FIRE RATED INSULATED GLAZING
GL-3	CLEAR TEMPERED GLASS
GL-4	CLEAR INSULATED TEMPERED GLASS
GL-5	FIRE RATED GLAZING

DOOR SCHEDULE

DOOR								FRAME						GENERAL			
		SIZE									DETAILS						
DOOR NO.	TYPE	WIDTH	HEIGHT	THICKNESS	MATERIAL	FINISH	INSULATED	TYPE	MATERIAL	THRESHOLD	HEAD	JAMB	SILL	CLOSER	FIRE RATING (MINUTES)	F.O.B. ACCESS	REMARKS
111,1	A	8'-0"	8'-0"	1 3/4"	WD	PTD	-	-	-	-	-	-	-	-	60	-	CUSTOM BARN DOOR WITH FULL HARDWARE PACKAGE
111,2	B	8'-0"	8'-0"	-	STL	PTD	-	-	STL	-	-	-	-	Y	60	-	FIRE RATED OVERHEAD ROLLING DOOR WITH AUTOMATIC CLOSER TIED TO FIRE ALARM SYSTEM WITH LASER EYE SAFTEY FEATURE, OVERHEAD DOOR MODEL 631, FUSEABLE LINK
111,3	EX	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	EXISTING EXTERIOR DOOR, REPLACE UPON OWNER DECISION
111,4	D	3'-0"	7'-0"	1 3/4"	AL	MA	-	-	AL	AL	-	-	-	Y	-	-	THERMALLY BROKEN STOREFRONT DOOR WITH PANIC AND LATCHING HARDWARE, MATCH EXISTING STOREFRONT DOOR
111,5	E	MA	MA	1 3/4"	AL	MA	Y	-	AL	-	-	-	-	Y	-	-	MATCH EXISTING EXTERIOR OVERHEAD DOOR, PROVIDE OPERATOR IF EXISITNG HAS ONE
111,6	C	3'-0"	7'-0"	1 3/4"	STL	PTD	-	2	STL	AL	-	-	-	Y	60	-	1 HR FIRE RATED DOOR WITH PANIC AND LATCHING HARDWARE
113,1	C	3'-0"	7'-0"	1 3/4"	STL	PTD	-	2	STL	AL	-	-	-	Y	60	-	1 HR FIRE RATED DOOR WITH PANIC AND LATCHING HARDWARE
113,2	C	3'-0"	7'-0"	1 3/4"	STL	PTD	-	2	STL	AL	-	-	-	Y	60	-	1 HR FIRE RATED DOOR WITH PANIC AND LATCHING HARDWARE
113,3	G	3'-0"	7'-0"	1 3/4"	STL	PTD	-	2	STL	-	-	-	-	Y	-	-	-
114,1	F	3'-0"	7'-0"	1 3/4"	STL	PTD	-	2	STL	-	-	-	-	-	-	-	-
115,1	G	3'-0"	7'-0"	1 3/4"	STL	PTD	-	2	STL	-	-	-	-	Y	-	-	-
116,1	F	3'-0"	7'-0"	1 3/4"	STL	PTD	-	2	STL	-	-	-	-	Y	-	-	-
213,1	C	3'-0"	7'-0"	1 3/4"	STL	PTD	-	2	STL	AL	-	-	-	Y	60	-	1 HR FIRE RATED DOOR WITH PANIC AND LATCHING HARDWARE

HARDWARE KEY
MLS - MORTISE LOCK SET
LS - LOCK SET
PR - PRIVACY SET
PS - PASSAGE SET
LP - LEVER PULL
PH - PEEPHOLE LENSE

MATERIALS KEY
AL - ALUMINUM
STL - STEEL
MTL - METAL
WD - WOOD

FINISH KEY
PTD - PAINTED
ANO - ANODIZED ALUMINUM
STN - STAINED

SUB-FLOOR ELEVATION

A GLIDER

B FIXED

2 WINDOW TYPES
1/4" = 1'-0"

3 TYPICAL WINDOW TRIM
NOT TO SCALE

WINDOW SCHEDULE LEGEND

T = TEMPERED GLASS

FG = FIBERGLASS

AL = ALUMINUM

DH = DOUBLE HUNG

AW = AWNING

LV = LOUVER

F = FIXED

GL = GLIDER

WINDOW SCHEDULE

KEY	ACTION	ROUGH ★ OPENING (WxH) VIF	R.O. HEAD HEIGHT FROM SUB-FLOOR	DETAILS			MATERIAL	FINISH	FOR TEMPERED GLASS LOCATIONS SEE WINDOW ELEVATION TYPES FOR MASONRY OPENING DIMENSIONS COORDINATE COURSING WITH EXTERIOR ELEVATION SHEETS AND PLAN AND SECTION DETAIL SHEETS REMARKS
				HEAD	JAMB	SILL			
A	GL	4' X 3'-4"	-	-	-	-	AL	PTD	THERMALLY BROKEN METAL WINDOW, MASONRY OPENING, HEAD HEIGHT PER SECTION DRAWING
B	F	5'-10" X 3'-4"	-	-	-	-	AL	PTD	INTERIOR METAL WINDOW HEAD HEIGHT PER SECTION DRAWING

WINDOW NOTES:

1.) COORDINATE AND ADJUST ROUGH OPENING DIMENSIONS TO ACCOMMODATE SILL PAN FLASHING SYSTEM

2.) ALL WINDOW UNITS AND MULTI-WINDOW UNIT COMBINATIONS TO MEET OR EXCEED DP-50 RATINGS FOR BOTH STRUCTURAL AND WATER

2.) PROVIDE MULL REINFORCING AT ALL MULTI-UNIT WINDOWS AS REQUIRED TO ACHIEVE DP-50 RATING, WITH INSTALLATION BRACKETS

3.) FULL SCREENS ALL OPENINGS

4.) CONTRACTOR TO VERIFY THAT ALL EGRESS OPENINGS MEET EGRESS REQUIREMENTS

5.) ALL GLAZING LOCATED WITHIN 18" OF FINISHED FLOOR TO BE TEMPERED GLASS

6.) ALL EXTERIOR GLAZING TO BE INSULATED

7.) FRAME ALL OPENINGS WITH ELEVATIONS

8.) SEAL WINDOW TO ROUGH OPENING WITH LOW EXPANDING FOAMINSULATION - SEE DETAILS

Reviewed for Code Compliance
Inspection Division
Date: 08/02/17

REGISTERED ARCHITECT
RYAN J. SENATORE
No. 3322
STATE OF MAINE

© 2017 RYAN SENATORE ARCHITECTURE

RISING TIDE BREWING - EXPANSION

103 FOX STREET
PORTLAND, MAINE 04101

RSA
RYAN SENATORE
ARCHITECTURE
565 CONGRESS STREET
PORTLAND, MAINE 04101
207-650-6414
senatorearchitecture.com

CONSULTANTS:

REVISIONS:

DATE:	MAY 12, 2017
PROJECT No.	1718
DRAWN BY:	JPF
CHECKED BY:	RJS
SCALE:	AS NOTED

SHEET TITLE:
WINDOW AND DOOR SCHEDULE

A7-0