



- GENERAL NOTES:**
1. FLOOR FINISHES IN SALES AREA, EXPOSED SLAB SHALL BE FILLED WITH SEAMANT COLOR TO BE DARK BROWN / BRONZE FINISH. JOINTS SHALL BE FILLED WITH BRONZE OR SETTING OF STONE.
  2. COORDINATE EPOXY FLOORING WITH FINAL EQUIPMENT LOCATIONS. EPOXY FLOORING SHALL ALIGN WITH CENTER OF EQUIPMENT AT MEAT, DAIRY, AND SEAFOOD AREAS. EPOXY FLOORING SHALL NOT BE FORCED IN FRONT OF EQUIPMENT TO TERMINATE AT SLAB EDGES AND COLUMN LINES.
  3. SECURE EQUIPMENT CASE COVERS AFTER EPOXY FLOOR FINISHES HAVE BEEN INSTALLED AND CURED.
- LEGEND:**
- CONTROL JOINT
  - THRU FINISH FLOOR
  - FLOOR FINISH GAP
  - EPOXY FLOOR
  - FINISH
  - EPOXY FLOOR
  - BLUESTONE WITH TUBESIDE EDGE
  - SCALED SQUARE TILE
  - SCORED SEALED CONCRETE FS-1
  - BRICK PAVERS

1 FIRST FLOOR PLAN - FLOOR FINISHES

