



1 MEZZANINE FRAMING PLAN
1/8" = 1'-0"



- NOTES
1. TOP OF SLAB ELEVATION = (+14'-0") ABOVE FINISH FIRST FLOOR SLAB ELEVATION UNLESS OTHERWISE NOTED.
 2. MEZZANINE FLOOR CONSTRUCTION: 5" THICK REINFORCED CONCRETE SLAB WITH 1-1/2" DIA. REINFORCING STEEL BARS @ 18" ON CENTER. SEE DETAIL 102-1 FOR REINFORCING DETAILS.
 3. TOP OF STEEL ELEVATION FOR MEZZANINE FLOOR IS (+14'-7") UNLESS OTHERWISE NOTED.
 4. FASTEN FLOOR BEAM TO STEEL FRAMING AS SHOWN IN TYPICAL DETAIL 102-2.
 5. (W) INDICATES NUMBER OF 3/4" x 4" x 4" SHEAR STUDS FOR COMPOSITE SLAB TO BEAM CONNECTION. SEE DETAIL 102-3 FOR ADDITIONAL REINFORCING OVER COMPOSITE BEAMS.
 6. (M) INDICATES MOMENT CONNECTION. SEE DETAILS 102-4 AND 102-5 FOR ADDITIONAL INFORMATION.
 7. STEEL FABRICATOR SHALL DESIGN ALL CONNECTIONS TO RESIST THE END REACTIONS INDICATED ON PLAN. REACTIONS NOT SHOWN SHALL BE FOR MANUAL AND TYPICAL MOMENTS.
 8. FOR LOCATIONS AND SIZES OF FLOOR PENETRATIONS, SEE ARCHITECTURAL, MECHANICAL, AND ELECTRICAL DRAWINGS.