


1 FIRST FLOOR PLAN



HVAC NOTES BY SYMBOLS

1. NEW FACTORY SUPPLIED CONCENTRIC TRANSMISSION AIR DISCHARGE ROOF MANUFACTURERS VENT LENGTH PARAMETERS AS DESCRIBED IN THE MANUFACTURERS VENT LENGTH PARAMETERS AS DESCRIBED IN THE MANUFACTURERS VENT LENGTH PARAMETERS AS DESCRIBED IN THE
2. NEW 8" OUTSIDE AIR DUCT UP ABOVE CEILING THRU EXTERIOR WALL PROVIDE VENT CAP MORE DUCT AS REQUIRED TO MAINTAIN A MINIMUM OF 10 FEET INSULATED LIQUID AND WATER LINES FROM EVAP COILS TO CONDENSERS.
3. FROM AS POSSIBLE CONNECTION TO VENT SIZE FOR CONDENSERS.
4. ROUTE TO NEAREST CONDENSATE STRAIGHT. SEE PLUMBING DINGS FOR LOCATIONS.
5. HEATING ONLY THERMOSTAT ON TSTAT WITH NOTATION

HVAC GENERAL NOTES

1. COORDINATE THE EXACT LOCATION OF CEILING MOUNTED AIR DEVICES WITH ARCH. REFLECTED CEILING PLAN.
2. AIRSTREAM DIMENSION REQUIREMENTS.
3. CONTRACTOR SHALL PROVIDE DUCTWORK WITHIN THE CEILING CLEARANCE ALLOWABLE.
4. CONTRACTOR TO REMOVE FIRE/SMOKE DAMPER AT ALL RATED LOCATIONS. NEW VENTS SHALL BE INSTALLED AT RATED LOCATIONS. SEE NEW REQUIREMENTS ON SHEET M004 FOR DUCT INSTALLATION.
5. MANUFACTURERS INSTALLATION REQUIREMENTS SHALL BE COMPATIBLE WITH DIFFUSER COLLAR DIMENSIONS.
6. COMPATIBLE WITH DIFFUSER COLLAR DIMENSIONS. DIV. 16 OR ABOVE 2000 CPM, WHEED BY DIV. 16.
7. COMPATIBLE WITH DIFFUSER COLLAR DIMENSIONS.
8. CONFIRM THAT ALL MECHANICAL EQUIPMENT MEETS LOCAL BUILDING, PERSON AND ENERGY CODES PRIOR TO PURCHASE.
9. ALL FEEDER DUCT RUNS SHALL NOT EXCEED 5'-0" IN LENGTH.
10. LOCATION FOR ALL ROOF MOUNTED EQUIPMENT CONTRACTOR TO PROVIDE A MINIMUM 10' CLEARANCE TO THE ROOF EDGE.
11. CONTRACTOR TO PROVIDE A MINIMUM 10' CLEARANCE TO THE ROOF EDGE.
12. CONTRACTOR TO PROVIDE A MINIMUM 10' CLEARANCE TO THE ROOF EDGE.
13. ALL OUTSIDE AIR SYSTEMS SHALL BE CONSTRUCTED OF STEEL. ALL SYSTEMS SHALL BE COVERED WITH A MINIMUM 1.5" INSULATION. INSULATION SHALL BE COVERED WITH A CALUM SLICER, THER INSULATION AND FROM DUCTWORK TO EXHAUST HOOD COLLARS.
14. CONTRACTOR TO PROVIDE ALL TRANSITIONS AND CONNECTIONS FROM DUCTWORK TO EXHAUST HOOD COLLARS.
15. CONTRACTOR TO PROVIDE ALL TRANSITIONS AND CONNECTIONS FROM DUCTWORK TO EXHAUST HOOD COLLARS.
16. CONTRACTOR TO PROVIDE ALL TRANSITIONS AND CONNECTIONS FROM DUCTWORK TO EXHAUST HOOD COLLARS.

2 ALTERNATE #1



HVAC GENERAL NOTES

1. CONTRACTOR TO PROVIDE A MINIMUM 10' CLEARANCE TO THE ROOF EDGE.
2. CONTRACTOR TO PROVIDE A MINIMUM 10' CLEARANCE TO THE ROOF EDGE.
3. CONTRACTOR TO PROVIDE A MINIMUM 10' CLEARANCE TO THE ROOF EDGE.
4. CONTRACTOR TO PROVIDE A MINIMUM 10' CLEARANCE TO THE ROOF EDGE.
5. CONTRACTOR TO PROVIDE A MINIMUM 10' CLEARANCE TO THE ROOF EDGE.
6. CONTRACTOR TO PROVIDE A MINIMUM 10' CLEARANCE TO THE ROOF EDGE.
7. CONTRACTOR TO PROVIDE A MINIMUM 10' CLEARANCE TO THE ROOF EDGE.
8. CONTRACTOR TO PROVIDE A MINIMUM 10' CLEARANCE TO THE ROOF EDGE.
9. CONTRACTOR TO PROVIDE A MINIMUM 10' CLEARANCE TO THE ROOF EDGE.
10. CONTRACTOR TO PROVIDE A MINIMUM 10' CLEARANCE TO THE ROOF EDGE.
11. CONTRACTOR TO PROVIDE A MINIMUM 10' CLEARANCE TO THE ROOF EDGE.
12. CONTRACTOR TO PROVIDE A MINIMUM 10' CLEARANCE TO THE ROOF EDGE.
13. CONTRACTOR TO PROVIDE A MINIMUM 10' CLEARANCE TO THE ROOF EDGE.
14. CONTRACTOR TO PROVIDE A MINIMUM 10' CLEARANCE TO THE ROOF EDGE.
15. CONTRACTOR TO PROVIDE A MINIMUM 10' CLEARANCE TO THE ROOF EDGE.
16. CONTRACTOR TO PROVIDE A MINIMUM 10' CLEARANCE TO THE ROOF EDGE.