



- NOTES**
1. ACCESS TO THE MEZZANINE SHALL BE THROUGH THE STAIRS. ALL ELECTRICAL WORK SHALL BE IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE (NEC) AND ALL LOCAL ORDINANCES. ALL ELECTRICAL WORK SHALL BE INSTALLED IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE (NEC) AND ALL LOCAL ORDINANCES. ALL ELECTRICAL WORK SHALL BE INSTALLED IN ACCORDANCE WITH THE NATIONAL ELECTRICAL CODE (NEC) AND ALL LOCAL ORDINANCES.
  2. THIS DRAWING SHOWS EQUIPMENT LOCATIONS ONLY. WIRING SHALL BE SHOWN IN A SEPARATE DRAWING. WIRING SHALL BE SHOWN IN A SEPARATE DRAWING. WIRING SHALL BE SHOWN IN A SEPARATE DRAWING.
  3. NOT USED.
  4. UNLESS NOTED OTHERWISE, ALL DIMENSIONS SHALL BE 1/4" = 1'-0". UNLESS NOTED OTHERWISE, ALL DIMENSIONS SHALL BE 1/4" = 1'-0". UNLESS NOTED OTHERWISE, ALL DIMENSIONS SHALL BE 1/4" = 1'-0".
  5. UNLESS NOTED OTHERWISE, ALL POWER WIRING OF CIRCUIT SHALL MATCH HARDWARE WIRING OF EQUIPMENT. UNLESS NOTED OTHERWISE, ALL POWER WIRING OF CIRCUIT SHALL MATCH HARDWARE WIRING OF EQUIPMENT. UNLESS NOTED OTHERWISE, ALL POWER WIRING OF CIRCUIT SHALL MATCH HARDWARE WIRING OF EQUIPMENT.
  6. ASSUMED WITH MECHANICAL CONTRACTOR. SEE MECHANICAL CONTRACTOR FOR FINAL LOCATION OF ALL DEVICES MOUNTED ON OR IN THE CEILING OF THE MECHANICAL WORK.
  7. NOT USED.
  8. HANG AND FINISHING EQUIPMENT REFER TO DRAWING E-11 AND E-12 FOR ADDITIONAL INFORMATION. COORDINATE FINAL LOCATION WITH MECHANICAL CONTRACTOR.
  9. NOT USED.
  10. PROVIDE 400-3/4" 3/4" CONDUIT INTERLOCK BETWEEN ALL 400-3/4" CONDUIT. PROVIDE 400-3/4" 3/4" CONDUIT INTERLOCK BETWEEN ALL 400-3/4" CONDUIT. PROVIDE 400-3/4" 3/4" CONDUIT INTERLOCK BETWEEN ALL 400-3/4" CONDUIT.
  11. PROVIDE #12 & #10 3/4" 3/4" INTERLOCK 1/2" DIA. AND NOTIFIED DAMPER WITH EXHAUST CONNECTIONS WITH MECHANICAL CONTRACTOR. COORDINATE WITH MECHANICAL CONTRACTOR.
  12. PROVIDE #12 & #10 3/4" 3/4" INTERLOCK 1/2" DIA. AND NOTIFIED DAMPER WITH EXHAUST CONNECTIONS WITH MECHANICAL CONTRACTOR. COORDINATE WITH MECHANICAL CONTRACTOR.
  13. COORDINATE WIRING AND CONDUIT IN MAIN-LEVEL COOLERS WITH RELATED WIRING SHOWN ON REFRIGERATION DRAWINGS AND DETAILS ON DRAWING E-10.
  14. REFER TO DRAWING E-10 FOR FURTHER INFORMATION REGARDING PANE FRAM.
  15. COORDINATE LOCATION OF OUTLET FOR REMOTE ENCLOSURES WITH ENERGY MANAGEMENT CONTRACTOR. REFER TO DRAWING E-10 FOR FURTHER INFORMATION.
  16. PROVIDE A BID ALTERNATE PRICE FOR 2" MINIMUM COVER CONCRETE ENCASEMENT OF THESE CONDUIT RISERS FROM FLOOR TO MEZZANINE LEVEL.

1 MEZZANINE LEVEL POWER FLOOR PLAN  
 1/08 - 1/10