

GENERAL DEMOLITION AND REMOVAL NOTES

THE DEMOLITION DRAWINGS PROVIDE GENERAL COORDINATION INFORMATION ONLY, AND ARE SCHEMATIC IN NATURE. THEY DO NOT IDENTIFY ALL INDIVIDUAL ITEMS TO BE REMOVED. REMOVE ANY EXISTING CONSTRUCTION WHICH IS IN THE WAY OF NEW CONSTRUCTION OR PROHIBITS THE NEW CONSTRUCTION. VERIFY EXISTING STRUCTURAL CONDITIONS PRIOR TO DEMOLITION OR REMOVALS PROTECT FROM DAMAGE AND WEATHER ANY EXISTING BUILDING COMPONENTS, WHICH ARE EXPOSED AS A RESULT OF DEMOLITION OR REMOVALS. COORDINATE AND SCHEDULE ALL WORK IN EXISTING OCCUPIED PORTIONS OF THE BUILDING WITH THE OWNER. NOTIFY THE ARCHITECT AND OWNER IMMEDIATELY UPON DISCOVERY OF POTENTIALLY HAZARDOUS MATERIAL OR SUBSTANCE NOT ADDRESSED IN THE CONTRACT DOCUMENTS, INCLUDING BUT NOT LIMITED TO ASBESTOS, PCB. LEAD. MERCURY, AND MOLD. DO NOT DISTURB HAZARDOUS MATERIALS. HAZARDOUS MATERIAL SHALL BE LEGALLY ABATED, TRANSPORTED, AND DISPOSED OF. CONCRETE SLAB REMOVALS MAY BE REQUIRED THROUGHOUT THE EXISTING BUILDING AND MAY NOT BE SHOWN ON THE DEMOLITION DRAWINGS. COORDINATE THE EXTENT OF SLAB REMOVALS WITH STRUCTURAL, MECHANICAL AND ELECTRICAL PLANS. CUT TRENCHES IN EXISTING CONCRETE FLOORS WITH NO MORE THAN A 1:2 SLOPE. PROVIDE AN UNDER-SLAB VAPOR RETARDER AT SLABS ON GRADE. REFER TO STRUCTURAL DRAWINGS FOR REINFORCEMENT REQUIREMENTS. PATCH CONCRETE TO MATCH ADJACENT THICKNESS AND FINISH PRIOR TO THE INSTALLATION OF UNDERLAYMENT OR NEW FINISHES. REMOVAL OF MATERIALS SHALL BE DONE WITHOUT DISTURBING ADJACENT SURFACES OR THE CURRENT CONDITION OF OTHER BUILDING ELEMENTS INTENDED TO REMAIN. THE OWNER SHALL REMOVE FURNITURE AND OTHER MOVABLE AND/OR FIXED EQUIPMENT PRIOR TO NEW WORK IN ANY AREA, EXCEPT FOR MECHANICAL, ELECTRICAL OR MINOR WORK NOT REQUIRING THE OWNER TO COMPLETELY VACATE THE PREMISES. NOTIFY THE OWNER OF THE SCHEDULE FOR NEW WORK AND EXTENT OF OWNER REMOVALS NECESSARY. REMOVE ALL DAMAGED AND/OR DISCARDED BUILDING CONSTRUCTION MATERIAL FROM CONCEALED SPACES. PRIOR TO CLOSING- OR SEALING-OFF CONCEALED SPACES, THE CONTRACTOR SHALL ALLOW FOR AN INSPECTION OF COMPONENTS WHICH WILL NOT BE VISIBLE WHEN THE SPACES HAVE BEEN SEALED. ALL DEMOLITION/REMOVAL DEBRIS IS THE PROPERTY OF THE CONTRACTOR, UNLESS NOTED OTHERWISE, AND SHALL BE LEGALLY DISPOSED OF.

COORDINATED WITH MEP DRAWINGS.

ELECTRICAL DEMOLITION AND REMOVAL NOTES			
1.	REMOVE AND DISCONNECT ALL EXISTING ELECTRIC, AREAS INDICATED, UNLESS OTHERWISE NOTED TO F LIGHTING FIXTURES, SWITCHES, RECEPTACLES, EXF CIRCUIT WIRING, SURFACE AND FLUSH DEVICE BOX ALL EXPOSED ABANDONED CONDUCTORS AND CON REMOVED. WHERE COMPLETE REMOVAL IS NOT POS WIRING FROM CONDUITS, CUT BACK, CAP AND ABAN REQUIRED. COORDINATE REMOVAL WITH ENGINEER		
2.	EXISTING ELECTRICAL EQUIPMENT NECESSARY FOR BUT PASSING THROUGH THE RENOVATED AREA, SHA REHUNG AND PROTECTED DURING CONSTRUCTION. ALL CONDUITS, BRANCH CIRCUITS AND FEEDERS PA RENOVATED AREAS AND SERVICING UNDISTURBED.		
3.	EXISTING CONDUIT FOUND TO BE REUSABLE MAY BE MATERIAL SHALL BE REMOVED FROM THE JOB SITE DIRECTED BY THE ENGINEER.		
4.	REMOVE EXISTING TELEPHONE WIRING AND BRANCH BEING REMOVED. COORDINATE DEMOLITION WITH C PRIOR TO REMOVAL.		
5.	ALL BRANCH CIRCUITS SHALL BE ROUTED TO EXISTI INDICATED ON THE CONSTRUCTION DRAWINGS OR A ENGINEER.		
6.	CONTRACTOR SHALL CARRY ALL COSTS RELATING T LAWFUL DISPOSAL OF ELECTRICAL EQUIPMENT, LIG WIRING AND ASSOCIATED DEVICES/HARDWARE. PRIO OF ELECTRICAL EQUIPMENT, CONTRACTOR SHALL OF FOR POSSIBLE SALVAGE OF ANY OF THE EQUIPMENT		
7.	THIS DRAWING HAS BEEN PREPARED TO ASSIST THE DEMOLITION WORK. CONTRACTOR IS TO VISIT THE S EXISTING CONDITIONS. NO EXTRA COMPENSATION OF BE PERMITTED BECAUSE OF LACK OF COMPLIANCE		
8.	THE ELECTRICAL CONTRACTOR SHALL TAKE INTO A BID, THE OBLIGATION TO PROVIDE FOR THE DISMAN MODIFICATION, OF EXISTING ELECTRICAL EQUIPMEN WIRING AND RELATED ITEMS FOR THEIR REPLACEMI HEREIN SPECIFIED OR AS MAY REASONABLY BE IMP		
MECHA	NICAL DEMOLITION AND REMOVAL NOTES		
1.	ALL HVAC, PLUMBING, FIRE PROTECTION GENERAL N DETAILS ARE TO BE CONSIDERED AS APPLICABLE TO FOR THIS PROJECT.		
2.	THE DRAWINGS ARE DIAGRAMMATIC IN NATURE AND ARRANGEMENTS OF EXIST./NEW EQUIPMENT, DUCTY COMPONENTS SHALL BE DETERMINED IN THE FIELD OF STRUCTURAL, ELECTRICAL AND ARCHITECTURAL STRUCTURAL SYSTEMS SHALL NOT BE MODIFIED WI		

- STRUCTURAL SYSTEMS SHALL NOT BE MODIFIED WITHOUT THE EXPRESS PERMISSION OF THE ENGINEER. THE PROJECT SHALL BE PHASED IN ACCORDANCE WITH THE APPROVED PHASING PLAN. THE CONTRACTOR SHALL OBTAIN APPROVAL FOR THE SEQUENCING AND TIMING OF OPERATIONS PRIOR TO COMMENCING WORK. SEE SPECIFICATIONS. CONTRACTOR IS TO MAINTAIN SERVICE TO ROOMS OUTSIDE THE PROJECT SCOPE OF WORK AND PHASING SCHEDULE. IF INTERRUPTION OF SERVICE IS REQUIRED COORDINATE SHUTDOWN. CARE SHALL BE TAKEN BY THE CONTRACTOR TO PROTECT EXISTING SYSTEMS AND SURFACES TO REMAIN. RESTORE DAMAGED AREAS THAT ARE
- BEYOND THE SCOPE OF THIS CONTRACT TO THEIR ORIGINAL CONDITION. WHERE INDICATED ON THE DRAWINGS, REMOVE OR RELOCATE EXISTING COMPONENTS AS REQUIRED TO ACCOMMODATE THE NEW WORK. REMOVALS SHALL INCLUDE ALL ASSOCIATED OFF-SITE DISPOSAL COSTS. COORDINATE REMOVALS AND RELOCATION'S INCLUDING SELECTIVE CUTTING AND PENETRATIONS WITH ARCHITECTURAL, MECHANICAL, STRUCTURAL AND
- ELECTRICAL CONTRACTORS. AT THE END OF EACH WORKING DAY, THE CONSTRUCTION SITE SHALL BE LEFT IN A CLEAN AND NEAT CONDITION. FIELD VERIFY EXISTING EQUIPMENT, DUCTWORK AND PIPING PRIOR TO REMOVAL OR REUSE. CONFIRM WITH OWNER THAT ALL EQUIPMENT,
- DUCTWORK AND PIPING DESIGNATED TO BE REMOVED IS NO LONGER IN SERVICE PRIOR TO ITS REMOVAL. EXISTING EQUIPMENT, DUCTWORK AND PIPING TO REMAIN IN SERVICE SHALL 10. BE INSPECTED. ANY EQUIPMENT FOUND TO BE INOPERABLE SHALL BE
- REPORTED TO THE PROJECT ENGINEER. INFILL ALL NEW OR EXISTING ABANDONED FLOOR SLAB PENETRATIONS WITH 11. GROUT, FULL THICKNESS OF SLAB. MAINTAIN 2 HR FIRE RATING. ALL EXISTING CONCRETE FLOORS AND CHASES ARE 2 HOUR FIRE RATED. FILL AND PATCH ALL OPENINGS IN WALLS WHERE CONDUITS, PIPES, DUCTS
- ETC. ARE OR HAVE BEEN REMOVED WITH UL LISTED FIRE ASSEMBLY APPROVED BY THE ARCHITECT. MAINTAIN 2 HR FIRE RATING WHERE APPLICABLE.
- ALL UNUSED (ABANDONED) DUCTWORK, PIPING AND EQUIPMENT INDICATED TO 13. BE REMOVED SHALL BE REMOVED AND CAPPED. TIE-IN POINT LOCATIONS ARE APPROXIMATE. CONTRACTOR SHALL DETERMINE EXACT LOCATIONS IN THE FIELD BASED ON EXISTING CONDITIONS.

PIPING ETC. TO BE LEFT IN SERVICE.

	DEMO NOTES		
KEY	DESCRIPTION		
1	DEMO WALLS AS INDICATED IN PLAN - TYP.		
2	DEMO FINISH FLOOR TO SLAB - TYP.		
3	DEMO COLUMN ENCLOSURE - FIRE PROOFING TO REN NECESSARY		
4	DEMO DOOR AND FRAME AS INDICATED IN PLAN - TYP.		
5	DEMO CASEWORK		
6	DEMO PLUMBING FIXTURES AS INDICATED IN PLANS - 1 PLUMBING		
7	DEMO GWB FINISH @ EXTERIOR WALLS UP TO A HEIGH EXISTING INSULATION FOR INSPECTION		
8	SELECTIVE DEMO OF WALL - PATCH AND REPAIR RATE RATINGS AS REQUIRED. AT TOIL. RM WALLS, REMOVE (WHERE PRESENT		
9	REMOVE OPERABLE WALL SYSTEM		
10	DEMO PARTITIONS AND TOIL. ROOM ACCESSORIES		
11	DEMO EXISTING CEILINGS TYP. U.N.O.		
12	DEMO EXISTING CEILING FIXTURES TYP. U.N.O.		
13	CEILING/FIXTURE TO REMAIN		
14	REMOVE WINDOW SYSTEM. REMOVE EXISTING CAULKI OPENING. REMOVE GWB WALL RETURN AT HEAD AND WOOD WINDOW SILL.		
15	REMOVE & SALVAGE MASONRY VENEER BELOW REMO BELOW JAMBS). SALVAGE 8X16 FACE BRICK AND JUMB BANDING FOR USE IN NEW INFILL WALL (SEE WALL TYF		
16	REMOVE & SALVAGE MASONRY VENEER BELOW NEW S FOR ROOF @ NEW ADDITION. SALVAGE 8X16 FACE BRI ACCENT BANDING FOR USE IN NEW INFILL WALL (SEE V A004)		
17	REMOVE EXTERIOR DOOR SYSTEM. SAWCUT AND REM INDICATED FOR NEW MASONRY OPENING. REPLACE EX NEW STEEL LINTEL. COORDINATE WITH SIZING OF NEW MASONRY FOR REUSE IF POSSIBLE.		

MASONRY FOR REUSE IF POSSIBLE. REMOVE CANOPY IN ITS ENTIRETY, INCLUDING MASONRY BASES, COLUMN 18 WRAPS, SOFFIT AND ROOF ASSEMBLY, LIGHTING, ROOF DRAIN, AND STEEL STRUCTURE.

GRAPHIC LEGEND - DEMOLITION

EXISTING WALL TO REMAIN		ARE/
WALL TO BE DEMOLISHED	(#)	
EXISTING FIRE RATED WALLS	(#)	DEM

