DOOR AND WINDOW NOTES

1. PACK MINERAL-FIBER INSULATION IN ALL INTERIOR HOLLOW METAL FRAMES IN STUD WALLS.

2. REFER TO SPECIFICATIONS FOR LOCATIONS OF TEMPERED, LAMINATED, WIRED, AND INSULATING GLASS.

3. PROVIDE DOOR STOPS TO PROTECT WALLS AT ALL LOCATIONS WHERE A DOOR SWING WILL STRIKE THE WALL.

4. CONFIRM EXISTING HARDWARE TYPE/ QUALITY OF "E" EXISTING DOORS TO REMAIN.



6E ALUM. HEAD/ JAMB SIM.
3" = 1'-0"



6D INTERIOR ALUMINUM SILL
3" = 1'-0"



5D ALUM SILL @ FLOOR
3" = 1'-0"



6C SLIDING WINDOW JAMB DETAILS
3" = 1'-0"



1C SECTION @ TRANSACTION COUNTER
3" = 1'-0"





3/18/2016 5:17:38 PM

ARCHITECTS
49 DARTMOUTH STREET
PORTLAND, MAINE 04101
207-775-1059
www.pdtarchs.com

Reviewed for Code Compliance Inspections Division Approved with Conditions
Date: 05/03/16

COPYRIGHT 2016
PDT Architects
Reuse or reproduction of the contents of this document is not permitted without written permission of PDT Architects.

PORTLAND GASTROENTEROLOGY CENTER

161 Marginal Way Portland, Maine

No.	Date	Description
Revision Schedule		

REGISTERED ARCHITECT ANN M. FONTAINE-FISHER NO.1439 STATE OF MAINE

JOB NO.
14054

DRWN. CHK
Checker

SCALE:

ISSUE
PERMIT SET
03/18/16

TITLE
DOOR AND BORROWED LIGHT DETAILS

SHEET
A602