


- NOTES FOR CONCRETE ENCASED DUCTBANKS:**
1. DUCTBANKS SHALL HAVE A MINIMUM THREE (3) SPACING BETWEEN CONDUITS.
 2. PROVIDE 3" CONCRETE ENCASEMENT AROUND PVC CONDUITS AT ALL ROAD AND DRIVEWAY CROSSINGS TO 5' BEYOND EDGE OF PAVEMENT TYPICAL.
 3. CONCRETE SHALL BE MINIMUM 3000 PSI COMPRESSIVE STRENGTH RATING. SLUMP SHALL BE 4 TO 6 INCHES AND CONCRETE SHALL BE WORKED IN TO COMPLETELY SURROUND CONDUITS. AGGREGATE SIZE: 3/4" STONE.
 4. BOTTOM OF TRENCH SHALL BE UNDISTURBED ORIGINAL GROUND OR FIRMLY COMPACTED EARTH FREE FROM VOILS, ROCK, RUBBLE AND OF RELATIVELY SMOOTH ARCH, AND LINED WITH A MINIMUM OF 2 INCHES OF CLEAN SAND.
 5. PVC CONDUIT SHALL BE PRIMED AND GLUED TO FORM A WATERTIGHT SEAL. TYPICAL.

DIG SAFE NOTE:
 UTILITIES ARE PLOTTED FROM FIELD LOCATION AND ANY RECORD INFORMATION AVAILABLE, AND SHOULD BE CONSIDERED APPROXIMATE. OTHER UTILITIES MAY EXIST WHICH ARE NOT EVIDENT OR FOR WHICH RECORD INFORMATION WAS NOT AVAILABLE. CONTRACTORS MUST CONTACT ALL UTILITY COMPANIES BEFORE EXCAVATING AND DRILLING. ALSO, CALL "DIG SAFE" AT 1 (888)344-7233 (1(888)NO SAFE) IN WA, ME, NH, RI AND, VT. DIG-SAFE WEBSITE: WWW.DIGSAFE.COM



Stantec Consulting Services Inc.
 460 Payne Road Scarborough Court
 Scarborough, ME 04074-8929
 Tel: (207) 883-3355 / Fax: (207) 883-3376
 www.stantec.com

No.	Date	Description
Revision Schedule		



JOB NO.
 195210863

DRWN: CHK:
 Author Checker

SCALE:

ISSUE:
 PERMIT SET - 95%
 CONSTRUCTION
 DOCUMENTS
 04.12.16

TITLE:
 ELECTRICAL SITE
 PLAN AND DETAILS

SHEET
 ES101