GENERAL NOTES:

1. ALL GLAZING SHALL BE TEMPERED.
2. ALL EXTERIOR DOORS AND FRAMES SHALL BE GALVANIZED STEEL.
3. KEYING SHALL BE COORDINATED WITH BUILDING OWNER AND TENANT.
4. ALL DOOR HARDWARE SHALL BE PROVIDED BY THE DOOR SUPPLIER. LOCK CYLINDERS SHALL BE PROVIDED AS PART OF DIVISION 08710 – FINISH HARDWARE.

REMARKS

1. DOOR HARDWARE AND ACTUATION DEVICES BY DOOR SUPPLIER.
2. DOOR AND ELECTRIC STRIKE SHALL BE PREPPED FOR FUTURE CARD ACCESS SYSTEM.
3. AUTOMATIC OPERATOR SHALL BE SET TO AUTOMATIC/MANUAL OPERATION.

ABBREVIATIONS

PWG = POLISHED WIRE GLASS
TEMP = TEMPERED GLASS
HM = HOLLOW METAL
IHM = INSULATED HOLLOW METAL
ST = STEEL
IST = INSULATED STEEL
OHD = OVER HEAD DOOR
AL = ALUMINUM
PLY = PVC COATED POLYESTER MONOFILAMENT
ISLD = INSULATED SLIDING DOOR
ISCL = INSULATED COOLER MAN–DOOR
SS = STAINLESS STEEL

DOOR SCHEDULE

DOOR NUMBER	DOOR WIDTH	DOOR HEIGHT	DOOR THICKNESS	DOOR MATERIAL	DOOR TYPE	FRAME MATERIAL	FRAME TYPE	FIRE RATING	MISC. DETAILS HEAD	MISC. DETAILS JAMB	MISC. DETAILS SILL
101	36	84	1 3/4	INSULATED HOLLOW METAL	F	HOLLOW METAL	A				
102	36	84	1 3/4	SOLID CORE WOOD	F	KNOCK DOWN HOLLOW METAL	D				
104	2@36	84	1 3/4	ALUMINUM STOREFRONT	2FG	ALUMINUM STOREFRONT	E				
105	2@36	84	1 3/4	ALUMINUM STOREFRONT –CURTAIN WALL	2FG	ALUMINUM STOREFRONT–CW	G				
106	24/36	84	1 3/4	SOLID CORE WOOD PAIR	2FNV	KNOCK DOWN HOLLOW METAL	C	60 MIN.			
107	36	84	1 3/4	HOLLOW METAL	F	HOLLOW METAL	D	45 MIN.			
109A	36	84	1 3/4	INSULATED HOLLOW METAL	F	HOLLOW METAL	A				
109B	36	84	1 3/4	SOLID CORE WOOD	FNV	HOLLOW METAL	D	60 MIN.			
115	36	84	1 3/4	INSULATED HOLLOW METAL	F	HOLLOW METAL	A				
116	36	84	1 3/4	SOLID CORE WOOD	HG	HOLLOW METAL	D				
117	36	84	1 3/4	SOLID CORE WOOD	HG	HOLLOW METAL	D				
201	24/36	84	1 3/4	SOLID CORE WOOD PAIR	2F	KNOCK DOWN HOLLOW METAL	C				
208	36	84	1 3/4	SOLID CORE WOOD	FNV	HOLLOW METAL	D	60 MIN.			
209	36	84	1 3/4	SOLID CORE WOOD	FNV	HOLLOW METAL	D	60 MIN.			
215	36	84	1 3/4	ALUMINUM STOREFRONT	FG	ALUMINUM STOREFRONT	F				

HARDWARE SCHEDULE

DOOR NUMBER	ITEM / LOCK FUNCTION	MANUFACTURER	MODEL NUMBER	FINISH	NOTES
	EXIT LATCH	SARGENT	8213 LNL	626	MORTISE LEVER – OFFICE/ENTRANCE
	LOCKSET NO.1	SARGENT	10G05LL	626	CYLINDRICAL LEVER – OFFICE/ENTRANCE
	LOCKSET NO. 2	SARGENT	8205 LNL	626	MORTISE LEVER – OFFICE/ENTRANCE
	TOP AND BOTTOM FLUSH BOLTS	IVES	358	626	INSTALL ON INACTIVE LEAF
	PASSAGE	SARGENT	10U15LL	626	CYLINDRICAL LEVER – OFFICE/ENTRANCE
	STOREROOM	SARGENT	8204 LNL	626	MORTISE LEVER – OFFICE/ENTRANCE
	PUSH / PULL	IVES	8102–8 PULL 8200 4X16 PUSH	626 626	
	PUSH / PULL	KAWNEER	STYLE T PULL STYLE V PUSH	626	INSTALL ON INACTIVE AND ACTIVE LEAVES
	TOP AND BOTTOM RAIL FLUSH BOLTS	KAWNEER		626	INSTALL ON INACTIVE LEAF
	DEAD BOLT	ADAMS RITE	MS1850S	626	INSTALL ON ACTIVE LEAF
	CLOSER 1 – PROVIDE ON EACH LEAF OF ALL PAIRS OF DOORS	SARGENT	1430/1431	626	ADJUST TO MEET ADA REQUIREMENTS. PROVIDE DELAYED ACTION AT DOORS NOTED. PROVIDE HOLD OPEN AS DOORS INDICATED.
	CLOSER 2 – PROVIDE ON EACH LEAF OF ALL PAIRS OF DOORS	SARGENT	281 SERIES	626	ADJUST TO MEET ADA REQUIREMENTS. PROVIDE DELAYED ACTION AT DOORS NOTED. PROVIDE HOLD OPEN AS DOORS INDICATED.
	WEATHER STRIPPING	PEMKO		626	
	DOOR BOTTOM SWEEP	PEMKO	345ZDP		
	BALL BEARING HINGES	HAGAR	FULL MORTISE	26D	PROVIDE BALL BEARING HINGES AT ALL DOORS W/ CLOSERS
		HAGAR	FULL MORTISE	26D	
	THRESHOLD	PEMKO	252x3	ALUM	THERMAL BARRIER. ADA COMPLIANT – MAX. HT 1/2"
	FLOOR STOP	IVES	436	ALUM	
	WALL STOP	IVES	406 1/2	ALUM	
	8x32 KICKPLATE	IVES	8400	SS	
	36x32 ARMOR PLATE	IVES	8400	SS	
	AUTOMATIC DOOR OPERATOR	DOOR–O–MATIC	SENIOR SWING		PROVIDE ON ACTIVE LEAF ONLY OF DOOR PAIRS
	H/C PUSH BUTTON ACTUATORS				
	MAGNETIC HOLD OPEN				TIE TO FIRE ALARM SYSTEM
	24 VOLT ELECTRIC STRIKE				

REMARKS

CWS Architects
454 Cumberland Avenue
Portland, ME 04101
Phone: (207) 774-4441
Fax: (207) 774-4016
www.CWSarch.com

MULTI-TENANT OFFICE BUILDING
155 MARGINAL WAY
PORTLAND, MAINE
04101

Owner:
FIVE LIVER COMPANY
5 MILK STREET
PORTLAND, MAINE
04112
207-772-6404

REVISIONS
Date:
Description:

Drawing Title:
DOOR & DOOR HARDWARE SCHEDULE
Scale: AS NOTED
Date: Progress 6/21/04
CWS Proj. No.: 04122.1L

Drawing Number:
A4.1

A DOOR & DOOR HARDWARE SCHEDULE SCALE: NTS
REFERENCED FROM:

ISSUED FOR PERMITTING