

# Technical Specifications



Vitodens 100-W wall-mounted gas condensing boiler

<b>Model</b>	WB1B	<b>26</b>	<b>35</b>
<b>Rated input</b>	MBH	37 - 91	37 - 118
<b>Altitude Levels</b>	ft.	up to 10,000	up to 10,000
<b>Dimensions</b>			
Width x Height x Depth	in.	15.75 x 28.5 x 14.13	
<b>Weight</b>	lbs	78	78



Optional Combi**PLUS** Kit for on-demand DHW

<b>Connected to Model</b>	WB1B	<b>26</b>	<b>35</b>
<b>DHW Supply Temperature</b>	°F / °C	140 / 60	140 / 60
<b>Continuous Draw Rate</b>	USG/h	156 <sup>†</sup>	216 <sup>†</sup>
<b>Dimensions</b>			
Width x Height x Depth	in.	17 x 8.7 x 9.8	
<b>Weight</b>	lbs	25	25
<b>Min./Max. distance between boiler and CombiPLUS</b>	in.	11.5 / 36	11.5 / 36

<sup>†</sup> At a 63 °F maximum temperature rise.



Vitodens 200-W wall-mounted gas condensing boiler

<b>Model</b>	B2HA	<b>19</b>	<b>28</b>	<b>35</b>	<b>45</b>	<b>60</b>	<b>80</b>	<b>100</b>	<b>112</b>	<b>150</b>
<b>Rated Input</b>	MBH	12-67	19-100	19-125	60-160	60-212	104-285	104-352	113-399	113-530
<b>Dimension</b>										
Width	in.	17.75	17.75	17.75	19	19	19	19	23.63	23.63
Height	in.	41	41	41	40.63	40.63	43.5	43.5	44.5	44.5
Depth	in.	14	14	14	15	15	21	21	27.1	27.1
<b>Weight</b>	lbs	101	106	106	155	155	194	194	298	298



Vitodens 222-F gas condensing boiler and DHW heating

<b>Model</b>	B2TA	<b>19</b>	<b>35</b>
<b>Rated input</b>	MBH	12 - 67	19 - 125
<b>Max. Allowable Working Pressure</b>	psig	45	45
<b>Dimensions</b>			
Width x Height x Depth	in.	23.5 x 64 x 23.63	
<b>Weight</b>	lbs	282	282
<b>DHW Storage Tank</b>			
Capacity	USG	26.5	26.5
Max. Allowable Working Pressure	psig	150	150
Continuous Draw Rate*	gpm	1.8	3.3
Max. Draw Rate* (over 10 min. period)	USG	44	60

\* Based on a temperature rise of 70 °F (50 °F to 120 °F).