

### OUTDOOR UNIT SCHEDULE

TAG	AREA SERVED	NOM. TONS	COOLING *		HEATING **		CONDENSER FAN		CRANKCASE HT'R		ELECTRIC			REFRIGERANT			WEIGHT LBS	REMARKS
			BTU	KW	BTU	KW	QUAN.	CFM	QUAN.	WATTS	POWER	MCA	TYPE	LIQUID	SUCTION			
CCU-1	B.C. CONTROLLER #1	14.0	168,000	14.97	188,000	15.02	2	14,100	0.38 EA.	2	5T EA.	208V-60-3P	58	R410A	1/8	1/8	1,090	STAND MOUNTED
CCU-2	B.C. CONTROLLER #2	17.0	204,000	18.71	228,000	18.65	2	14,100	0.38 EA.	2	5T EA.	208V-60-3P	72	R410A	1/8	1/8	1,090	STAND MOUNTED
CCU-3	B.C. CONTROLLER #3	18.0	216,000	19.42	240,000	21.03	2	14,100	0.38 EA.	2	5T EA.	208V-60-3P	77	R410A	1/8	1/8	1,090	STAND MOUNTED
CCU-4	B.C. CONTROLLER #4	14.5	234,000	21.62	268,000	23.11	2	14,100	0.38 EA.	2	5T EA.	208V-60-3P	83	R410A	1/8	1/8	1,090	STAND MOUNTED
CCU-5	B.C. CONTROLLER #5	14.5	234,000	21.62	268,000	23.11	2	14,100	0.38 EA.	2	5T EA.	208V-60-3P	83	R410A	1/8	1/8	1,090	STAND MOUNTED
CCU-6	B.C. CONTROLLER #6	14.5	234,000	21.62	268,000	23.11	2	14,100	0.38 EA.	2	5T EA.	208V-60-3P	83	R410A	1/8	1/8	1,090	STAND MOUNTED
CCU-7	B.C. CONTROLLER #7	18.0	216,000	19.42	240,000	21.03	2	14,100	0.38 EA.	2	5T EA.	208V-60-3P	77	R410A	1/8	1/8	1,090	STAND MOUNTED
CCU-8	B.C. CONTROLLER #8	14.5	234,000	21.62	268,000	23.11	2	14,100	0.38 EA.	2	5T EA.	208V-60-3P	83	R410A	1/8	1/8	1,090	STAND MOUNTED
CCU-9	B.C. CONTROLLER #9	14.0	168,000	14.97	188,000	15.02	2	14,100	0.38 EA.	2	5T EA.	208V-60-3P	58	R410A	1/8	1/8	1,090	STAND MOUNTED

\* COOLING OPERATING RANGE OF 23 DEG. F. TO 104 DEG. F. \*\* HEATING OPERATING RANGE OF -4 DEG. F. TO 60 DEG. F. CONFIRM REFRIGERANT PIPE SIZING WITH ACTUAL JOB CONDITIONS AND MFR'S RECOMMENDATIONS

### B.C. CONTROLLER SCHEDULE

TAG	AIR HANDLERS SERVED	POWER	COOLING KW	HEATING KW	MCA	MAXIMUM BRANCHES	REFRIGERANT TYPE	WEIGHT LBS
BCC-1	01 -> 04, 30, 31 & 50	208V-60-1P	0.178	0.060	1.34	8	R410A	84
BCC-2	05 -> 07, 04, 44, 45, 58 & 61	208V-60-1P	0.112	0.053	0.85	8	R410A	84
BCC-3	21, 28, 31 & 54 -> 57	208V-60-1P	0.112	0.053	0.85	8	R410A	84
BCC-4	34 -> 36, 41 -> 43	208V-60-1P	0.112	0.053	0.85	8	R410A	84
BCC-5	08, 32, 33, 37 -> 40, 53, 63	208V-60-1P	0.112	0.053	0.85	13	R410A	126
BCC-6	13, 14, 18, 22, 23 & 25	208V-60-1P	0.112	0.053	0.85	8	R410A	84
BCC-7	10 -> 12, 16, 17, 21 & 26	208V-60-1P	0.112	0.053	0.85	8	R410A	84
BCC-8	15, 19, 20, 24 & 46	208V-60-1P	0.112	0.053	0.85	8	R410A	84
BCC-9	47, 48, 44, 51 & 60	208V-60-1P	0.112	0.053	0.85	8	R410A	84



### AIR HANDLER SCHEDULE

TAG	AREA SERVED	NOM. TONS	CFM	FAN KW	ELECTRIC		COOLING *		HEATING **		REFRIGERANT			WEIGHT LBS	REMARKS
					POWER	MCA	BTU	KW	BTU	KW	TYPE	LIQUID	GAS		
AH-01	101 CONFERENCE	2.50	740	0.10	230V-60-1P	1.34	30,000	0.021	34,000	0.210	R410A	3/8	5/8	86	HORIZONTAL DUCTED
AH-02	102 CONFERENCE	2.50	740	0.10	230V-60-1P	1.34	30,000	0.021	34,000	0.210	R410A	3/8	5/8	86	HORIZONTAL DUCTED
AH-03	103 I.T. OFFICE	3.00	980	0.14	230V-60-1P	1.85	36,000	0.240	40,000	0.240	R410A	3/8	5/8	115	HORIZONTAL DUCTED
AH-04	103 I.T. OFFICE	1.50	490	0.07	230V-60-1P	0.91	18,000	0.150	20,000	0.150	R410A	1/4	1/2	75	HORIZONTAL DUCTED
AH-05	106 CORRIDOR	0.50	300	0.08	230V-60-1P	0.77	6,000	0.120	6,700	0.012	R410A	1/4	1/2	51	HORIZONTAL DUCTED
AH-06	113 HALL	0.50	300	0.08	230V-60-1P	0.77	6,000	0.120	6,700	0.012	R410A	1/4	1/2	51	HORIZONTAL DUCTED
AH-07	115 & 116 MANAGERS	0.50	300	0.08	230V-60-1P	0.77	6,000	0.120	6,700	0.012	R410A	1/4	1/2	51	HORIZONTAL DUCTED
AH-08	117, 118 & 119 MANAGERS	0.67	300	0.08	230V-60-1P	0.77	8,000	0.120	9,000	0.012	R410A	1/4	1/2	51	HORIZONTAL DUCTED
AH-09	120 CONFERENCE	0.67	300	0.08	230V-60-1P	0.77	8,000	0.120	9,000	0.012	R410A	1/4	1/2	51	HORIZONTAL DUCTED
AH-10	130 MANAGER	0.50	300	0.08	230V-60-1P	0.77	6,000	0.120	6,700	0.012	R410A	1/4	1/2	51	HORIZONTAL DUCTED
AH-11	131 - 134 MANAGERS	2.00	620	0.10	230V-60-1P	1.04	24,000	0.170	27,000	0.170	R410A	3/8	5/8	86	HORIZONTAL DUCTED
AH-12	124 OPERATIONS	4.00	1,100	0.14	230V-60-1P	2.44	48,000	0.340	54,000	0.340	R410A	3/8	5/8	115	HORIZONTAL DUCTED
AH-13	124 OPERATIONS	4.00	1,100	0.14	230V-60-1P	2.44	48,000	0.340	54,000	0.340	R410A	3/8	5/8	115	HORIZONTAL DUCTED
AH-14	124 OPERATIONS	4.00	1,100	0.14	230V-60-1P	2.44	48,000	0.340	54,000	0.340	R410A	3/8	5/8	115	HORIZONTAL DUCTED
AH-15	124 OPERATIONS	4.00	1,100	0.14	230V-60-1P	2.44	48,000	0.340	54,000	0.340	R410A	3/8	5/8	115	HORIZONTAL DUCTED
AH-16	218 PROGRAMMING	4.00	1,100	0.14	230V-60-1P	2.44	48,000	0.340	54,000	0.340	R410A	3/8	5/8	115	HORIZONTAL DUCTED
AH-17	218 PROGRAMMING	4.00	1,100	0.14	230V-60-1P	2.44	48,000	0.340	54,000	0.340	R410A	3/8	5/8	115	HORIZONTAL DUCTED
AH-18	214 PROGRAMMING	4.00	1,100	0.14	230V-60-1P	2.44	48,000	0.340	54,000	0.340	R410A	3/8	5/8	115	HORIZONTAL DUCTED
AH-19	214 PROGRAMMING	4.00	1,100	0.14	230V-60-1P	2.44	48,000	0.340	54,000	0.340	R410A	3/8	5/8	115	HORIZONTAL DUCTED
AH-20	214 PROGRAMMING	4.00	1,100	0.14	230V-60-1P	2.44	48,000	0.340	54,000	0.340	R410A	3/8	5/8	115	HORIZONTAL DUCTED
AH-21	124 EXTERIOR ZONE	3.00	980	0.14	230V-60-1P	1.85	36,000	0.240	40,000	0.240	R410A	3/8	5/8	115	HORIZONTAL DUCTED
AH-22	124 EXTERIOR ZONE	4.00	1,100	0.14	230V-60-1P	2.44	48,000	0.340	54,000	0.340	R410A	3/8	5/8	115	HORIZONTAL DUCTED
AH-23	124 EXTERIOR ZONE	3.00	980	0.14	230V-60-1P	1.85	36,000	0.240	40,000	0.240	R410A	3/8	5/8	115	HORIZONTAL DUCTED
AH-24	124 EXTERIOR ZONE	4.00	1,100	0.14	230V-60-1P	2.44	48,000	0.340	54,000	0.340	R410A	3/8	5/8	115	HORIZONTAL DUCTED
AH-25	228 & 229 MANAGERS	0.50	300	0.08	230V-60-1P	0.77	6,000	0.120	6,700	0.012	R410A	1/4	1/2	51	HORIZONTAL DUCTED
AH-26	230 & 231 MANAGERS	0.50	300	0.08	230V-60-1P	0.77	6,000	0.120	6,700	0.012	R410A	1/4	1/2	51	HORIZONTAL DUCTED
AH-27	125 EMPLOYEE LOUNGE	4.00	1,100	0.14	230V-60-1P	2.44	48,000	0.340	54,000	0.340	R410A	3/8	5/8	115	HORIZONTAL DUCTED
AH-28	125 EMPLOYEE LOUNGE	4.00	1,100	0.14	230V-60-1P	2.44	48,000	0.340	54,000	0.340	R410A	3/8	5/8	115	HORIZONTAL DUCTED
AH-29	203, 204 & 205 OFFICES	3.00	980	0.14	230V-60-1P	1.85	36,000	0.240	40,000	0.240	R410A	3/8	5/8	115	HORIZONTAL DUCTED
AH-30	202 OPEN OFFICE	4.00	1,100	0.14	230V-60-1P	2.44	48,000	0.340	54,000	0.340	R410A	3/8	5/8	115	OMITTED
AH-31	202 OPEN OFFICE	4.00	1,100	0.14	230V-60-1P	2.44	48,000	0.340	54,000	0.340	R410A	3/8	5/8	115	HORIZONTAL DUCTED
AH-32	123 SALES	3.00	980	0.14	230V-60-1P	1.85	36,000	0.240	40,000	0.240	R410A	3/8	5/8	115	HORIZONTAL DUCTED
AH-33	123 SALES	3.00	980	0.14	230V-60-1P	1.85	36,000	0.240	40,000	0.240	R410A	3/8	5/8	115	HORIZONTAL DUCTED
AH-34	123 SALES	3.00	980	0.14	230V-60-1P	1.85	36,000	0.240	40,000	0.240	R410A	3/8	5/8	115	HORIZONTAL DUCTED
AH-35	123 SALES	4.00	1,100	0.14	230V-60-1P	2.44	48,000	0.340	54,000	0.340	R410A	3/8	5/8	115	HORIZONTAL DUCTED
AH-36	123 EXTERIOR ZONE	4.00	1,100	0.14	230V-60-1P	2.44	48,000	0.340	54,000	0.340	R410A	3/8	5/8	115	HORIZONTAL DUCTED
AH-37	123 EXTERIOR ZONE	4.00	1,100	0.14	230V-60-1P	2.44	48,000	0.340	54,000	0.340	R410A	3/8	5/8	115	HORIZONTAL DUCTED
AH-38	232 & 233 MANAGERS	0.50	300	0.08	230V-60-1P	0.77	6,000	0.120	6,700	0.012	R410A	1/4	1/2	51	HORIZONTAL DUCTED
AH-39	216 FINANCE	4.00	1,100	0.14	230V-60-1P	2.44	48,000	0.340	54,000	0.340	R410A	3/8	5/8	115	HORIZONTAL DUCTED
AH-40	216 FINANCE	4.00	1,100	0.14	230V-60-1P	2.44	48,000	0.340	54,000	0.340	R410A	3/8	5/8	115	HORIZONTAL DUCTED
AH-41	216 FINANCE	4.00	1,100	0.14	230V-60-1P	2.44	48,000	0.340	54,000	0.340	R410A	3/8	5/8	115	HORIZONTAL DUCTED
AH-42	216 FINANCE	4.00	1,100	0.14	230V-60-1P	2.44	48,000	0.340	54,000	0.340	R410A	3/8	5/8	115	HORIZONTAL DUCTED
AH-43	234 MANAGER	0.50	300	0.08	230V-60-1P	0.77	6,000	0.120	6,700	0.012	R410A	1/4	1/2	51	HORIZONTAL DUCTED
AH-44	100 LOBBY	4.00	1,100	0.14	230V-60-1P	2.44	48,000	0.340	54,000	0.340	R410A	3/8	5/8	115	HORIZONTAL DUCTED
AH-45	100 LOBBY	3.00	980	0.14	230V-60-1P	1.85	36,000	0.240	40,000	0.240	R410A	3/8	5/8	115	HORIZONTAL DUCTED
AH-46	143 LOBBY	3.00	980	0.14	230V-60-1P	1.85	36,000	0.240	40,000	0.240	R410A	3/8	5/8	115	HORIZONTAL DUCTED
AH-47	143 LOBBY	3.00	980	0.14	230V-60-1P	1.85	36,000	0.240	40,000	0.240	R410A	3/8	5/8	115	HORIZONTAL DUCTED
AH-48	143 LOBBY	3.00	980	0.14											