

GENERAL NOTES

1. THE FOLLOWING NOTES ARE INTENDED TO BE USED AS OUTLINED SPECIFICATIONS FOR THIS PROJECT. THE REFERENCED STANDARDS ARE CONSIDERED TO BE PART OF THE WORK.
2. ALL DIMENSIONS AND CONDITIONS MUST BE VERIFIED IN THE FIELD. ANY DISCREPANCIES SHALL BE BROUGHT TO THE ATTENTION OF THE ARCHITECT BEFORE PROCEEDING WITH THE AFFECTED PART OF THE WORK.
3. THE REPLACEMENT GRANITE PANEL AND THE SURROUNDING EXISTING GRANITE ARE DESIGNED TO BE SELF SUPPORTING AND STABLE ONLY AFTER THE STRUCTURAL WORK CONTAINED IN THE STRUCTURAL DRAWINGS IS COMPLETED. IT IS THE CONTRACTOR'S SOLE RESPONSIBILITY TO DETERMINE ERECTION PROCEDURES, PROJECT SHORING AND SEQUENCE TO ENSURE THE SAFETY OF THE BUILDING, THE EXISTING FACADE AND ITS COMPONENTS DURING ERECTION.
4. BASED ON A LIMITED FIELD REVIEW, THE EXISTING GRANITE PANELS LOCATED ABOVE THE PANEL TO BE REPLACED ARE UNDERSTOOD TO BE "STACKED", AND THEREFORE SHORING OF THE PANELS ABOVE THE REPLACEMENT PANEL WILL BE REQUIRED. A SHORING LOAD IS INDICATED ON DRAWING S1. A CONCEPTUAL SHORING ELEVATION IS SHOWN ON S2. CONTRACTOR SHALL PROVIDE SHORING CALCULATIONS SIGNED AND SEALED BY A STRUCTURAL ENGINEER LICENSED IN THE STATE OF MAINE.
5. ALL APPLICABLE FEDERAL, STATE, AND MUNICIPAL REGULATIONS SHALL BE FOLLOWED, INCLUDING THE FEDERAL DEPARTMENT OF LABOR OCCUPATIONAL SAFETY AND HEALTH ACT (OSHA).

MATERIALS

1. GRANITE STONE PANEL: MATCH EXISTING WITH PANEL COMPLYING WITH ASTM C615. SUBMIT SAMPLE NOT LESS THAN 6"x6x1" FOR OWNER REVIEW AND APPROVAL PRIOR TO FABRICATION.
2. SEALANT: SIKAFLEX 1A BY SIKA. PROVIDE ALL ACCESSORIES AND INSTALL PER MANUFACTURER'S INSTRUCTIONS.
3. ADHESIVE ANCHORS: HY70 ADHESIVE, HAS-R STAINLESS STEEL RODS AND ASSOCIATED ACCESSORIES BY HILTI NORTH AMERICA. INSTALL PER MANUFACTURER'S REQUIREMENTS.
4. PLASTIC SHIMS:
 - 4.1. BEARING: "VERS-A-SHIM" BY DESLAURIERS OR EQUIVALENT WITH MINIMUM COMPRESSIVE STRENGTH OF 10,000 PSI
 - 4.2. AT CONNECTIONS: "KEY SLOT ECON-O-SHIM" BY DESLAURIERS OR EQUIVALENT WITH MINIMUM COMPRESSIVE STRENGTH OF 10,000 PSI
5. GROUT: NON-SHRINK, NON-METALLIC CEMENT BASED GROUT, HARRIS CONSTRUCTION GROUT OR 5 STAR GROUT



PPL - CAR IMPACT REPAIR
PORTLAND, ME

NOTES

Designed ARW	Scale AS NOTED
Drawn ARW	Date 12/12/14
Checked EAR	Becker Job Number 3452

S0