Location of Construction:	Owner: The Metre Gr	oup	*	Phone:		Permit No: 970442
Owner Address:	Lessee/Buyer's Name:	Pho	e:	Busines	sName:	PERMIT ISSUED
Contractor Name:	Address:	rham, MF				Permit Issued: MAY 3 1997
Past Use:	Proposed Use:		OF WOI	RK:	PERMIT FEE: \$ 25.00	
Restaurant	Sune	FIRE I		Approved Denied	INSPECTION: Use Group: Type:	Zone: CBL:
Proposed Project Description: Make Interior Renovations			PEDESTRIAN ACTIVITIES DISTRICT (P.A.D.) Action: Approved			☐ Shoreland
Permit Taken By:	Date Applied For:	1 Nay 199	7			☐ Site Plan maj ☐minor ☐mm ☐
2. Building permits do not include plumbin 3. Building permits are void if work is not stoom may invalidate a building permit and I hereby certify that I am the owner of record authorized by the owner to make this application if a permit for work described in the application areas covered by such permit at any reasonable.	CERTIFICATION of the named property, or that the proposed wition as his authorized agent and I agree to come is issued, I certify that the code official's	vork is autho onform to all authorized r	ized by t applicab presenta	the owner of ole laws of the tive shall har	is jurisdiction. In addition,	□ Denied
SIGNATURE OF APPLICANT Ed Poley	ADDRESS:	DA	Hay 1 E:	997	PHONE:	
RESPONSIBLE PERSON IN CHARGE OF W	/ORK, TITLE				PHONE:	CEO DISTRICT
White	e-Permit Desk Green-Assessor's Can	ary-D.P.W.	Pink-P	ublic File	vory Card-Inspector	SINA - I

431 Congress Street -18 ft. Wall will be fromed with Metal Stute (No Electrical Units)
Proposed WALL Door and Sheefret. Gradudian (Kithen) Soor

BUILDING PERMIT REPORT

DATE:	ADDRESS: (1.8 (an) to see
REASON FOR PERMIT:	chan of of
BUILDING OWNER:	11.11.1
CONTRACTOR:	
PERMIT APPLICANT:	APPROVAL: 4/ *6 *1.6 *1.7 *1.8 *1.9 *24 25 26 22 DENIED

CONDITION(S) OF APPROVAL

- 1. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.
 - 2. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection)
- 3. Precaution must be taken to protect concrete from freezing.
- 4. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
- 5. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than I-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996)

 4. All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA
 - All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993) U.L. 103.
 - 7. Guardrail & Handrails A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect.
 - 8. Headroom in habitable space is a minimum of 7'6".
 - 9. Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group minimum 11" tread. 7" maximum rise.
 - 10. The minimum headroom in all parts of a stairway shall not be less than 80 inches.
 - Every sleeping room below the fourth story in buildings of use Groups R and 1-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. Ω.
 - 12. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units.
 - 13. All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors with self-closer's
 - 14. The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment.
 - 15. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 19, 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
 - In the immediate vicinity of bedrooms
 - In all bedrooms
 - In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required)

A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. The Fire Alarm System shall be maintained to NFPA #72 Standard. The Sprinkler System shall maintained to NFPA #13 Standard. All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 1024. Of the City's building code. (The BOCA National Building Code/1996) 20. All construction and demolition debris must be disposed at the City's authorized reclamation site. The fee rate is attached. Proof of such disposal must be furnished to the office of Inspection Services before final Certificate of Occupancy is issued or demolition permit is granted. 21. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year". 22. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services. 23. (24) (25) (26) This permit does not excuse the applicant from obtaining any license which may be needed from the City Clerk's office. Ventilation shall meet the requirements of Chapter 12 Sections 1210, of the City's Building Code. All electrical and plumbing permits must be obtained by a Master Licensed holders of their trade. Ventitation Shall as stated in The City's Mechanical Code ChauTer 5 Code /1993 MAINTaine rules and regulations SIGNAGE Includina neserva TION P. Samuel Hoffses, Chief of Code Enforcement ce: Li. McDougall/PFD Marge Schmuckal DANdreng SP.