

Certificate of Flame Resistance

WCLZ stage, WPAK stage, Coast stage, Bull Feeney's



REGISTERED APPLICATION CONCERN No.

F-06901

ISSUED BY

HERCULITE PRODUCTS, INC.
PO BOX 435
EMIGSVILLE PA 17318

Date Work Performed

5/19/09

-000-0000

This is to certify that the materials described on the reverse side hereof have been flame-retardant treated (or are inherently nonflammable).

FOR TRI VANTAGE, LLC AT 2937 WEST 25th STREET

CITY CLEVELAND STATE OHIO 44113

Certification is hereby made that: (Check "a" or "b")

(a) The articles described on the reverse side of this Certificate have been treated with a flame-retardant chemical approved and registered by the State Fire Marshal and that the application of said chemical was done in conformance with the laws of the State of California and the Rules and Regulations of the State Fire Marshal.

Name of chemical used _____ Chem. Reg. No. _____

Method of application _____

(b) The articles described on the reverse side hereof are made from a flame-resistant fabric or material registered and approved by the State Fire Marshal for such use.

Trade name of flame-resistant fabric or material used REINFRCD VINYL Reg. No. F-06901

The flame Retardant Process Used WILL NOT Be Removed By Washing (will or will not)

PETER COHEN
Name of Production Superintendent

By STEPHANIE MUMMERT, Q C MANAGER
Title

We hereby certify this to be a true copy of the original "CERTIFICATE OF FLAME RESISTANCE" issued to us, "original copy" of which has been filed with the California State Fire Marshal.

TRI VANTAGE, LLC

By Thony R. Bell

Control/lot # _____

Quantity 50.000 YD

Customer order # MARK _____

Description WEBLON CP2707-62 PORTLIGHT RED

Tri Vantage, LLC Invoice # 39143403 _____

Product Code 857207

MAINE AWNING & CANVAS
404 ELM ST
NEWPORT ME 04953

DISPATCH STAGE

Certificate of Flame Resistance

REGISTERED
FABRIC
NUMBER

Issued by

TOPTec, INC.

1905 N.E. Main Street
Simpsonville, SC 29681

Date Manufactured

11/03/04



F53501

*This is to certify that the materials described
are inherently flame retardant.*

Name A-PLUS RENTAL

Address 342 US RT 1

City SCARBOROUGH

ME

State

04074

Zip

Certification is hereby made that:

The articles described are flame-retardant, approved and registered by the State Fire Marshal and that the fabric is in conformance with the laws of the State of California and the Rules and Regulations of the State Fire Marshal. Fabric has been tested and passes NFPA 701-96, CPAI84, ULC109, MVSS302.

Method of Application: The Flame Retardency of this Fabric is Inherent and Permanent.

20x30

PARTY

Description of item certified: WHITE

The Flame Retardant Process Used WILL NOT Be Removed By Washing.

TOPTec, INC.

MODEL TTP203000

SERIAL # 244046B

Name of Production Superintendent

MIA M M STAGE



CALIFORNIA DEPARTMENT OF FORESTRY and FIRE PROTECTION
OFFICE OF THE STATE FIRE MARSHAL

REGISTERED FLAME RESISTANT PRODUCT

Product:

PRECONSTRAINT 702 BLACKOUT

Registration No.

F-14408

Product Marketed By:

FERRARI SA
BK54,38352 LA TOUR DU PIN
LA TOUR DU PIN, FRANCE

This product meets the minimum requirements of flame resistance established by the California State Fire Marshal for products identified in Section 13115, California Health and Safety Code.

The scope of the approved use of this product is provided in the current edition of the **CALIFORNIA APPROVED LIST OF FLAME RETARDANT CHEMICALS AND FABRICS, GENERAL AND LIMITED APPLICATIONS CONCERNS** published by the California State Fire Marshal.

Pet Sweeney

Deputy State Fire Marshal


Expire: 06/30/2004

FR-9



PRINTED WITH SOY INK





DIVERSIFIED

TESTING LABORATORIES, INC.

"We Test Per Your Request"

336 WEST FRONT STREET
P.O. BOX 4004
BURLINGTON, NORTH CAROLINA 27215
Phone (336) 227-7710 • Fax (336) 227-1175

January 9, 2003

Ms. Catherine MERILLON
FERRARI SA
BP 54
38352 La Tour Du Pin Cedex
La Mure, France

Reference: Laboratory Test Report
Lab Identification No. 5349
Invoice No. 8270 (Attached)

Dear Ms. MERILLON:

One (1) fabric sample, identified as PRECONTRAIN 702, was received and tested in accordance with the National Fire Prevention Association No. 701, "Flame Propagation of Textiles and Films, 1999 Edition, (Test 2, Large Scale)". The results are as follows:

<u>Specimen Number</u>	<u>Afterflame (seconds)</u>	<u>Residual Flame (seconds)</u>	<u>Char Length (inches)</u>
Single 1	0.0	0.0	10.0
Flat 2	0.0	0.0	11.0
Specimen 3	0.0	0.0	11.0
4	0.0	0.0	10.0
5	0.0	0.0	10.0
6	0.0	0.0	10.0
7	0.0	0.0	12.0
8	0.0	0.0	7.0
9	0.0	0.0	10.0
10	0.0	0.0	8.0

The sample submitted meets the minimum requirements of the above standard. The length of char on the individual single flat specimens shall not exceed 17.1 inches. Additionally, no specimen shall continue flaming for more than two (2) seconds after the test flame is removed and no residue shall fall to the floor of the test chamber and continue flaming for more than two (2) seconds at any time during the test.

If there are any questions or when we can be of further assistance, please let us know.

Sincerely,

Karon S. Matkins
Karon S. Matkins

KSM/mr
Attachment

OUR LETTERS AND REPORTS ARE FOR THE EXCLUSIVE USE OF THE CLIENT TO WHOM THEY ARE ADDRESSED. ANY COMMUNICATION TO OTHERS OR THE USE OF OUR COMPANY NAME MUST RECEIVE PRIOR APPROVAL. OUR TEST RESULTS APPLY ONLY TO THE SAMPLE TESTED AND ARE NOT NECESSARILY INDICATIVE OF THE QUALITIES OF APPARENTLY IDENTICAL OR SIMILAR PRODUCTS. SAMPLES NOT DESTROYED IN TESTING ARE DETAINED A MAXIMUM OF THIRTY DAYS. THE LETTERS, REPORTS OR NAME OF DIVERSIFIED TESTING LABORATORIES, INC. MAY NOT BE USED IN ADVERTISING TO THE GENERAL PUBLIC.

