Marhsall Austin Map 24 Specifications

FEATURES

WATER RESISTANT AND FIRE RETARDANT CANOPY. BACKDROP, SIDEWALLS, AND SKIRTING

Keep your performers safe and dry with a canopy that covers the entire main floor plus an additional foot front and rear.

EQUIPMENT COMPARTMENTS / SPLASH GUARDS

Have all the items you need (adapters, bulbs and more) under secure lock and key. 6.25 cubic feet of welded, 120 thick polished aluminum tred plate, fulllength stainless steel hinge and tee handle turn locks.

ELECTRICAL DISTRIBUTION

The stage is equipped with a 125-amp 220/110v load center with eight independent circuits. A 50-amp twist lock is also included.

LEVELING AND STABILIZER JACKS

A patented feature of the stage, the 7,000 lb. capacity jacks are drop leg and crank adjustable, allowing you to level the stage on uneven surfaces.

A COMPLETE TOWING PACKAGE

Including a 7,000 lb, capacity tandem axle with electric brakes (all wheels), a two inch 5,000 capacity ball-type coupler, two 10,000 pound capacity safety chains, breakaway brakes, reflectors, brake lights and more. All stages comply with DOT and NHTSA requirements.

STAGE EXTENSIONS

Lightweight and sturdy 4' X 4' extensions attach to stage frame or each other for maximum stability. Two aluminum fold-up legs permit fine and coarse adjustments for easy set up.

WINCH ASSEMBLE

The winch is manual and does not require outside or on-board power to raise the roof. The patented singlewinch mechanism allows the canopy to rise to a tendegree slope (front to back) and helps shed water and maintain the great looking slope roof design.

BANNER PACKAGE

Maximize your advertising and revenue stream by selling sponsorship space on the stage or by leveraging your own brand to it's fullest. The Banner Package features a special aluminum attachment that affixes to the stage to support a 32 ft x 4 ft Valance Banner and two 4 ft x 12.5 ft vertical side banners. Marshall Austin can place your graphics, size them appropriately and output your banners for any sponsor or event.

ROLLING BILLBOARD PACKAGE

Take your brand on the road with the Rolling Billboard Package to promote your city, your company, your events or your sponsors. We reproduce your artwork



into large, durable, custom decals that are affixed to interchangeable aluminum side panels. You can easily switch the panels to feature different signage as your advertising needs change. It's more that just your stage it's your rolling billboard.

MOVIE-IN-THE-PARK-PACKAGE

Convert the Marshall Austin Mobile Stage into an outdoor theater with the Movie-in-The-Park Package - the only adaptable stage conversion on the market. The Movie-in-The-Park Package includes a large venue projector and a 24 ft. x 13.5 ft movie screen. The movie screen easily mounts to the front of the stage. And with our remote screen controller, you are ready to go in minutes!

TOWING DIMENSIONS

Overall length: (including hitch 28 ft. 7 in.) Stage length: 24 ft. Stage width: 8 ft. 5.5 in. Overall height: 9 ft. 5.5 in.

PERFORMANCE DIMENSIONS

Stage floor: 24 ft. X 16 ft. Stage height (from ground): 44 in.

MAXIMUM FRONT CANOPY

Height from floor: 12 ft. 6 in. **MAXIMUM REAR CANOPY**

Height from floor: 9 ft. 6 in.

WEIGHT

Gross vehicle weight: 4,240 lbs. Hitch tongue load (empty): 350 lbs.

ALLOWABLE LOADS

Stage floor load: 100 psf

TENT TOP LOADING

Single side loaded: 1640 lbs. Both sides loaded: 2800 lbs.

WIND SPEED

Maximum wind speed: 50-60 mph Maximum uplift on roof: 13 psf



ON AND OFF ROAD

WITH TRUE TRACK ENGINEERING

TRUE TRACK ENGINEERING combines a custom Stageline chassis with multiple hinged panels and telescoping structures that will not alter in performance from mileage and bad roads. True Track results in excellent road handling and safety year after year.



COMPACT TRAILER TO FULL PERFORMANCE STAGE

The Stageline SL50 short trailer design features an easy application for event site challenges. The SL50 is simple to drive into place and can be hand positionned. Spring loaded stabilisers help you turn a road vehicle into the base of a Stageline mobile stage. It's fast, it's simple and it's dependable.



A ROOF WITH FULL WEATHER PROTECTION AND LOAD BEARING CAPACITY

The Stageline SL50 fiberglass roof is raised with one easy operation of the 12v remote controlled power lifting mechanism. Several welded aluminium I-beam air-frame structures make rigging capacity possible. Specially designed I-beam clamps are provided to install rigging pipes and/or trusses anywhere in the roof. Sound rigs can weigh up to 375 lb per side. The SL50 roof is strong, watertight and wind resistant.



Stage Floor: 20' x 16' Roaf lifting capacity: 200 lb Roof max load capacity: 2,500 lb Wings load bearing capacity: 375 lb Sound rig height: (max) 15' l Roof rig height: (from seck) 11' to 9'5' Deck height: 3'2''

ALL STANDARD EQUIPMENT TRAVELS IN ONE TRALER UNIT:

Decks rated at 100lb / sq. ft.

Roof: Therelass bended to aluminum.

2 sound rigging extensions: 375 ta.

per age, accept line array system.

2 sound wing areas: 8 x 16 w/ guardia.

1 rooflop banner support up to 21 x.

2 lateral harrays supports: 3 x 11

Skirming Cover-freds

1 dairway with handrails 1 Ramp 10 w. hadr windwall

Mesh Black backdrop

OPTIONAL

Tailared windwalls, scrim or men

RENTAL AVAILABILITY AND PRICING UPON REQUEST PLEASE CONTACT ROBBIE SNOW • ROBBIE@PRODUCTIONSERVICESOFMAINE.COM • 207-358-9327