



1 THIRD FLOOR PLATFORM FRAMING PLAN
3/16" = 1'-0"

TYPICAL FLOOR CONSTRUCTION:
23/32" STURD-I-FLOOR (24/0) OSB
PLACED PERPENDICULAR TO
SUPPORTING MEMBERS GLUED &
NAILED w/ 8d RING SHANK NAILS AT
10" O.C. TO SUPPORTING MEMBERS
AND AT 6" O.C. AT EDGES. EACH
STURD-I-FLOOR PANEL SHALL
HAVE A 1/8" GAP ALL AROUND.

SEE DRAWING S103
FOR FRAMING NOTES

Date: 04/19/16		Scale: 3/16" = 1'-0"		Revisions:	
THIRD FLOOR PLATFORM FRAMING PLAN		FOUNDATION PERMIT		05/16/16	
		80% REVIEW DRAWINGS		06/07/16	
		100% STRUCTURAL DRAWINGS		06/24/16	
		100% CONSTRUCTION DRAWINGS		07/20/16	
Project: LUMINATO		Architect: ARCHETYPE architects		Consulting Engineer: VEITAS engineers	
Newbury Street Portland, Maine		48 Union Wharf Portland, Maine 04101		68 Granite Street, Suite 101 Portland, Maine 04104 Tel: (707) 668-7444 Fax: (707) 668-2905	
Prepared For: NewHeight Group		118 Congress Street, Unit 401 Portland, Maine			
S103A					