



LIMITS OF LOWER FLOOR FOR OUTSIDE DECK (-6').

LIMITS OF LOWER FLOOR FOR OUTSIDE DECK (-6').

TYPICAL FLOOR CONSTRUCTION:  
 23/32" STURD-I-FLOOR (24/0) OSB  
 PLACED PERPENDICULAR TO  
 SUPPORTING MEMBERS GLUED &  
 NAILED W/ 6d RING SHANK NAILS AT  
 10" O.C. TO SUPPORTING MEMBERS  
 AND AT 6" O.C. AT EDGES. EACH  
 STURD-I-FLOOR PANEL SHALL  
 HAVE A 1/8" GAP ALL AROUND.

SEE DRAWING S105  
 FOR FRAMING NOTES

**1 FIFTH FLOOR PLATFORM FRAMING PLAN**  
 3/16" = 1'-0"

**S105A**

Date: 04/19/16  
 Scale: 3/16" = 1'-0"  
**FIFTH FLOOR  
 PLATFORM FRAMING  
 PLAN**

Revisions:	05/16/16	FOUNDATION PERMIT
	06/07/16	80% REVIEW DRAWINGS
	06/24/16	100% STRUCTURAL DRAWINGS
	07/20/16	100% CONSTRUCTION DRAWINGS

Project: **LUMINATO**  
 Newbury Street Portland, Maine

Architect: **ARCHETYPE architects**  
 48 Union Wharf Portland, Maine 04101  
 (207) 775-6022 ARCHETYPE@ARCHETYPEPA.COM

Consulting Engineer: **VEITAS VEITAS engineers**  
 638 Granite Street, Suite 101  
 Portland, Maine 04103  
 TEL: (207) 866-8868 FAX: (207) 866-2805

Prepared For: **NewHeight Group**  
 118 Congress Street, Unit 401  
 Portland, Maine