APPLICATION FOR AMENDMENT TO PERMIT

Amendment No.



Portland, Maine, _____

To the INSPECTOR OF BUILDINGS, PORTLAND, MAINE 01 April 1998 028-N-009 The undersigned hereby applies for amendment to Permit No. 980178 pertaining to the building or structure comprised in the original application in accordance with the Laws of the State of Maine, the Building Code and Zoning Ordinance of the City of Portland, plans and specifications, if any, submitted herewith, and the following specifications: 115 Middle St ____ Within Fire Limits? _____ Dist. No. Owner's name and address Brothers Three LLC 111 Commercial ST Ptld Telephone Lessee's name and address _ Telephone __ Contractor's name and address Monaghan Woodworks Telephone _____ Architect Bill Nemmers 424 Fore St Ptld, ME 04101 774-3683 Plans filed Office Bldg Proposed use of building ____ Same Last use ____ 67,000.00 380.00 Increased cost of work____ Description of Proposed Original permit for leasee on 1st floor only. Tenant has now. expanded into second floor portion of building. Make Interior Renovations. Bill Nemmers Call Bill Nemmers for Pick-Up Details of New Work Is any plumbing involved in this work? ______ Is any electrical work involved in this work Height average grade to top of plate _____ Height average grade to highest point of Re Size, front depth No. stories solid or filled land? earth or Material of foundation ______ Thickness, top _____ bottom ____ Material of underpinning_____ ____ Height__ Kind of roof Rise per foot Roof covering No. of chimneys _____ Material of chimneys ____ of lining Framing lumber — Kind ______ Dressed or full size? ____ Corner posts _____ Sills ____ Girt or ledger board? _____ Size Girders_____Size ____Columns under girders_____Size ____ Max. on centers Studs (outside walls and carrying partitions) 2x4-16" O.C. Bridging in every floor and flat roof span over 8 f. " 1st floor ______, 2nd ______, 3rd ______, roof _____ Joints and rafters: 1st floor ______, 2nd ______, 3rd ______ roof On centers: _____, 2nd ______. 3rd___ 1st floor _ roof ... Maximum span: Signature of Dumer

INSPECTION COPY - WHITE APPLICANT'S COPY — YELLOW FILE COPY - PINK ASSESSOR'S COPY - GOLDEN

Approved

of Buildings





CITY OF PORTLAND

June 2, 1998

William Nemmers 424 Fore Street Portland, ME 04101

Re: 115 Middle Street, Change of Use

Dear Mr Nemmers:

On May 21, 1998 the Portland Planning Authority granted minor site plan approval for a change of use from vacant to office space at 115 Middle Street.

The approval is based on the submitted site plan. If you need to make any modifications to the approved site plan, you must submit a revised site plan for staff review and approval.

Please note the following provisions and requirements for all site plan approvals:

- 1. The site plan approval will be deemed to have expired unless work in the development has commenced within one (1) year of the approval or within a time period agreed upon in writing by the City and the applicant. A one year extension may be granted by this department if requested by the applicant in writing prior to the expiration date of the site plan.
- 2. Prior to construction, a preconstruction meeting shall be held at the project site with the contractor, development review coordinator, Public Work's representative and owner to review the construction schedule and critical aspects of the site work. At that time, the site/building contractor shall provide three (3) copies of a detailed construction schedule to the attending City representatives. It shall be the contractor's responsibility to arrange a mutually agreeable time for the preconstruction meeting.
- 3. If work will occur within the public right-of-way such as utilities, curb, sidewalk and driveway construction, a street opening permit(s) is required for your site. Please contact Carol Merritt at 874-8300, ext. 8828. (Only excavators licensed by the City of Portland are eligible.)

O:\PLAN\CORRESP\SECRETAR\FORMS\MINORSP.WPD

BUILDING PERMIT REPORT

DATE: 14 APRI 98 ADDRESS: 115 MIDGLE ST, 028-N-009
REASON FOR PERMIT: Amend Perm, T # 980128 To Second Floor -
BUILDING OWNER: Brothers Three 46C
CONTRACTOR: Monaghan Woodworks
PERMIT APPLICANT: B.11 Nemmer S
USE GROUP BOCA 1996 CONSTRUCTION TYPE 3B
CONDITION(S) OF APPROVAL

This Permit is being issued with the understanding that the following conditions are met:

Approved with the following conditions: * (*8 *9 *10 *11 *14 *17 *20 *22 *24, *26 *27 *29 *30_

- This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.
- Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection)
- Precaution must be taken to protect concrete from freezing.
- It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
- 5 Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996)
- All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993).
- Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214 0 of the city's
- Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36" In occupancies in Use Group A, B, H-4, I-1, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 34" but not more than 38" Use Group R-3 shall not be less than 30", but not more than 38".) Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than
- Headroom in habitable space is a minimum of 7'6"
- **⊀**9 **⋌**10. Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group minimum 11" tread. 7" maximum rise.
- X 11 The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6' 8")
 - Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one operable window or 12. exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft.
 - Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it 13 exits directly from the apartment to the building exterior with no communications to other apartment units.
- All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors with self *11 closer's (Over 3 stories in height requirements for fire rating is two (2) hours.)
 - The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing 15. automatic extinguishment.
 - All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the 5

provisions of the City's Building Code Chapter 9, Section 19, 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):

- In the immediate vicinity of bedrooms
- In all bedrooms
- In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required)

- X 17 A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type.
 - 18 The Fire Alarm System shall be maintained to NFPA #72 Standard.
 - 19 The Sprinkler System shall maintained to NFPA #13 Standard.
- X-20. All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 1024. Of the City's building code. (The BOCA National Building Code/1996)
 - 21 Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year"
- X 22. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.
 - Ventilation shall meet the requirements of Chapter 12 Sections 1210. Of the City's Building Code.
- All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade.
 - All requirements must be met before a final Certificate of Occupancy is issued.
- All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code. (The BOCA National Building Code/1996).
- Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993).

Please read and implement the attached Land Use-Zoning report requirements.

28 X29. An exit access shall not pass Through a room subject to Locking,

X30. Fire escapes shall Meet The requirements setforth under Section 1025,0 OF The CITY'S 31

Hoffses Code Enforcement

cc: Lt McDougall, PKP Marge Schunuckal

32