Submittal Data: ASU7RLF



Job Name:		Location	:					
Purchaser:								71 - 14 - 14 - 14 - 14 - 14 - 14 - 14 -
Engineer:		makayarin maameey ya ah ah ah ay ah ah ah a	****					
Submitted To:		For:		Reference		Approval		Construction
Submitted By:			-,					
Unit Designation: Schedule No.		Model No.:						
Capacities:								
Cooling	7,000 BTU/h			OUTLIN	IE AN	ID DIMEN	SION	IS
Outdoor Design Temp. Fo DB/WB	95/75							
Heating	8,100 BTU/h							
Outdoor Design Temperature Fo DB/WB	47/43		-	31	-1/16			
HSPF						Acceptance		8
Ducted	9.3							
Non-Ducted	9.8	1/16						
Mixed	9.5	11-1/16						
SEER			LE			(),		113
Ducted	14.7							
Non-Ducted	17.0							
Mixed	15.8	S	tand	ard Featur	es:			
EER Cooling		•	Sev	ven year comp	ressor	warranty		
Ducted	8.7	•	Fiv	e year parts v	varranty	7	•	
Non-Ducted	9.25			-	-			
Mixed	8.97	•		gital wireless:				
Voltage/Frequency/Phase	208-230/60/1	•		to Louver: U	-			
Indoor Unit:		*	Ap	ple Catechin /	Ion De	eodorizing Fil	ters	
Noise Level Cooling db (A) - H/ M/ L/ Q	37/33/29/25	•	Sle	ep Timer				
Noise Level Heating db (A) - H/ M/ L/ Q	37/33/29/25	•	Au	to Restart/Re	set			
Weight	18 lbs.	•	24	hour timer				
Refrigerant Piping:*		•	Qu	iet Mode				
Discharge Vapor Line (O.D.)	1/4 in.	•	Dry	y mode				
Suction (O.D.)	3/8 in.	•	Rei	frigerant R410)A			
Notes:								
				Y				
2								

^{*}Piping lengths vary by outdoor unit. See outdoor unit submittal sheet for detailed specifications.

